

# **2012 IEEE 9th International Conference on Group IV Photonics**

**(GFP 2012)**

**San Diego, California, USA  
29 – 31 August 2012**



**IEEE Catalog Number: CFP12GFP-PRT  
ISBN: 978-1-4577-0826-8**

# TABLE OF CONTENTS

**Wednesday, August 29, 2012**

## **PLE Plenary Session**

PLE1	Future Photonics Convergence on Si	1
PLE2	TBD	N/A

## **WA Silicon Waveguides**

WA1	Heralded Single Photons from Silicon Coupled-Resonator Optical Waveguides	3
WA2	Measurement of Nonreciprocal Stimulated Raman Scattering in Silicon Photonic Wires	6
WA3	Silicon PIN Quasi-Continuous Wave Terahertz Emitter	9
WA4	Mid-Infrared Photonic Crystal Waveguides in SOI	12
WA5	Submicron Silicon Waveguides and Optical Splitters for Mid-Infrared Applications	15
WA6	Si-Wire MZI Optical Isolator Fabricated by Direct Bonding	18
WA7	Single-Band Add-Drop Filters Using Anti-Reflection, Contra-Directional Couplers	21
WA8	Low Mode Volume Slotted Photonic Crystal Single Nanobeam Cavity in Silicon	24

## **WB Design and Process Optimization**

WB1	Is There a Need for on-Chip Photonic Integration for Large Data Warehouse Switches	27
WB2	IPKISS: A Parametric Design and Simulation Framework for Silicon Photonics	30
WB3	Spatially Resolved Measurement of Free-Carrier Absorption in Silicon Waveguides	33
WB4	Ultra-Low-Loss Silicon Based Spot-Size Converter Fabricated by CMOS Compatible Process	36
WB5	Ultralow-Loss Silicon Ring Resonators	39
WB6	Accurate Post-Fabrication Trimming of Silicon Resonators	42
WB7	High Capacity, Photo-trimmable Athermal Silicon Waveguides	45

## **WC Student Paper Competition**

WC1	High-Speed Avalanche Photodiodes Using III-V Nanopillars Monolithically Grown on Silicon	48
WC2	Epitaxial III-V-on-Silicon Waveguide Butt-Coupled Photodetectors	51
WC3	Widely Wavelength Tunable Hybrid III-V/Silicon Laser with 45 nm Tuning Range Fabricated Using a Wafer Bonding Technique	54
WC4	High Linear Ring-Assisted MZI Electro-Optic Silicon Modulators Suitable for Radio-over-Fiber Applications	57
WC5	High Speed Electro-Absorption Modulator based on Quantum-Confined Stark Effect from Ge/SiGe Multiple Quantum Wells	60

WC6	Silicon Multi-Project Wafer Platforms for Optoelectronic System Integration	63
WC7	Silicon-on-Insulator 100um-Core Multimode Interferometer Waveguides for Two-Dimensional Microparticle Trapping and Manipulation	66
WC8	Photothermal Optical Switching in Ultra-Compact Hybrid Si-VO <sub>2</sub> Ring Resonators	69
WC9	1.53μm Electroluminescence of Erbium Excited by Hot Carriers in ErRE (RE=Yb, Y) Silicates	72
<b>WP</b>	<b>Poster Session I</b>	
WP1	Robust 4-Channel WDM Demultiplexing Filter Based on Collectively Tuned Silicon Microrings	75
WP2	Electrically Tunable Resonant Filters in Phase-Shifted Contra-Directional Couplers	78
WP3	1.55 μm Electroluminescence from Strained n-Ge Quantum Wells on Silicon Substrates	81
WP4	Improvement in Leakage Characteristics of Ge-on-Si Photodetectors	84
WP5	Monolithic Suspended Membrane Ring Resonator for Mid-infrared Applications	87
WP6	High Efficiency Grating Couplers based on CMOS Poly-Silicon Gate Layer	90
WP7	Si Waveguide Wavelength Filters Using High-Order-Mode Selection by Waveguide Coupler	93
WP8	Sub-fF Nanophotodetector for Efficient Waveguide Integration	96
WP9	Gain-Assisted Hybrid Silicon Microring Electro-Absorption Modulators	99
WP10	Highly Efficient Coupling Between a Nanocavity and Monolithic Bus Waveguide	102
WP11	Designing Short Tapered Waveguide Adapters for Ge Lasers and Ge/SiGe Modulators Integrated with SOI Waveguides	105
WP12	Silicon-based Photonic Ring Resonators for Optical OFDM Demultiplexing	108
WP13	Single Trench Waveguide TE-TM Mode Converter Fabricated with SiON	111
WP14	Integrated Silicon Photonic Temperature Sensors Based on Bragg Reflectors with Asymmetric Fano Lineshapes	114
WP15	Accurate Chromatic Dispersion Characterization of Nanophotonic Waveguides with Thermal Phase Noise Cancellation	117
WP16	A CMOS Compatible Metallised Nanofocusing Coupler	120
WP17	A Temperature Sensor Based on Silicon Eye-like Microring with Sharp Asymmetric Fano Resonance	123
WP18	Numerical Analysis of Strained SiGe-based Carrier-Injection Optical Modulators	126
WP19	12.5 Gb/s Carrier-Injection Silicon Mach-Zehnder Optical Modulator with High Optical Bandwidth	129
WP20	Double Resonance 1-D Glass-on-Silicon Photonic Crystal Cavities for Single-Molecule Mid-Infrared Photothermal Spectroscopy: Theory and Design	132
WP21	Electroluminescence of Unstrained and Tensile Strained Ge-on-Si LEDs	135
WP22	Temperature Dependence of Ge Quantum Well Light Emitting Diode on Si Substrate	138

WP23	The Improvement Effect of Carrier Injection by Ag Nanoparticles on the Electroluminescence of SiNx-based LEDs	141
WP24	Improvement of SiGe MOS Interfaces by Plasma Post-Nitridation for SiGe High-k MOS Optical Modulators	144
WP25	Si-ncs Size Distribution Induced Inhomogeneous Linewidth Broadening and Lifetime Dispersion	147
WP26	Low-Loss Low-Crosstalk Silicon Rib Waveguide Crossing with Tapered Multimode-Interference Design	150

## Thursday, August 30, 2012

### ThA Devices and Integration

ThA1	A Complete CMOS Photonics Platform for sub-pJ/bit Macrochip Interconnects	N/A
ThA2	Hybrid Integration of Coherent Receivers for Terabit Ethernet on SOI Waveguide PLC	153
ThA3	16 Channel Receiver with 20 GHz Ge Photodiodes	156
ThA4	Performance of Parallel 4x25 Gbs Transmitter and Receiver Fabricated on SOI Platform	159
ThA5	250 Gbps 10-Channel WDM Silicon Photonics Receiver	162
ThA6	Compact Silicon Differential Receiver with Integrated Zero Biased Balanced Detection	165

### ThB Design Competition

ThB1	Modeling and Simulation of Large-Scale Photonic Integrated Circuits Including Radiation	168
ThB2	A Novel Spot Size Convertor for Hybrid Integrated Light Sources on Photonics-Electronics Convergence System	171
ThB3	Silicon/Silica-Hybrid Delay Line Interferometer for DPSK Demodulation	174
ThB4	Compact Broadband Directional Coupler	177
ThB5	Bragg Grating based Fabry-Perot Filters for Characterizing Silicon-on-Insulator Waveguides	180
ThB6	High Efficiency Grating Coupler for 3 $\mu$ m SOI Waveguides	183
ThB7	Energy-Efficient Coherent Supercontinuum Generation in Silicon	186

### ThC Transceivers And Modulators I

ThC1	25 Gb/s Silicon Photonic Transceivers	189
ThC2	50-Gb/s Silicon Modulator Using 250- $\mu$ m-Long Phase Shifter Based-on Forward-Biased Pin Diodes	192
ThC3	Low Drive Voltage 10 Gb/s and High Contrast 40 Gb/s Silicon Slow Wave Modulators	195
ThC4	An Alignment Tolerant High Speed Ring Resonator based Silicon Optical Modulator	198

ThC5	44 Gbit/s Silicon Mach-Zehnder Modulator based on Interleaved PN Junctions	201
ThC6	Photonic Nanostructure Tx/Rx Devices for Advanced Optical Networks	204
<b>ThD</b>	<b>Integrated Sources</b>	
ThD1	Silicon Photonics for Optical Access Networks	207
ThD2	Comb-Laser Driven WDM for Short Reach Silicon Photonic based Optical Interconnection	210
ThD3	Toward An Integrated Silicon-Photonic Module for Widely Tunable Narrow-line RF Source Using Injection-Locking	213
ThD4	Narrow Spectral Linewidth Wavelength Tunable Laser with Si Photonic-Wire Waveguide Ring Resonators	216
ThD5	Miniaturized Laser Doppler Vibrometers Integrated on Silicon-on-Insulator with Thermo-Optic Serrrodyne Optical Frequency Shifter	219
ThD6	A Highly Efficient Electrically Pumped Optical Amplifier Integrated on a SOI Waveguide Circuit	222
ThD7	High Efficiency CW Four-Wave Mixing at 1.5 $\mu\text{m}$ in SOI Nano-Rib Waveguides Using p-i-n Diodes	225
<b>ThE</b>	<b>Alternative Integration Techniques</b>	
ThE1	Propagation of Lossy Wave in Si Slot Waveguide	228
ThE2	High-Uniformity Waveguide-integrated Metal-Semiconductor-Metal Germanium Photodetector with SiGe Capping Layer and its Application to Differential Receivers	231
ThE3	CMOS-Compatible Tungsten Heaters for Silicon Photonic Waveguides	234
ThE4	Ferroelectric Properties of PZT and PLZT Films on Si Substrate with ITO Buffer Layer	237
<b>ThP</b>	<b>Poster Session II</b>	
ThP1	Small Dimension Hybrid SPP Waveguide with Low Propagation Loss	240
ThP2	Suppression of Scattering Loss in Erbium-Yttrium Silicate Crystalline Waveguide Fabricated by Radical-Assisted Sputtering	243
ThP3	Mid-Infrared As <sub>2</sub> Se <sub>3</sub> Chalcogenide Glass-on-Silicon Waveguides	246
ThP4	Hybrid Si <sub>3</sub> N <sub>4</sub> -Er/Yb/Y Silicate Waveguide Amplifier with 1.25dB/cm Internal Gain	249
ThP5	Vertical-Tunneling Spot-Size Converters for Silicon-Wire Waveguides	252
ThP6	Object-Oriented Modified Photometric Stereo Algorithm for 3D Imaging in Fiber-to-Chip Coupling	255
ThP7	Time-of-Flight Range Finding Sensor Using an Integrated PNP PIN Phototransistor in 180 nm CMOS	258
ThP8	Capacitance of Carrier Depletion Silicon-on-Insulator Optical Modulation Diodes	261
ThP9	Polarization-Entangled Photon Pair Source on a Chip	264
ThP10	GHz Response of Si Photodiodes Fabricated with 0.35- $\mu\text{m}$ Si BiCMOS Technology	267
ThP11	Photonic Crystal Cavity Based WDM Components	270
	Low-Loss and High Extinction Ratio 40 Gbit/s Optical Modulator with Self-Aligned Fabrication	

ThP12	Process	273
ThP13	A Uniform, Low Loss 1x16 Power Splitter Based on a High Q Si <sub>3</sub> N <sub>4</sub> Ring Resonator	276
ThP14	On-Chip Wavelength-Routed Photonic Networks with Comb Switches	279
ThP15	Circuit-Switched On-Chip Photonic Interconnection Network	282
ThP16	High-Fidelity Photonic Building Blocks Fabricated Using Thermal Nanoimprint Lithography (T-NIL)	285
ThP17	Lithography Simulation for the Fabrication of Silicon Photonic Devices with Deep-Ultraviolet Lithography	288
ThP18	Narrow Gap Width Induced Radiation Loss on Waveguide Coupled Microring	291
ThP19	Full Area Emitter SiGe Phototransistor for Opto-Microwave Circuit Applications	294
ThP20	Real-Time Analysis of Antigen-Antibody Association Kinetics using a Low-cost SOI Photonic Biosensor	297
ThP21	Mach-Zehnder Based 2X2 Electro-Optical Switches on Silicon-on-Insulator with Low Crosstalk	300
ThP22	Vertical Integration of Silicon Nitride on Silicon-on-Insulator Platform	303
ThP23	Low-Power-Consumption, High Speed Mach-Zehnder Silicon Optical Modulator for CMOS Compatible Integration	305
ThP24	Bit-Error Rate Improvement through All-Optical Signal Regeneration in Deposited Silicon Waveguides	308

## Friday, August 31, 2012

### FA Light Emission

FA1	GeSn Light-Emitting Pin Diodes on Si	311
FA2	Light Emission from Thulium Silicates for Optical Amplifiers on Silicon in Extended Optical Communication Bands	314
FA3	High-Efficiency Hybrid III-V/Si External Cavity DBR Laser for 3- $\mu$ m SOI Waveguides	317
FA4	12.6 Gb/s Direct OFDM Modulation of a Hybrid III-V-on-Silicon laser	320
FA5	Multi-Guide Vertical Integration in InP: Technology and Applications	N/A

### FB Ge Light Emission

FB1	Germanium Laser: A CMOS Compatible Light Emitter	323
FB2	Large Transient Optical Gain from N <sup>+</sup> Ge-on-Si	325
FB3	Lateral Carrier Injection to Germanium for Monolithic Light Sources	328
FB4	Lateral PIN Current-Injected Photonic Crystal Nanocavity Light Emitting Diodes Based on Ge Quantum Dots	331
FB5	Improvement of Photoluminescence from Ge Layers with Si <sub>3</sub> N <sub>4</sub> /SiO <sub>2</sub> Stressors	334
FB6	Tuning the Electroluminescence of n-Ge LEDs using Process Induced Strain	337

FB7	Time-Resolved Photoluminescence Study of Highly n-doped Germanium Grown on Silicon	340
-----	--	-----

**FC Novel Materials And Processes**

FC1	Scaling Down Photonics: Plasmon Lasers, Waveguide and Graphene Modulators	N/A
FC2	Carbon Nanotube Photonics on Silicon	343
FC3	Low Temperature Crystallization of Highly Textured GeSn Thin Films on SiO2 for 3D Photonic Integration	346
FC4	Plasma deposited $\mu\text{-Si:H}$ Wire Waveguide- An alternative low temperature platform of Si photonics	349
FC5	Gas Cluster Ion Beam Treatment for Silicon Waveguide Trimming	352
FC6	Advanced Light Manipulation with Photonic Crystal Nanostructures	N/A

**FD Transceivers and Modulators II**

FD1	The Impact of Networking Trends and Architectures on Optical Technology Requirements	N/A
FD2	High-Speed GeSi EA Modulator at 1550nm	355
FD3	Wavelength-Tuning-Free 10-Gb/s Operation of a Silicon-Integrated Resonantly-Enhanced Modulator and Single-Mode Laser	358

**PD Post Deadline**

PD1	Transfer Printed Photonic Crystal Nanomembrane Lasers on Silicon with Low Optical Pumping Threshold	*** *%
PD2	Self-Aligned Microbonded Ge/Si PIN Waveguide Photodetectors	* (
PD3	Sub-100 $\mu\text{m}$ , 40 Gb/s Photonic Crystal Silicon Optical Modulators	* +
PD4	40 Gb/s Thermally Tunable CMOSs Ring Modulator	+ \$