

# **2016 IEEE First International Conference on Control, Measurement and Instrumentation (CMI 2016)**

**Kolkata, India  
8-10 January 2016**



**IEEE Catalog Number: CFP16C90-POD  
ISBN: 978-1-4799-8850-1**

**Copyright © 2016 by the Institute of Electrical and Electronic Engineers, Inc  
All Rights Reserved**

*Copyright and Reprint Permissions:* Abstracting is permitted with credit to the source. Libraries are permitted to photocopy beyond the limit of U.S. copyright law for private use of patrons those articles in this volume that carry a code at the bottom of the first page, provided the per-copy fee indicated in the code is paid through Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923.

For other copying, reprint or republication permission, write to IEEE Copyrights Manager, IEEE Service Center, 445 Hoes Lane, Piscataway, NJ 08854. All rights reserved.

***\*\*\*This publication is a representation of what appears in the IEEE Digital Libraries. Some format issues inherent in the e-media version may also appear in this print version.***

|                         |                   |
|-------------------------|-------------------|
| IEEE Catalog Number:    | CFP16C90-POD      |
| ISBN (Print-On-Demand): | 978-1-4799-8850-1 |
| ISBN (Online):          | 978-1-4799-1769-3 |

**Additional Copies of This Publication Are Available From:**

Curran Associates, Inc  
57 Morehouse Lane  
Red Hook, NY 12571 USA  
Phone: (845) 758-0400  
Fax: (845) 758-2633  
E-mail: [curran@proceedings.com](mailto:curran@proceedings.com)  
Web: [www.proceedings.com](http://www.proceedings.com)

CURRAN ASSOCIATES INC.  
**proceedings**  
.com

## Table of Contents

| Paper ID | Paper Title  | Page No. |
|----------|--|----------|
| 1        | Power Density & Thermal Limits of The Flyback SMPS   | 1-5      |
| 6        | Optimal solutions of load frequency control problem using oppositional krill herd algorithm  | 6-10     |
| 12       | Performance Comparison of Optimized Controller Tuning Technique for Voltage Stability  | 11-15    |
| 19       | Estimation of Glucose and Insulin Concentration Using Nonlinear Gaussian Filters   | 16-20    |
| 21       | Real-time Compression of Electrocardiogram Using Dynamic Bit Allocation Strategy   | 21-25    |
| 24       | Economic Load Dispatch with Prohibited Zone and Ramp-rate Limit Constraints- A Comparative Study   | 26-30    |
| 25       | Two-Stage Adaptive Sliding-mode Controller for Vehicle Yaw Stability Using Differential ABS  | 31-35    |
| 30       | Design, Modeling and Software Implementation of a Current-Perturbed Maximum Power Point Tracking Control in a DC-DC Boost Converter for Grid-Connected Solar Photovoltaic Applications         | 36-41    |
| 31       | Speed Control of A Grid Connected Doubly-Fed Induction Generator System for Maximum Power Point Tracking with Improved Input Power Factor Employing Matrix Converter as a Slip Power Exchanger | 42-47    |
| 34       | EV Charging Station Using Renewable Energy   | 48-52    |
| 39       | Adaptive Coding and Modulation (ACM) Technique for Performance Enhancement of FSO Link   | 53-57    |
| 40       | Fractal Spiral Capacitor for RF Applications   | 58-61    |
| 41       | Application of the Tuned Kalman Filter in Speech Enhancement   | 62-66    |
| 42       | Electrical impedance model of piezoelectric based sensor   | 67-71    |
| 43       | Internal Model Based PI Controller Design for the Coupled Tank System: An Experimental study   | 72-76    |
| 44       | Online Detection and Location Estimation of Earthquake Events Using Continuous Wavelet Transform   | 77-82    |
| 45       | Machine vision system based monitoring approach for friction stir welding process  | 83-86    |
| 46       | Real-Time Parameter Estimation for Arbitrary Aerial Manipulators   | 87-91    |
| 49       | Second Order Sliding Mode Control for Quadrotor  | 92-96    |
| 50       | Disturbing Load Identification in Distribution System Network  | 97-102   |
| 52       | Parameters affecting the switching life in HPF self ballasted lamps  | 103-106  |
| 53       | An experimental set-up for measuring thermodynamic response of low temperature phase change materials  | 107-109  |
| 56       | An Extended Linear Quadratic Regulator and its Application for Control of Power System Dynamics  | 110-114  |
| 57       | Recognition of Harmonic Sources in Distribution Network using Fractal Analysis   | 115-119  |
| 60       | GA Optimized Fuzzy Controlled DPLL using Discrete Energy Separation Algorithm  | 120-124  |
| 61       | State estimation by orthogonal hybrid (combination of SHF and RHTF) function   | 125-130  |
| 63       | Diagnosis of Power System Failures Using Observer based Discrete Event System  | 131-135  |
| 64       | Robust Load Frequency Control in Multi-Area Power System: An LMI Approach  | 136-140  |
| 69       | Design of Chemo-GA for Engineering Design Optimization Problem   | 141-145  |
| 71       | Beaglebone based Employee Details Verification System (EDVS)   | 146-150  |
| 73       | Studies on PI/PID Controllers in the Proportional Integral Plane via Different Performance Indices   | 151-155  |
| 75       | Quench Analysis, Detection & Protection of 5-Tesla Superconducting Solenoid Magnet using Numerical Methods   | 156-161  |
| 79       | Switching of Selectivity from Sulfur Dioxide to Butane: the Role of V2O5 Concentration in Nanostructured SnO2 Sensors  | 162-166  |
| 80       | Two-Mass Robot Hopping on an Elastic Foundation: Apex Height Control   | 167-171  |
| 83       | Guaranteed performance PID controller for UAV pitch control  | 172-176  |
| 91       | Sparse identification of Output Error models using l-1 regularized least square  | 177-181  |
| 92       | Importance of Social Welfare Approach for the Analysis of Demand Response  | 182-185  |
| 93       | Analysis of 6-DOF motion with PI controller in electrohydraulic Stewart platform   | 186-190  |
| 94       | SCADA based system for Discriminating Faulty Bearing of Induction Motors used in Process Control Operations  | 191-195  |
| 96       | Performance Analysis of Arc Welding Parameters using Self Organizing Maps and Probability Density Distributions  | 196-200  |
| 98       | An Investigation on the Performance of an Oscillating Flat Plate Fin with Compliant Joint for Underwater Robotic Actuation   | 201-205  |
| 99       | Automatic Generation Control using Optimally Tuned Tilt Integral Derivative Controller   | 206-210  |
| 100      | A novel way to acquire foot contour measurements of remotely located patients having foot deformities  | 211-214  |
| 102      | Performance study of Multiresolution PI controller for Third Order System  | 215-218  |
| 106      | Comparative Analysis of Different Fractal Methods in Studying Post-ictal ECG signals of Epilepsy Patient   | 219-223  |
| 108      | Level Control of Two Tank system by Fractional Order Integral State Feedback Controller Tuned by PSO with Experimental Validation  | 224-228  |
| 112      | Dissimilarity Factor Based Classification of Inferior Myocardial Infarction ECG  | 229-233  |
| 113      | Badminton Shuttlecock Detection and Prediction of Trajectory using Multiple 2 Dimensional Scanners   | 234-238  |

|     |   |         |
|-----|---|---------|
| 116 | Switched Capacitor Single-Slope Capacitance to Direct Digital Converter for Differential Capacitive Sensors   | 239-243 |
| 117 | Novel Switched Capacitor Direct Digital Converters for Variable Reluctance Sensors  | 244-248 |
| 122 | Identifying Cancer Biomarkers From Leukemia Data using Feature Selection and Supervised Learning  | 249-253 |
| 125 | Biogeography Based PI Controller for Unified Power Quality Conditioner  | 254-258 |
| 126 | A Low Cost Comparative and Qualitative Conditional Assessment of the Human Limb using Force Masking Technique with a Simple Strain Gauge Setup      | 259-263 |
| 127 | Entropy-Based Wavelet De-noising for Partial Discharge Measurement Application  | 264-268 |
| 129 | Measurement of Power Flow Variations in Gaussian Plane Using Phasor Measuring Unit  | 269-273 |
| 130 | Application of Data Mining in Fault Diagnosis of Induction Motor  | 274-278 |
| 131 | A novel fuzzy based signal analysis technique in electronic nose and electronic tongue for black tea quality analysis                               | 279-283 |
| 132 | Design of Predictive Sliding Mode Controller for Cascade Control System   | 284-289 |
| 133 | Application of Close Loop Expert System for Heating Control of Rolling Mill Furnaces in a Steel Plant   | 290-294 |
| 134 | Velocity Control of Omni Drive Robot using PID Controller and Dual Feedback.  | 295-299 |
| 135 | Adaptive Force Tracking in Electrohydraulic System with First-Order Sliding Mode Control  | 300-304 |
| 137 | Optimal PID controller design of an Inverted Pendulum Dynamics: A Hybrid Pole-Placement & Firefly Algorithm Approach                                | 305-310 |
| 139 | Condition Monitoring of Electrical Equipment using Thermal Image Processing   | 311-315 |
| 142 | Designing Low-Chattering Sliding Mode Controller for an Electrohydraulic System   | 316-320 |
| 147 | Mathematical Modeling and Fuzzy Logic Control of a Brushless DC Motor Employed in Automobile and Industrial Applications                            | 321-325 |
| 148 | Design and Tuning of Fractional Order PID Controller for Speed control of Permanent Magnet Brushless DC Motor                                       | 326-330 |
| 149 | Fractional Order Speed Controller for Buck-Converter fed DC Motor   | 331-335 |
| 152 | Emotion Recognition from Facial Image Analysis Using Composite Similarity Measure Aided Bidimensional Empirical Mode Decomposition                  | 336-340 |
| 154 | Implementation of a PID control PWM Module on Altera DE0 Nano Kit Using FPGA  | 341-345 |
| 155 | Efficient estimation of system states of a poorly modeled 2-D target tracking system using evolutionary strategy based particle filter algorithm    | 346-350 |
| 156 | Assessment of DC Servo Motor with Sliding Mode Control Approach   | 351-355 |
| 159 | Analysis of singular systems via Taylor series using a recursive algorithm  | 356-360 |
| 162 | Disturbance observer based optimal second order sliding mode controller for nonlinear systems with mismatched uncertainty                           | 361-365 |
| 165 | Characterization of bubbly flow through the fusion of multiple features extracted from high speed images  | 366-370 |
| 166 | Impedance Estimation of a Pneumatic Muscle as a Mechanical Transmission and Actuation device  | 371-375 |
| 167 | Inertial Delay Control based State Feedback Control for Active Suspension with Full Car Model   | 376-380 |
| 168 | Analysis of Inter-turn Short Circuit Fault in 2.5HP 3-Phase Induction Motor   | 381-385 |
| 169 | Adaptive Fault Tolerant Control For Active Suspension   | 386-390 |
| 170 | Learning Object Manipulation from Demonstration through Vision for the 7-DOF Barrett WAM  | 391-396 |
| 171 | Control of a 4 DoF Barrett WAM Robot - Modeling, Control Synthesis and Experimental Validation  | 397-402 |
| 172 | Modelling and Performance Improvement of Phase-angle-based Conductivity Sensor  | 403-407 |
| 174 | Adaptive fuzzy nonsingular fast terminal sliding mode control for spacecraft formation flying   | 408-413 |
| 175 | Smart-phone as Measuring Device   | 414-418 |
| 177 | Characterizing the Composite Noise of a Camera used as a Sensor for Position Estimation   | 419-423 |
| 178 | Detection and Quantification of Arsenic in Water Using Electronic Tongue  | 424-428 |
| 179 | Review of Sensor Technology for Mine Safety Monitoring Systems: A Holistic Approach   | 429-434 |
| 181 | Prototype Development of an SPWM Inverter for PV Applications on dSPACE Platform  | 435-439 |
| 182 | An FPGA-based Integrated Signal Conditioner for measurement of position, velocity and acceleration of a rotating shaft using an incremental encoder | 440-444 |
| 184 | Design and Manufacture of Bio-mimic Robotic Fish  | 445-448 |
| 186 | Design of a PC based Real Time Mass Flow Indicator using AD590 as sensor  | 449-453 |
| 189 | Radial basis function Neural Network for Prediction of Cardiac Arrhythmias based on Heart rate time series  | 454-458 |
| 190 | A comparison of several nonlinear filters for ballistic missile tracking on re-entry  | 459-463 |
| 192 | Occupancy Grid Map Generation using 360° Scanning Xtion Pro Live for Indoor Mobile Robot Navigation   | 464-468 |
| 193 | Auto Target Detection of Humanoid and Auto Shooting Using Sniper: A Design Approach   | 469-473 |
| 194 | A Three-Phase State Estimation in Unbalanced Distribution Networks with Switch Modelling  | 474-478 |
| 195 | Design of Block Backstepping Based Nonlinear State Feedback Controller for Pendubot   | 479-483 |
| 196 | A Real-Time Heart-Rate Monitor Using Non-Contact Electrocardiogram for Automotive Drivers   | 484-488 |
| 198 | Ultrasonic Measurement and Detection of Pre-delamination damage in Composite under Tension-Torsion Loading  | 489-493 |

|     |   |         |
|-----|---|---------|
| 199 | Evaluation of Video Magnification for Nonintrusive Heart Rate Measurement   | 494-498 |
| 201 | Design of Binary Search ADC using N Comparators   | 499-502 |
| 205 | Electrooculogram based Approach for Prevention of Dry Eye Condition in Computer Users                             | 503-507 |
| 207 | Reference Input Tracking of inversion-based Non-Minimum phase System using Adaptive Two-Degree-of-Freedom Control | 508-513 |