## PROCEEDINGS OF SPIE

# 17th International Conference on Optical Communications and Networks (ICOCN2018)

**Zhaohui Li** Editor

16–19 November 2018 Zhuhai, China

Organized by Sun Yat-sen University (China) Jinan University (China) Macau University of Science and Technology (Macao, China)

Technical Cosponsor SPIE

Published by SPIE

> Volume 11048 Part One of Two Parts

Proceedings of SPIE 0277-786X, V. 11048

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

The papers in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. Additional papers and presentation recordings may be available online in the SPIE Digital Library at SPIEDigitalLibrary.org.

The papers reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from these proceedings:

Author(s), "Title of Paper," in 17th International Conference on Optical Communications and Networks (ICOCN2018), edited by Zhaohui Li, Proceedings of SPIE Vol. 11048 (SPIE, Bellingham, WA, 2019) Seven-digit Article CID Number.

ISSN: 0277-786X ISSN: 1996-756X (electronic)

ISBN: 9781510627703 ISBN: 9781510627710 (electronic)

Published by **SPIE** P.O. Box 10, Bellingham, Washington 98227-0010 USA Telephone +1 360 676 3290 (Pacific Time)· Fax +1 360 647 1445 SPIE.org Copyright © 2019, Society of Photo-Optical Instrumentation Engineers.

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of copying fees. The Transactional Reporting Service base fee for this volume is \$18.00 per article (or portion thereof), which should be paid directly to the Copyright Clearance Center (CCC), 222 Rosewood Drive, Danvers, MA 01923. Payment may also be made electronically through CCC Online at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher. The CCC fee code is 0277-786X/19/\$18.00.

Printed in the United States of America by Curran Associates, Inc., under license from SPIE.

Publication of record for individual papers is online in the SPIE Digital Library.



**Paper Numbering:** Proceedings of SPIE follow an e-First publication model. A unique citation identifier (CID) number is assigned to each article at the time of publication. Utilization of CIDs allows articles to be fully citable as soon as they are published online, and connects the same identifier to all online and print versions of the publication. SPIE uses a seven-digit CID article numbering system structured as follows:

- The first five digits correspond to the SPIE volume number.
- The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc. The CID Number appears on each page of the manuscript.

### Contents

xiii	Authors
xix	Conference Committee

#### Part One

	SESSION 1
11048 02	Adaptively loaded offset-QAM OFDM based on set-partitioned QAM in IMDD systems (Invited Paper) [11048-237]
11048 03	A simple OAM mode generator based on SOI strip waveguides [11048-4]
11048 04	Intra symbol frequency domain averaging channel estimation for coherent optical OFDM/ OQAM system [11048-6]
11048 05	Space optical communication DSP simplification scheme based on ICC and CMA [11048-9]
11048 06	Joint intra symbol frequency domain averaging channel estimation for polarization-division- multiplexed CO-OFDM/OQAM system [11048-12]
11048 07	Two-dimensional optical phased array with grating lobe suppression by element distribution and emitting amplitude optimization [11048-14]
11048 08	Speech enhancement with stacked frames and deep neural network for VoIP applications [11048-15]
11048 09	Multiband phase-coded signal generation based on a simple photonic bi-phase modulator [11048-16]
11048 0A	Hyper-Chen chaos-based frequency domain shifting and time domain scrambling for physical-layer encryption in CO-OFDM [11048-22]
11048 OB	A corrosion detection algorithm via the random forest model [11048-23]
11048 OC	Resource reservation scheme in nesting ring optical network on chip [11048-24]
11048 OD	Dynamic range improvement for a microwave photonic link using a phase modulator [11048-25]
11048 OE	Demand-adaptive VNF placement and scheduling with low latency in optical datacenter networks [11048-27]

-

11048 OF	Photonic generation of linearly chirped microwave waveform with tunable frequency and bandwidth multiplication factor [11048-28]
11048 0G	Sparse I/Q Volterra filter for optical 16-QAM signals in direct-detection Kramers-Kronig receiver [11048-29]
11048 OH	Time domain hybrid modulation scheme for visible light communication [11048-30]
11048 0	Average power requirement of MPSK subcarrier modulation in wireless optical communications [11048-33]
11048 OJ	A sidelobe suppression method for Beidou passive radar based on window adding technology [11048-34]
11048 OK	Passive radar imaging based on spatial spectrum theory [11048-35]
11048 OL	Visible light communication using segmental frequency domain pre-equalization [11048-36]
11048 0M	<b>Optimized configuration of visible light communication featured traffic control system</b> [11048-39]
11048 ON	Volterra equalizer with MLSD for 100 Gb/s PAM4 over up to 160m OM3-MMF using 20GHz class 850nm VCSEL [11048-42]
11048 00	A shared regeneration location scheme with auxiliary graph and deep neural networks in translucent optical networks [11048-45]
11048 OP	Research on colorimetric characterization of LCD based on the steepest descent method [11048-47]
11048 0Q	Research on colorimetric characterization of LCD based on cubic polynomials curve model [11048-48]
11048 OR	Performance analysis of PPM modulation in log-normal fading channels of FSO [11048-49]
11048 OS	An algorithm approach to optical true time delay pool enabled centralized control beamforming for wireless base station [11048-50]
11048 OT	A clustering algorithm to resist multipath effect for OFDM-VLC system [11048-51]
11048 OU	Multi-path pre-reserved resource allocation based on tidal traffic prediction in metropolitan optical network [11048-55]
11048 OV	A method for detecting INS horizontal and azimuth reference datum deviation [11048-58]
11048 OW	Operation conditions and considerations of single photon avalanche photodiode for optical wireless communication [11048-62]
11048 OX	Bit-mapping-based irregular QC-LDPC coded BICM scheme for optical communication systems [11048-67]

- 11048 0Y A spectrum efficient anycast protection approach for single-datacenter and single-link failures in inter-datacenter elastic optical networks [11048-68]
- 11048 0Z Wavelength-insensitive weakly coupled FMFs and components for the MDM-GPON [11048-70]
- 11048 10 An infrared and visible image fusion algorithm based on MAP [11048-75]
- 11048 11 A multi-passband microwave photonic filter based on multiple dispersion devices [11048-77]
- 1104812 Performance analysis of FSO system with different modulation schemes over gamma-gamma turbulence channel [11048-83]
- 11048 13 Design of highly stable DFB laser source [11048-85]
- 1104814 Secure optical layer flexibility in 5G networks (Invited Paper) [11048-92]
- 1104815 Short term traffic flow prediction research based on chaotic local model [11048-93]
- 1104816 Kalman scheme implement for RSOP equalization in hardware perspective [11048-96]
- 1104817 A novel asymmetrically clipped STTC for IM/DD MIMO atmospheric optical communications [11048-101]
- 1104818 Ergodic channel capacity of MIMO WOC systems over combined effects of correlated atmospheric turbulence channel with MPPM [11048-103]
- 11048 19 Coherent transmitter skew limitation on spectrally efficient optical communication systems (Invited Paper) [11048-108]
- 11048 1A Nonequilibrium statistical theory of particulate matter growth [11048-109]
- 110481B Optimization of pilot pattern in ACO-OFDM systems channel estimation based on compressed sensing [11048-110]
- 11048 1C Capacity of MIMO free space optical communications [11048-113]
- 11048 1D A new indoor visible light positioning scheme to reduce the influence of reflections [11048-118]
- 110481E Generation of frequency tripled and quintupled PSK millimeter wave signal without phase multiplication employing parallel phase modulators [11048-121]
- 11048 1F Trellis coded modulation scheme based on three dimension 32QAM signal [11048-124]
- 110481G Linear-interpolation-based phase noise suppression method in Nyquist-WDM-PON [11048-127]
- 11048 1H A simple and effective tracking scheme for visible light communication systems [11048-128]

11048 11	Measurement and analysis of MPI penalty in operator's PON system [11048-130]
11048 1J	100G DFT-spread OFDM-WDM-PON based on probabilistic shaped 16QAM [11048-131]
11048 1K	A service reconfiguration scheme for network restoration based on reinforcement learning [11048-132]
11048 1L	A modified model of backscattering light and pump light [11048-133]
11048 1M	Beam-forming method for optically phased array based on compressed sensing [11048-134]
11048 1N	Homogenization of power intensity based on micro lens array in optical wireless communication systems [11048-135]
1104810	Low complexity multi-level NB-QC-LDPC coded modulation scheme for optical communication systems [11048-137]
11048 1P	Experimental demonstration of WDM-PON based on probabilistic shaped PAM4 modulation format [11048-142]
11048 1Q	A 2×2 photonic crystal waveguide thermo-optic switch [11048-143]
11048 1R	Experimental studies of mode-locked fiber laser in large normal and anomalous dispersion regimes by using a CFBG-based dispersion management component [11048-146]
11048 15	Cost-minimized algorithm for POTN device in POTN+IPRAN 5G bearer network [11048-152]
11048 1T	A new method of using deep neural network to compensate PDL [11048-154]
110481U	Design and implementation of adaptive coupling system for making space light into single- mode fiber [11048-155]
110481V	Crosstalk-aware flexible grouping spectrum and core assignment in SDM-EONs based on mixed super-channel [11048-161]
11048 1W	The two-level group network meter reading system based on SX1278 [11048-167]
11048 1X	A multi-wavelength optical comb-based communication system with tunable wireless multi- waveband [11048-170]
11048 1Y	An equalization method based on KNN for GPON with PAM4 [11048-172]
11048 1Z	Experimental demonstration of GFDM-OFDM hybrid modulation in an IM-DD system [11048-173]
11048 20	Multilevel brightness modulation scheme based on a LED array and K-means clustering algorithm for optical camera communications [11048-176]
11048 21	A channel estimation scheme for HACO-OFDM system-based visible light communications [11048-180]

11048 22	Performance comparison of DFT-OFDM, DCT-OFDM, and DWT-OFDM for visible light communications [11048-182]
11048 23	Free space wide-spectrum optical communication system based on supercontinuum [11048-184]
11048 24	Mach-Zehnder interferometer based on core-offset splicing technique for sensing applications [11048-186]
11048 25	Long-distance near-infrared VCSEL wireless optical communication system based on collimating lens design [11048-189]
11048 26	Novel training symbol design for transmitter IQ mismatch compensation in CO-OFDM system [11048-190]
11048 27	Distance-adaptive routing, modulation, and spectrum assignment (DA-RMSA) algorithm based on signal overlap in elastic optical networks (EONs) [11048-192]
11048 28	Comparison of chromatic dispersion pre- and post-compensation with Kramers-Kronig receiver [11048-194]
11048 29	Arbitrary waveform generation based on complex filter and frequency-time mapping [11048-195]
11048 2A	Parallelized few-mode receivers for MDM transmission [11048-202]
11048 2B	Blind and efficient modulation format identification based on fourth-power characteristic value [11048-205]
11048 2C	Robust digital-controllable broadband analog optical chaos generation [11048-213]
11048 2D	High resolution fiber optic spectrometer system [11048-214]
11048 2E	Maximizing the security of digital chaos based OFDM-PON with a dynamical nonlinear transformation [11048-221]
11048 2F	Frequency reshaping and compensation scheme based on deep neural network for a FTN CAP 9QAM signal in visible light communication system [11048-222]
11048 2G	Research on data availability of shipboard navigation system [11048-226]
11048 2H	Preliminary study on inversion of seabed parameters from ocean ambient noise [11048-231]
11048 2	Deep-learning-based failure prediction with data augmentation in optical transport networks [11048-232]
11048 2J	Application of large shipborne theodolite in space target measurement [11048-233]
11048 2K	An overlapping amplitude and pulse position modulation scheme for non-Kolmogorov turbulent gamma-gamma channel free-space optical communication [11048-236]

#### Part Two

	SESSION 2
11048 2L	Tunable optical filter with variable bandwidth based on Vernier-cascade second-order microring resonators [11048-7]
11048 2M	Photonics channelization spectrum stitching technique in a dual-OFC-based channelizer [11048-18]
11048 2N	Low-noise stable millimeter-wave optoelectronic oscillator based on self-regenerative frequency-dividing and phase-locking techniques [11048-19]
11048 20	A compact mode sorter for demultiplexing vortex light beams [11048-20]
11048 2P	The coherence measurement of a low coherence supercontinuum source [11048-31]
11048 2Q	High-accuracy optical vector analyzer based on optical double-sideband suppressed carrier modulation and Pound Drever Hall technique [11048-44]
11048 2R	Demonstration of broadband chirped grating couplers for MPW fabrication [11048-53]
11048 2S	The measurement of heat dissipate rate from the micro-cavity resonator bulk to the environment based on thermo-optic oscillation [11048-57]
11048 2T	Integratable microwave photonic phase shifter based on a tunable optical coupler [11048-60]
11048 20	A novel filterless scheme for 16-tupled frequency millimeter-wave generation based on only two MZMs [11048-63]
11048 2V	Analysis and numerical simulation of a roof optical microcavity with micro-nano size [11048-64]
11048 2W	Inverse-design-based polarization rotator using multi-layer metamaterials [11048-74]
11048 2X	Performance optimization for plasmonic refractive index sensor based on machine learning [11048-79]
11048 2Y	Radio frequency downconversion based on a tunable optoelectronic oscillator [11048-87]
11048 2Z	A high-precision frequency estimation method based on harmonic expansion technique [11048-102]
11048 30	A nanoscale refractive index sensor based on periodically modulated graphene metamaterial [11048-117]
11048 31	Optimization of optical phased array antenna with grating array superlattice [11048-122]

11048 32	Microwave frequency division based on an optoelectronic oscillator [11048-123]
11048 33	High efficiency silicon-on-insulator fiber-chip spot size converting edge coupler [11048-125]
11048 34	Tunable microwave photonic phase shifter based on silicon microring resonator [11048-126]
11048 35	Simultaneous frequency down-conversion, self-interference cancellation, and image rejection for radio-over-fiber systems using a DP-QPSK modulator [11048-139]
11048 36	Design and simulations of photonic switch using hybrid Ge <sub>2</sub> Sb <sub>2</sub> Te <sub>5</sub> -silicon waveguides in mid-IR region [11048-147]
11048 37	A feedback system for the stability improvement of optical frequency comb generating system based on a single integrated PM-DMZM [11048-156]
11048 38	Numerical simulation of pulse states in dual-pump figure-of-eight fiber lasers [11048-200]
11048 39	Thermally tunable silicon microring resonators with ultralow tuning power [11048-204]
11048 3A	Study on graphene heater electrode silicon nitride waveguide phase shifters [11048-216]
11048 3B	Reconfigurable two-mode multiplexer based on three-waveguide-coupling structure [11048-234]
11048 3C	Reconfigurable data exchange for wavelength- and mode-division multiplexing optical networks [11048-235]

#### SESSION 3

11048 3D	Random fiber laser based on weak fiber Bragg grating array [11048-3]
11048 3E	Multi-state solitons in a CFBG-based ultrafast bidirectional fiber laser [11048-5]
11048 3F	Research on photonic crystal fiber polarization devices based on surface plasmon [11048-8]
11048 3G	Theoretical research on torsion measurement by FBG and its simulation verification [11048-10]
11048 3H	An optical fiber weight sensor based on SMS fiber structure [11048-11]
11048 3	Theoretical simulation of the acetylene-filled hollow-core fiber laser [11048-13]
11048 3J	Study on chaos-control of a dual-ring erbium-doped fiber laser by dual-signal stimulating dual-pump [11048-17]
11048 3K	Triggered supercontinuum generation in picosecond pump scheme [11048-26]

11048 3L	Thulium doped fiber laser with a limited pulse width of 560fs [11048-32]
11048 3M	Transmission performance of OM3, OM4, and OM5 multimode fibers [11048-37]
11048 3N	Photonic-assisted dual-band radar transmitter system based on a triple-loop optoelectronic oscillator [11048-41]
11048 30	Fabrication of monolithic microlenses in ytterbium doped microstructured optical fibers [11048-43]
11048 3P	Motor exhaust telemetry device based on differential optical absorption spectroscopy [11048-52]
11048 3Q	Effects of installing scheme on the strain measurement accuracy of optical fiber sensors [11048-59]
11048 3R	Stable and tunable nanosecond pulse fiber laser based on MOPA structure [11048-61]
11048 3S	High-resolution displacement sensor based on variable spacing grating [11048-71]
11048 3T	Weakly coupled 4-mode step-index FMF and demonstration of IM/DD MDM transmission [11048-72]
11048 3U	High performance interrogation by a composite-double-probe-pulse for ultra-weak FBG array [11048-73]
11048 3V	Development of three-component fiber laser geophone array system and field test analysis [11048-78]
11048 3W	Carbon nanotube Q-switched and mode-locked, tunable MIR fiber laser [11048-80]
11048 3X	Analysis and testing of displacement damage on several commercial optical transceivers via high speed protons [11048-86]
11048 3Y	All-fiber ring fiber structure fused-type mode selective coupler with polarization-maintaining and wide bandwidth [11048-90]
11048 3Z	Fabrication mechanism of fiber Bragg grating by 800nm femtosecond laser pulses [11048-94]
11048 40	Dual-channel optical fiber sensor based on the plasmon multimode interaction [11048-98]
11048 41	Spectral tuning effect and refractive index sensing characteristics of graphene oxide coated excessively tilted fiber gratings [11048-99]
11048 42	RI and temperature sensing based on cascaded core-offset structure with thin-core fiber [11048-100]
11048 43	Measuring static femto-Newton optical forces by a nanofiber with white-light interferometry [11048-105]

11048 44 High-resolution broadband phase interrogation for fiber optic interferometer using frequency stabilization and PGC demodulation [11048-115] 11048 45 Buoyancy material curing monitoring based on optical fiber Bragg grating sensors [11048-116] 11048 46 Label-free DNA hybridization monitoring through mFBG biosensor with self-assembly technique [11048-119] 11048 47 Research on sensing characteristics of cascaded tilted fiber Bragg grating [11048-140] Theoretical analysis and experimental demonstration of the radiation mode distribution of 45° 11048 48 **TFG** [11048-145] 11048 49 Design and fabrication of sapphire-derived fiber with controllable core diameter [11048-148] 11048 4A Investigation on fiber optic curvature sensor based on SMF-FMF-SMF structure with up-taper fusion [11048-149] 11048 4B Er,Yb-doped fiber superfluorescent source with 11-W single-end output power [11048-151] 11048 4C **Controllable acid stripping system for bare fiber with high tensile strength** [11048-153] 11048 4D High-energy wavelength-tunable picosecond all-fiber laser based on active mode-locking [11048-157] 11048 4E Bend property of few-mode ring-core fiber supporting seven spatial modes for mode-division multiplexed applications [11048-159] 11048 4F Refractive index insensitive temperature sensor based on a photonic crystal nanobeam cavity [11048-160] 11048 4G Real-time detection of BSA concentration based on a Mach-Zehnder interferometric biosensor [11048-163] 11048 4H The OAM transmission fiber based on step-index and graded-index refractive distribution [11048-164] 11048 4 Laser wavelength monitoring based on a packaged microbubble resonator [11048-166] 11048 4J Orbital angular momentum generation in two mode fiber [11048-169] 11048 4K Effect of loading mode and test method on dynamic fatigue parameter measurement of **optical fiber** [11048-175] 11048 4L Donor-acceptor-donor organic dye-based optofluidic laser for sensitive explosive detection with a large dynamic range [11048-178] 11048 4M Double fiber Bragg gratings liquid level sensor based on push-pull self-demodulation scheme [11048-188]

11048 4N	Simultaneous measurements of refractive index and temperature based on Mach-Zehnder interferometer with sphere-trapezoid structure [11048-193]
11048 40	Polydimethylsiloxane optical microring resonator by nano-imprint lithography on MgF2 substrate $[11048-196]$
11048 4P	<b>50µJ rectangular pulse at 10 kHz from an all-fiber polarization-maintaining MOPA amplifier</b> [11048-201]
11048 4Q	Frequency response enhancement for long-range φ-OTDR system by additive random sampling and nonlinear frequency modulation [11048-203]
11048 4R	High-sensitivity hydraulic pressure sensor realized with PDMS film-based Fabry-Perot interferometer [11048-206]
11048 4S	Temperature-tunable optical filter based on Fano resonance liquid-core microcapillary resonator [11048-207]
11048 4T	Two-pass gas signal detection system based on fiber loop ring-down cavity [11048-212]
11048 4U	Analysis of mechanical properties of multimode fiber optic sensors [11048-215]
11048 4V	Optical fiber magnetic sensor based on magnetic fluid and long period fiber grating [11048-217]
11048 4W	All-fiber-integrated and spectrally flat 2-5 $\mu m$ supercontinuum generation in InF3 fiber with high conversion efficiency $[11048\text{-}220]$
11048 4X	Dark pulse generation based on black phosphorus in a Yb-doped fiber laser [11048-229]
11048 4Y	Accurate, robust, and fast mode decomposition for few-mode optical fiber with deep neural network [11048-230]