2nd International Conference on Advances in Materials, Mechanical and Manufacturing (AMMM 2020)

IOP Conference Series: Materials Science and Engineering Volume 893

Online 27 - 29 March 2020

ISBN: 978-1-7138-2690-3

ISSN: 1757-8981

Printed from e-media with permission by:

Curran Associates, Inc. 57 Morehouse Lane Red Hook, NY 12571



Some format issues inherent in the e-media version may also appear in this print version.

This work is licensed under a Creative Commons Attribution 3.0 International Licence. Licence details: http://creativecommons.org/licenses/by/3.0/.

No changes have been made to the content of these proceedings. There may be changes to pagination and minor adjustments for aesthetics.

Printed with permission by Curran Associates, Inc. (2021)

For permission requests, please contact the Institute of Physics at the address below.

Institute of Physics Dirac House, Temple Back Bristol BS1 6BE UK

Phone: 44 1 17 929 7481 Fax: 44 1 17 920 0979

techtracking@iop.org

Additional copies of this publication are available from:

Curran Associates, Inc. 57 Morehouse Lane Red Hook, NY 12571 USA Phone: 845-758-0400

Fax: 845-758-2633

Email: curran@proceedings.com Web: www.proceedings.com

TABLE OF CONTENTS

MATERIAL SYNTHESIS AND PREPARATION
THE ANALYSIS ABOUT SYNTHESIS, STRUCTURE AND PROPERTIES OF WILLEMITE CERAMIC PIGMENTS OBTAINED BY A SOL–GEL METHOD
INFLUENCE OF PHYSICAL MIXING RATIO ON PORE DEVELOPMENT IN HIGHLY POROUS CARBON PREPARED FROM NIPA PALM HUSK USING HYDROTHERMAL CARBONIZATION WITH CHEMICAL ACTIVATION
PRELIMINARY RESEARCH OF SYNTHESIZING BATTERY GRADE NICKEL SULPHATE FROM DISSOLUTION OF NICKEL MATTE IN DILUTE SULPHURIC ACID
EVALUATION OF NOISE ABSORPTION CAPACITY OF VARIOUS MATERIALS
OPTIMIZATION OF CUTTING PARAMETERS IN MACHINING POLYOXYMETHYLENE USING RSM
VIBRATION RESPONSE SIMULATION ON A HIGH RISK BUILDING WITH LAMINATED RUBBER BEARING BASE ISOLATION SUBJECTED TO EARTHQUAKE EXCITATION
OPTIMIZATION OF LAMINATE TOPOLOGY FOR MULTILAYERED COMPOSITE STRUCTURES SUBJECTED TO BUCKLING AND FAILURE CONSTRAINTS
MECHANICAL PROPERTIES AND AUTOMATION EQUIPMENT
THE INFLUENCE OF THE PITCH TO DIAMETER RATIO (P/D) ON A NOVEL TIDAL TURBINE PERFORMANCE
STORAGE ALLOCATION FOR STOCKED AND BUFFER BASKETS
Author Index