# 18th International Conference on Hydrotransport 2010

Rio de Janeiro, Brazil 22 – 24 Ser tember 2010

ISBN: 978-1-63439-445-1

#### Printed from e-media with permission by:

Curran Associates, Inc. 57 Morehouse Lane Red Hook, NY 12571



Some format issues inherent in the e-media version may also appear in this print version.

Copyright© (2010) by BHR Group All rights reserved.

Printed by Curran Associates, Inc. (2014)

For permission requests, please contact BHR Group at the address below.

BHR Group The Fluid Engineering Centre Cranfield, Bedfordshire MK43 0AJ United Kingdom

Phone: +44 1234 750422 Fax: +44 1234 750074

contactus@bhrgroup.co.uk

#### Additional copies of this publication are available from:

Curran Associates, Inc. 57 Morehouse Lane Red Hook, NY 12571 USA Phone: 845-758-0400 Fax: 845-758-2634 Email: curran@proceedings.com Web: www.proceedings.com

#### 18th International Conference on

## **H**YDROTRANSPORT

Rio de Janeiro, Brazil: 22–24 September 2010

## CONTENTS

| FORTY YEARS ON: Hydrotransport Conferences 1970-2010   |      |
|--|------|
| Sponsors   | xxix |
| FOREWORD   | 1    |
| LONG DISTANCE PIPELINES:<br>ECONOMICS, DESIGN, CONSTRUCTION AND OPERATION  |      |
| Specific energy consumption and desirable operating conditions for<br>fine-particle slurries<br>S A Hashemi, R S Sanders, University of Alberta; K C Wilson, Consultant,<br>Canada           | 5    |
| A technical comparison of coal pipeline options<br>N T Cowper, A D Thomas, Slurry Systems Pty Limited, Australia;<br>J Sobota, Wroclaw University of Environmental and Life Sciences, Poland | 17   |
| ESSAR'S iron ore slurry pipe line operations in India – a case study<br>M K Sampath, A S Prasad, M V B Murali, Essar Steel Ltd, India  | 31   |
| Savage River pipeline – 43 years of operation<br>F Salt, Consultant, Australia   | 53   |
| COARSE PARTICLE TRANSPORT  |      |
| Vertical conveying of coarse particles in pipelines with non-Newtonian carriers<br>L J W Graham, J Wu, CSIRO Process Science and Engineering;<br>L Pullum, Private Consultant, Australia     | 67   |
| New method of coal hydro transportation, process philosophy<br>B Enkhbold, E-Trans Company, Mongolia   | 81   |
| Semi-empirical formulae for upper plane bed friction<br>J Krupička, V Matoušek, Academy of Sciences of Czech Republic,<br>Czech Republic   | 95   |

| Determining the maximum coarse particle concentration (C∞) for slurry<br>pipeline flows<br>D Gillies, R S Sanders, University of Alberta; R G Gillies, Saskatchewan<br>Research Council, Pipe Flow Technology Centre, Canada                         | 105 |
|--|-----|
| Behaviour of intermediate-particle slurries in pipelines<br>K C Wilson, Consultant, Canada; A Sellgren, Lulea University of Technology,<br>Sweden  | 117 |
| In situ performance and potential applications of a thermal bed-load<br>measurement method<br>H J Ilgner, CSIR, Centre for Mining Innovations; P Goosen, Paterson & Cooke<br>Consulting Engineers (Pty) Ltd; S Dumbu, Stoner (Pty) Ltd, South Africa | 129 |
| Modeling of settling-slurry flow around deposition-limit velocity<br>V Matoušek, J Krupička, Academy of Sciences of Czech Republic,<br>Czech Republic  | 143 |
| Deposition velocities and concentration distributions of apatite slurry<br>T C Souza Pinto, L S Leal Filho, University of São Paulo; D Moraes Junior,<br>Santa Cecilia University, Brazil; P T Slatter, RMIT University, Australia                   | 155 |

## **OPEN CHANNEL FLOWS**

| Flow of highly concentrated, extended particle size distribution slurries<br>in open channels in laminar, transition and turbulent flow<br><i>L Fernández, A González, R Fuentes, JRI Engineering; J Martínez,</i><br><i>AUSENCO-PSI, Chile</i> | 167 |
|---|-----|
| Limit velocity for coarse solids transport in launders<br>M Zegpi, R Janssen, Bechtel Chile Limitada, Chile   | 183 |
| Laminar non-Newtonian open channel flow: investigating velocity, wall shear<br>stress and fluid depth<br>J Burger, R Haldenwang, Cape Peninsula University of Technology, South<br>Africa; N Alderman, BHR Group Ltd, UK                        | 193 |

## SOLIDS SEDIMENTATION

| Sedimentation and erosion of sediment at high solids concentration<br>C van Rhee, A M Talmon, Delft University of Technology, The Netherlands   | 211 |
|---|-----|
| A comprehensive methodology to predict particle sedimentation and solids concentration along the time in gelled drilling fluids <i>R Abensur Gandelman, G H Vieira Pereira Pinto, A Leibsohn Martins, Petrobras, Brazil</i> | 223 |
| Settling lengths for coarse particles in solid-liquid pipe flow<br>T F Jones, TFJ Consulting Ltd; C Ariyaratne, University of Sussex, UK  | 237 |
| Sedimentation velocity of grinded particles: a new, explicit semi-empirical formula for its determination<br><i>R Fuentes, F Calle, A González, P Koch, JRI Engineering, Chile</i>  | 249 |

| SLURRY RHEOLOGICAL ASSESSMENT   |     |
|---|-----|
| Viscous scaling and flow behaviour of a phosphate clay slurry<br>G R Addie, GIW Industries Inc, USA; L Pullum, Private Consultant, Australia;<br>A Sellgren, Lulea University of Technology, Sweden   | 277 |
| Design, construction, commissioning and testing of a portable tube viscometer<br>and pump rig<br><i>R Haldenwang, V Fester, A Sutherland, R du Toit, Cape Peninsula University</i><br>of Technology, South Africa; <i>R Holm, INNVENTIA, Sweden</i> | 287 |
| The sheet flow viscometer<br>P Slatter, RMPC, RMIT, Australia; R Haldenwang, IMST, CPUT, South Africa;<br>R Chhabra, IIT, Kanpur, India   | 299 |
| Pressure loss and discharge coefficients for non-Newtonian fluids in long<br>orifices<br>V G Fester, M R Chowdhury, Cape Peninsula University of Technology,<br>South Africa; F Iudicello, IHS-ESDU, UK   | 309 |

L Pullum, Private Consultant; L Graham, J Wu, CPSE, CSIRO, Australia

Bed establishment lengths under laminar flow

Method of determining the inherent viscosity of a slurry and other rheological trends as illustrated by a data bank of over 200 different slurries *A D Thomas, Slurry Systems Pty Limited, Australia* 325

#### FLOW BEHAVIOUR OF COARSE & FINE PARTICLE MIXTURES

| The effect of coarse particle addition on the rheology of fine clay slurries<br>E Paulsen, Cameco Corporation, Canada; R J Sumner, BHP Billiton Uranium,<br>Australia; R S Sanders, University of Alberta, Canada | 343 |
|---|-----|
| Studies on flow characteristics of fly ash-bottom ash mixture slurry at high concentrations <i>P K Senapati, B K Mishra, A Parida, Council of Scientific &amp; Industrial Research, India</i>                     | 363 |
| Flow behaviour of sand-water slurries   | 383 |

P Vlasak, Z Chara, Institute of Hydrodynamics ASCR, Czech Republic

261

## PIPELINE INTEGRITY ASSESSMENT

| Leak detection and other intelligence software for slurry pipelines<br>J Martinson, Ausenco PSI, USA   | 395        |
|--|------------|
| Oversized HDPE liners to combat internal corrosion and erosion in mining industry pipelines<br><i>J Thorne, NBS Incorporated, USA</i>  | 407        |
| Optimisation and monitoring of valves for GEHO piston diaphragm pumps<br>V Quites, Samarco Mineracao, Brazil; J Kuenen, J Sloesen, WEIR Minerals<br>Netherlands b.v., The Netherlands; J Abreu, WEIR Minerals Netherlands b.v.,<br>Brazil  | 423        |
| Development of a pilot-scale facility for evaluating wear in slurry pipeline<br>systems  | 431        |
| B Fotty, M Krantz, J Been, J Wolodko, Alberta Innovates – Technology Futures<br>(AITF), Canada   |            |
|  |            |
| PASTE AND HIGH DENSITY TAILINGS PUMPING  |            |
|  |            |
| Newmont's Boddington Gold Mine tailings pipelines. Hydraulic design issues<br>and comparisons with operating data<br>A D Thomas, Slurry Systems Pty Ltd; S Hart, Newmont Boddington Gold;<br>B Parker, I Edwards, Chemech Consulting Pty Ltd, Australia  | 447        |
| and comparisons with operating data<br>A D Thomas, Slurry Systems Pty Ltd; S Hart, Newmont Boddington Gold;  | 447<br>463 |
| and comparisons with operating data<br><i>A D Thomas, Slurry Systems Pty Ltd; S Hart, Newmont Boddington Gold;</i><br><i>B Parker, I Edwards, Chemech Consulting Pty Ltd, Australia</i><br>GLORES, the gateway to piston diaphragm pumps for high volume<br>applications<br><i>R van Rijswick, J Kuenen, A Wilmsen, J Sloesen, WEIR Minerals</i>   |            |
| and comparisons with operating data<br><i>A D Thomas, Slurry Systems Pty Ltd; S Hart, Newmont Boddington Gold;</i><br><i>B Parker, I Edwards, Chemech Consulting Pty Ltd, Australia</i><br>GLORES, the gateway to piston diaphragm pumps for high volume<br>applications<br><i>R van Rijswick, J Kuenen, A Wilmsen, J Sloesen, WEIR Minerals</i><br><i>Netherlands b.v., The Netherlands</i><br>Cost-effective pumping of paste and tailings at maximum solids concentration | 463        |

## SEWAGE SLUDGE HANDLING

| Assessment of 387 mm ID Mersey Valley sludge pipeline (MVSP) for transfer<br>of primary digested and thermally-hydrolysed digested sludge mixtures<br>N Heywood, N Alderman, BHR Group Ltd; M Rush, United Utilities, UK | 503 |
|--|-----|
| Flow of Newtonian and non-Newtonian fluids through static screens<br>S S Chandrawanshi, R P Chhabra, Indian Institute of Technology, Kanpur,<br>India  | 517 |

## AUTHOR INDEX