

2016 3rd Conference on Power Engineering and Renewable Energy (ICPERE 2016)

**Yogyakarta, Indonesia
29-30 November 2016**



**IEEE Catalog Number: CFP1646T-POD
ISBN: 978-1-5090-5109-0**

**Copyright © 2016 by the Institute of Electrical and Electronics Engineers, Inc
All Rights Reserved**

Copyright and Reprint Permissions: Abstracting is permitted with credit to the source. Libraries are permitted to photocopy beyond the limit of U.S. copyright law for private use of patrons those articles in this volume that carry a code at the bottom of the first page, provided the per-copy fee indicated in the code is paid through Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923.

For other copying, reprint or republication permission, write to IEEE Copyrights Manager, IEEE Service Center, 445 Hoes Lane, Piscataway, NJ 08854. All rights reserved.

****** This is a print representation of what appears in the IEEE Digital Library. Some format issues inherent in the e-media version may also appear in this print version.***

| | |
|-------------------------|-------------------|
| IEEE Catalog Number: | CFP1646T-POD |
| ISBN (Print-On-Demand): | 978-1-5090-5109-0 |
| ISBN (Online): | 978-1-5090-5108-3 |

Additional Copies of This Publication Are Available From:

Curran Associates, Inc
57 Morehouse Lane
Red Hook, NY 12571 USA
Phone: (845) 758-0400
Fax: (845) 758-2633
E-mail: curran@proceedings.com
Web: www.proceedings.com

CURRAN ASSOCIATES INC.
proceedings
.com

CONTENTS

| | | |
|--|--|----|
| Session 1. Power Electronics (1) | | |
| 29A1-1 | Improved Indirect Current Control for UtilityInteractive Inverter System with Critical Load | 1 |
| 29A1-2 | Suppressing The Effect of Unbalanced Grid in Current Controller of Grid Connected Inverter Using Virtual Inductor | 7 |
| 29A1-3 | PFM Controller with Phase Lead Characteristics Using Hysteretic Comparator for LLC Converter | 13 |
| 29A1-5 | The Effect of Safe Ball Size Changes on Boost Converter Using Hybrid Control | 19 |
| 29A1-6 | Variable Switching Period to Achieve Minimum Output Current Ripple of Discontinuous PWM Three-Phase Voltage Source Inverters | 25 |
| Session 2. Distributed Generation | | |
| 29B1-1 | Smart Diesel Generator to Compensate On-Grid PV Fluctuation: A Case Study in Sumba Island Indonesia | 33 |
| 29B1-2 | Design, Implementation and Techno-Economic Analysis of Hybrid PV-Diesel for Off-Grid System in Sebira Island | 39 |
| 29B1-3 | Study of a Renewable Energy Sources-Based Smart Grid. Requirements, Targets and Solutions | 45 |
| 29B1-4 | Non-Detection Zones of Voltage and Speed Relay for Synchronous Distributed Generation | |
| 29B1-5 | Study and Design of Hybrid Off-Grid PV-Generator Power System for Administration Load and Communal Load at Three Regions in Indonesia | 57 |
| Session 3. Electric Machinery | | |
| 29C1-1 | The Technical Problems to Modify Low Voltage Winding of Power Transformer | 63 |
| 29C1-2 | Effect of Core Cutting Topology on Inrush Current of Three-Phases Transformer | 69 |
| 29C1-3 | Influence of manufacturing process on Soft-Magnetic Properties of Iron Powder | |
| 29C1-4 | Design of Synchronous Generator 10625 kVA for Small Power-plant in Indonesia | 81 |
| 29C1-5 | Analysis of Magnetic Saturation Effect in Closed Form Solution of Synchronous Machine Short Circuit Transient By Using Linear Segment Method | 87 |

Session 4. Power Electronics (2)

| | | |
|--------|---|-----|
| 29A2-1 | Transient Response of Feedback Gain Changing DC-DC Converter for Line Variation | 93 |
| 29A2-2 | Parallel Operation of Transformerless 5 kW Bidirectional Inverter in PT. Len Industri | 99 |
| 29A2-3 | Output Current Ripple Minimization of Nine-phase PWM Inverters | 105 |
| 29A2-4 | A New Digital Hysteresis Current Control for Switching Power Converters | 113 |

Session 5. High Voltage (1)

| | | |
|--------|--|-----|
| 29B2-1 | Partial Discharge Patterns on Cross-Linked Polyethylene DC Power Cables | 119 |
| 29B2-2 | Effect of Water Content on Dielectric Properties and Partial Discharge Characteristics of Silicone Oil | 125 |
| 29B2-3 | Design And Testing Of Rogowski Coil Based PCB Double Helix For Gas Insulated Switchgear 150 KV Application | 131 |
| 29B2-4 | Design and Simulation of High Frequency Current Transformer as Partial Discharge Detector | 135 |
| 29B2-5 | Design of Planar Goubau Line Antenna for Detecting Partial Discharge on GIS | 141 |

Session 6. Electric Vehicle Technology

| | | |
|--------|---|-----|
| 29C2-1 | Desain Procedure for A 5 KW Mini Electric Vehicle Drive Train | 147 |
| 29C2-2 | Robust DC-Link Control Method Based On Voltage Deviation for High Voltage Battery Charger | 153 |
| 29C2-3 | Analysis of Power Converters for High Frequency Resonant Inductive Electric Vehicle Charging System | 159 |
| 29C2-4 | Power Drive System Product Development for Electric Vehicle in PT Len Industri | 165 |

Session 7. Industrial Application

| | | |
|--------|---|-----|
| 30A1-1 | Prototype Development of a Low Cost Data Logger and Monitoring System for PV Application | 171 |
| 30A1-2 | The Effect Of Voltage Variation (160-240 Volt) on Lighting Quality And Color Properties Of LED Lamps In Indonesia | 179 |
| 30A1-3 | Design, Implemetation and Calibration of Electric Field Mill | 185 |

| | | |
|--------|--|-----|
| 30A1-4 | Preliminary Design of Solar Thermal Power Generation - Indonesia Case Study | 191 |
| 30A1-5 | Investigation of Zero Sequence Capacitive Charging at Feeder X and Y on Ground Fault at Feeder Z | |
| 30A1-6 | Development of ARM Microcontroller-based QuasiResonant Inverter Induction Heater | 201 |

Session 8. High Voltage (2)

| | | |
|--------|---|-----|
| 30B1-1 | Effects of Thermal Ageing on the Dielectric Properties and Dissolved Gas Analysis in Ester from Palm Oil and Kraft Composite Paper Insulation | 209 |
| 30B1-2 | Effect of Bushing Material on the Electric Field Distribution of 150 kV GIS Bushing | 215 |
| 30B1-3 | Detection and Localization of Partial Discharge in Air-Insulated Substations Using UHF Antenna Array | 221 |
| 30B1-4 | Electric Field Optimization on 150 kV GIS Spacer by Modification of Spacer Shape and Conductor Configuration | 225 |
| 30B1-5 | Effects of Thermal Aging on Dielectric Properties and DGA of oil-paper Insulations | 231 |

Session 9. Power System

| | | |
|--------|--|-----|
| 30A2-1 | Radial Basis Function (RBF) Neural Network for Load Forecasting during Holiday | 235 |
| 30A2-2 | Solution of Dynamic Economic Dispatch Considered Dynamic Penalty Factor | 241 |
| 30A2-3 | The Performance Comparison between Fast Decoupled and Backward-Forward Sweep in Solving Distribution Systems | 247 |
| 30A2-4 | Data Organization Method For Energy Metering System | |
| 30A2-5 | Implementation of Axis Rotation Fast Decoupled Load Flow on Distribution System | 257 |

Session 10. High Voltage (3)

| | | |
|--------|--|-----|
| 30B2-1 | Modelling of Dry Lightning Impulse Test on 145 kV Oil Impregnated Paper Bushing for High Voltage Transformer | 263 |
| 30B2-2 | Locating Lightning Using Time of Arrival Method in Western Part of Java Island | 269 |
| 30B2-3 | Analysis of Lightning Strike to Overhead EHV 500 KV Transmission System Jawa – Bali Crossing | 275 |