

# **2018 IEEE ISAF-FMA-AMF-AMEC-PFM Joint Conference (IFAAP 2018)**

**Hiroshima, Japan  
27 May – 1 June 2018**



**IEEE Catalog Number: CFP18ISA-POD  
ISBN: 978-1-5386-1163-0**

**Copyright © 2018 by the Institute of Electrical and Electronics Engineers, Inc.  
All Rights Reserved**

*Copyright and Reprint Permissions:* Abstracting is permitted with credit to the source. Libraries are permitted to photocopy beyond the limit of U.S. copyright law for private use of patrons those articles in this volume that carry a code at the bottom of the first page, provided the per-copy fee indicated in the code is paid through Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923.

For other copying, reprint or republication permission, write to IEEE Copyrights Manager, IEEE Service Center, 445 Hoes Lane, Piscataway, NJ 08854. All rights reserved.

***\*\*\* This is a print representation of what appears in the IEEE Digital Library. Some format issues inherent in the e-media version may also appear in this print version.***

IEEE Catalog Number:	CFP18ISA-POD
ISBN (Print-On-Demand):	978-1-5386-1163-0
ISBN (Online):	978-1-5386-1162-3
ISSN:	1099-4734

**Additional Copies of This Publication Are Available From:**

Curran Associates, Inc  
57 Morehouse Lane  
Red Hook, NY 12571 USA  
Phone: (845) 758-0400  
Fax: (845) 758-2633  
E-mail: [curran@proceedings.com](mailto:curran@proceedings.com)  
Web: [www.proceedings.com](http://www.proceedings.com)

CURRAN ASSOCIATES INC.  
**proceedings**  
.com

# Proceedings of the 2018 IEEE ISAF-FMA-AMF-AMEC-PFM Joint Conference (IFAAP)

Hiroshima (Japan), May 27<sup>th</sup> – June 1<sup>st</sup>, 2018

## Table of Contents

	Page
<i>Data-Mining Driven Design for Novel Perovskite-type Piezoceramics</i> J. Yu, J. Li, Y. Jiang, and J. Chu	1
<i>An Ag decorated P(VDF-CTFE)/BT@HBP@PDA nanocomposites with double-shell core structure for high dielectric performance</i> W. Xia, Y. Yin, J. Xing, N. Zhang, and Z. Xu	5
<i>Ferromagnetism in barium titanate nanoparticles. Effect of annealing in hydrogen atmosphere on magnetic properties</i> N. A. Emelianov, L. N. Korotkov, W. M. Al Mandalawi, M. A. Kashirin, J. A. Roldan Lopez, and T. N. Korotkova	9
<i>Control of leakage current through BaTiO<sub>3</sub> film by cumulative cycle of applied voltage scanning for ReRAM or neuromorphic application</i> S. Maejima, M. Uchida, and M. Noda	12
<i>Origins of conduction at domain boundaries, LaAlO<sub>3</sub>/SrTiO<sub>3</sub> and surface for depolarization &amp; size effect</i> Y. Watanabe, D. Matsumoto, Y. Urakami, M. Okano, and A. Masuda	15
<i>Influence of K/Na ratio on the piezoelectric properties of the (K<sub>0.38</sub>Na<sub>0.52</sub>Li<sub>0.04</sub>)(Nb<sub>0.86</sub>Ta<sub>0.1</sub>Sb<sub>0.04</sub>)O<sub>2.97</sub> lead-free piezoceramics</i> A. Borta-Boyon and M. Pham-Thi	19
<i>Bi<sub>4</sub>Ti<sub>3</sub>O<sub>12</sub>/SrTiO<sub>3</sub> Sol-Gel Composite for Ultrasonic Transducers</i> S. Nozawa, T. Yamamoto and M. Kobayashi	23
<i>Domain switching by applied electric field in (001) and (111)-epitaxial (K<sub>0.5</sub>Na<sub>0.5</sub>)NbO<sub>3</sub> films</i> M. Kawano, T. Yamada, S. Matsuo, M. Yoshino, T. Nagasaki, O. Sakata, and Y. Imai	27
<i>Piezoelectric ultrasonic microsensors on buckled diaphragms using sol-gel derived PZT films</i> K. Yamashita, S. Nakajima, J. Shiomi, M. Noda, and P. Muralt	30
<i>Investigating the effects of losses of a piezoelectric transducer in temperature varying environment through Finite Element Analysis</i> T. Meurisse and D. Damjanovic	34
<i>Piezoelectric resonating force sensor in the second vibration mode</i> K. Yamashita and P. Muralt	38

<i>Performance and reliability of PZT-based piezoelectric micromirrors operated in realistic environments</i>	42
R. P. Dahl-Hansen, T. Tybell, and F. Tyholdt	
<i>Vibration mode analyses for circular wedge acoustic waveguides</i>	46
T.-H. Yu	