
Combating Representation Learning Disparity with Geometric Harmonization

Zhihan Zhou¹ Jiangchao Yao^{1,2†} Feng Hong¹ Ya Zhang^{1,2} Bo Han³ Yanfeng Wang^{1,2†}

¹Cooperative Medianet Innovation Center, Shanghai Jiao Tong University

²Shanghai AI Laboratory ³Hong Kong Baptist University

{zhihanzhou, Sunarker, feng.hong, ya.zhang, wangyanfeng}@sjtu.edu.cn
bhanml@comp.hkbu.edu.hk

Abstract

Self-supervised learning (SSL) as an effective paradigm of representation learning has achieved tremendous success on various curated datasets in diverse scenarios. Nevertheless, when facing the long-tailed distribution in real-world applications, it is still hard for existing methods to capture transferable and robust representation. Conventional SSL methods, pursuing *sample-level uniformity*, easily leads to representation learning disparity where head classes dominate the feature regime but tail classes passively collapse. To address this problem, we propose a novel Geometric Harmonization (GH) method to encourage *category-level uniformity* in representation learning, which is more benign to the minority and almost does not hurt the majority under long-tailed distribution. Specially, GH measures the population statistics of the embedding space on top of self-supervised learning, and then infer an fine-grained instance-wise calibration to constrain the space expansion of head classes and avoid the passive collapse of tail classes. Our proposal does not alter the setting of SSL and can be easily integrated into existing methods in a low-cost manner. Extensive results on a range of benchmark datasets show the effectiveness of GH with high tolerance to the distribution skewness. Our code is available at <https://github.com/MediaBrain-SJTU/Geometric-Harmonization>.

1 Introduction

Recent years have witnessed a great success of self-supervised learning to learn generalizable representation [7, 9, 15, 63]. Such rapid advances mainly benefit from the elegant training on the label-free data, which can be collected in a large volume. However, the real-world natural sources usually exhibit the long-tailed distribution [50], and directly learning representation on them can lead to the distortion issue of the embedding space, namely, the majority dominates the feature regime [75] and the minority collapses [47]. Thus, it becomes urgent to pay attention to representation learning disparity, especially as fairness of machine learning draws increasing attention [28, 41, 68, 77].

Different from the flourishing supervised long-tailed learning [29, 46, 68], self-supervised learning under long-tailed distributions is still under-explored, since there is no labels available for the calibration. Existing explorations to overcome this challenge mainly resort to the possible tailed sample discovery and provide the implicit bias to representation learning. For example, BCL [77] leverages the memorization discrepancy of deep neural networks (DNNs) on unknown head classes and tail classes to drive an instance-wise augmentation. SDCLR [28] contrasts the feature encoder and its pruned counterpart to discover hard examples that mostly covers the samples from tail classes, and efficiently enhance the learning preference towards tailed samples. DnC [59] resorts to a divide-and-conquer methodology to mitigate the data-intrinsic heterogeneity and avoid the representation

† The corresponding authors are Jiangchao Yao and Yanfeng Wang.




Figure 1: Comparison of Geometric Harmonization and the plain SSL method on a 2-D imbalanced synthetic dataset. (Left) Visualization of the 2-D synthetic dataset. (Middle) The embedding distribution of each category learnt by the vanilla contrastive learning loss is approximately proportional to the number of samples, leading to the undesired representation learning disparity. (Right) GH mitigates the adverse effect of class imbalance and approaches to the category-level uniformity.

collapse of minority classes. Liu et al. [41] adopts a data-dependent sharpness-aware minimization scheme to build support to tailed samples in the optimization. However, few works hitherto have considered the intrinsic limitation of the widely-adopted contrastive learning loss, and design the corresponding balancing mechanism to promote the representation learning parity.

We rethink the characteristic of the contrastive learning loss, and try to understand “*Why the conventional contrastive learning underperforms in self-supervised long-tailed context?*” To answer this question, let us consider two types of representation uniformity: (1) *Sample-level uniformity*. As stated in [62], the contrastive learning targets to distribute the representation of data points uniformly in the embedding space. Then, the feature span of each category is proportional to their corresponding number of samples. (2) *Category-level uniformity*. This uniformity pursues to split the region equally for different categories without considering their corresponding number of samples [49, 19]. In the class-balanced scenarios, the former uniformity naturally implies the latter uniformity, resulting in the equivalent separability for classification. However, in the long-tailed distributions, they are different: sample-level uniformity leads to the feature regime that is biased towards the head classes considering their dominant sample quantity and sacrifices the tail classes due to the limited sample quantity. By contrast, category-level uniformity means the equal allocation *w.r.t.* classes, which balances the space of head and tail classes, and is thus more benign to the downstream classification [17, 19, 37]. Unfortunately, there is no support for promoting category-level uniformity in contrastive learning loss, which explains the question arisen at the beginning.

In this study, we propose a novel method, termed as *Geometric Harmonization* (GH) to combat representation learning disparity in SSL under long-tailed distributions. Specially, GH uses a geometric uniform structure to measure the uniformity of the embedding space in the coarse granularity. Then, a surrogate label allocation is computed to provide a fine-grained instance-wise calibration, which explicitly compresses the greedy representation space expansion of head classes, and constrain the passive representation space collapse of tail classes. The alternation in the conventional loss refers to an extra efficient optimal-transport optimization that dynamically pursues the category-level uniformity. In Figure 1, we give a toy experiment¹ to visualize the distribution of the embedding space without and with GH. In a nutshell, our contributions can be summarized as follows,

1. To our best knowledge, we are the first to investigate the drawback of the contrastive learning loss in self-supervised long-tailed context and point out that the resulted sample-level uniformity is an intrinsic limitation to the representation parity, motivating us to pursue category-level uniformity with more benign downstream generalization (Section 3.2).
2. We develop a novel and efficient *Geometric Harmonization* (Figure 2) to combat the representation learning disparity in SSL, which dynamically harmonizes the embedding space of SSL to approach the category-level uniformity with the theoretical guarantee.
3. Our method can be easily plugged into existing SSL methods for addressing the data imbalance without much extra cost. Extensive experiments on a range of benchmark datasets demonstrate the consistent improvements in learning robust representation with our GH.

¹For more details, please refer to Appendix E.3.

2 Related Work

Self-Supervised Long-tailed Learning. There are several recent explorations devoted to this direction [40, 28, 59, 41, 77]. BCL [77] leverages the memorization effect of DNNs to automatically drive an instance-wise augmentation, which enhances the learning of tail samples. SDCLR [28] constructs a self-contrast between model and its pruned counterpart to learn more balanced representation. Classic Focal loss [40] leverages the loss statistics to putting more emphasis on the hard examples, which has been applied to self-supervised long-tailed learning [77]. DnC [59] benefits from the parameter isolation of multi-experts during the divide step and the information aggregation during the conquer step to prevent the dominant invasion of majority. Liu et al. [41] proposes to penalize the sharpness surface in a reweighting manner to calibrate class-imbalance learning. Recently, TS [35] employs a dynamic strategy on the temperature factor of contrastive loss, harmonizing instance discrimination and group-wise discrimination. PMSN [2] proposes the power-law distribution prior, replacing the uniform prior, to enhance the quality of learned representations.

Hyperspherical Uniformity. The distribution uniformity has been extensively explored from the physic area, *e.g.*, Thomson problem [58, 53], to machine learning area like some kernel-based extensions, *e.g.*, Riesz s -potential [21, 43] or Gaussian potential [12, 4, 62]. Some recent explorations regarding the features of DNNs [49, 17, 47] discover a terminal training stage when the embedding collapses to the geometric means of the classifier *w.r.t.* each category. Specially, these optimal class means specify a perfect geometric uniform structure with clear geometric interpretations and generalization guarantees [78, 67, 31]. In this paper, we first extend this intuition into self-supervised learning and leverage the specific structure to combat the representation disparity in SSL.

3 Method

3.1 Problem Formulation

We denote the dataset \mathcal{D} , for each data point $(\mathbf{x}, \mathbf{y}) \in \mathcal{D}$, the input $\mathbf{x} \in \mathbb{R}^m$ and the associated label $\mathbf{y} \in \{1, \dots, L\}$. Let N denote the number of samples, $R = N_{max}/N_{min}$ denote the imbalanced ratio (IR), where N_{max}, N_{min} is the number of samples in the largest and smallest class, respectively. Let n_i denote the number of samples in class i . In SSL, the ground-truth \mathbf{y} can not be accessed and the goal is to transform an image to an embedding via DNNs, *i.e.*, $f_\theta : \mathbb{R}^m \rightarrow \mathbb{R}^d$. In the linear probing evaluation, we construct a supervised learning task with balanced datasets. A linear classifier $g(\cdot)$ is built on top of the frozen $f_\theta(\cdot)$ to produce the prediction, *i.e.*, $g(f_\theta(\mathbf{x}))$.

3.2 Geometric Harmonization

As aforementioned, most existing SSL methods in long-tailed context leverage the contrastive learning loss, which encourages the sample-level uniformity in the embedding space. Considering the intrinsic limitation illustrated in Figure 1, we incorporate the geometric clues from the embedding space to calibrate the current loss, enabling our pursuit of category-level uniformity. In the following, we first introduce a specific geometric structure that is critical to Geometric Harmonization.

Definition 3.1. (Geometric Uniform Structure). Given a set of vertices $\mathbf{M} \in \mathbb{R}^{d \times K}$, the geometric uniform structure satisfies the following between-class duality

$$\mathbf{M}_i^\top \cdot \mathbf{M}_j = C, \quad \forall i, j \in \{1, 2, \dots, K\}, i \neq j, \quad (1)$$

where $\|\mathbf{M}_i\| = 1, \forall i \in \{1, 2, \dots, K\}$, K is the number of geometric vertices and C is a constant.

Above structure provides a characteristic that any two vectors in \mathbf{M} have the same angle, namely, the unit space are equally partitioned by the vectors in \mathbf{M} . This fortunately follows our expectation about category-level uniformity. Specially, if we use \mathbf{M} as a constant classifier to involve into training, and have the oracle label \mathbf{y} of the long-tailed data ($K = L$) to supervise the below prediction

$$\mathbf{q} = p(\mathbf{y}|f_\theta(\mathbf{x}), \mathbf{M}) = \exp(\mathbf{M}_y^\top \cdot f_\theta(\mathbf{x})/\gamma_{GH}) / \left(\sum_{i=1}^K \exp(\mathbf{M}_i^\top \cdot f_\theta(\mathbf{x})/\gamma_{GH}) \right), \quad (2)$$

then according to the neural collapse theory [49], the representation of all samples will fit the geometric uniform structure of \mathbf{M} in the limit, namely, approach category-level uniformity. However,




Figure 2: **Overview of Geometric Harmonization (w/ InfoNCE)**. To achieve harmonization with the category-level uniformity, we require ground-truth labels for supervision during training. However, these labels are not available under the self-supervised paradigm. Moreover, estimating surrogate labels directly from the geometric uniform structure is challenging and noisy, especially when the representation is not ideally distributed. To fulfill this gap, we utilize the geometric uniform structure to measure the embedding space, and the captured population statistics are used for an instance-wise calibration by surrogate label allocation, which provides a supervision feedback to counteract the sample-level uniformity. Specially, our method are theoretically grounded to approach category-level uniformity at the loss minimum. The additional model parameters incurred by GH are analytically and empirically demonstrated to be trained in an efficient manner.

the technical challenge is the complete absence of annotation \mathbf{y} in our context, making directly constructing the objective $\min \mathbb{E}[\mathbf{y} \log \mathbf{q}]$ with Eq. (2) impossible to combat the representation disparity.

Surrogate Label Allocation. To address the problem of unavailable labels, we explore constructing the surrogate geometric labels $\hat{\mathbf{q}}$ to supervise the training of Eq. (2). Concretely, we utilize the recent discriminative clustering idea [1] to acquire such geometric labels, formulated as follows

$$\min_{\hat{\mathbf{Q}}=[\hat{\mathbf{q}}_1, \dots, \hat{\mathbf{q}}_N]} \mathcal{L}_{\text{GH}} = -\frac{1}{|\mathcal{D}|} \sum_{\mathbf{x}_i \sim \mathcal{D}} \hat{\mathbf{q}}_i \log \mathbf{q}_i, \quad \text{s.t. } \hat{\mathbf{Q}} \cdot \mathbb{1}_N = N \cdot \boldsymbol{\pi}, \quad \hat{\mathbf{Q}}^\top \cdot \mathbb{1}_K = \mathbb{1}_N, \quad (3)$$

where $\hat{\mathbf{q}}_i$ refers to the soft assignment constrained in a K -dimensional probability simplex and $\boldsymbol{\pi} \in \mathbb{R}_+^K$ refers to the distribution constraint. As we are dealing with long-tailed data, we propose to use the geometric uniform structure \mathbf{M} to automatically compute the population statistic of the embedding space as $\boldsymbol{\pi}$. Finally, Eq. (3) can be analytically solved by *Sinkhorn-Knopp algorithm* [14] (refer to Appendix D for Algorithm 1). Note that, the above idea builds upon a conjecture: the constructed surrogate geometric labels are mutually correlated with the oracle labels so that they have the similar implication to approach category-level uniformity. We will empirically verify the rationality of such an assumption via *normalized mutual information* in Section 4.4.

Overall Objective. Eq. (3) can be easily integrated into previous self-supervised long-tailed learning methods for geometric harmonization, *e.g.*, SDCLR [28] and BCL [77]. For simplicity, we take their conventional InfoNCE loss [48] as an example and write the overall objective as follows

$$\min_{\theta, \hat{\mathbf{Q}}} \mathcal{L} = \mathcal{L}_{\text{InfoNCE}} + w_{\text{GH}} \mathcal{L}_{\text{GH}}, \quad (4)$$

where w_{GH} represents the weight of the geometric harmonization loss. Optimizing Eq. (4) refers to a bi-level optimization style: in the outer-loop, optimize $\min_{\hat{\mathbf{Q}}} \mathcal{L}_{\text{GH}}$ with fixing θ to compute the surrogate geometric labels; in the inner-loop, optimize $\min_{\theta} \mathcal{L}_{\text{InfoNCE}} + \mathcal{L}_{\text{GH}}$ with fixing $\hat{\mathbf{Q}}$ to learn the representation model. The additional cost compared to the vanilla method primarily arises from from the outer-loop, which will be discussed in Section 3.4 and verified in Section 4.4.

Compared with previous explorations [1, 7], the uniqueness of GH lies in the following three aspects: (1) *Geometric Uniform Structure*. The pioneering works mainly resort to a learnable classifier to perform clustering, which can easily be distorted in the long-tailed scenarios [17]. Built on

the geometric uniform classifier, our method is capable to provide high-quality clustering results with clear geometric interpretations. (2) *Flexible Class Prior*. The class prior π is assumed to be uniform among the previous attempts. When moving to the long-tailed case, this assumption will strengthen the undesired sample-level uniformity. In contrast, our methods can potentially cope with any distribution with the automatic surrogate label allocation. (3) *Theoretical Guarantee*. GH is theoretically grounded to achieve the category-level uniformity in the long-tailed scenarios (refer to Section 3.3), which has never been studied in previous methods. To gain more insights into our method, we further compare GH with discriminative clustering methods (SeLA [1], SwAV [7]) and investigate the impact of various components in GH. From the results in Table 1, we can see that GH consistently outperforms the vanilla discriminative clustering baselines in the linear probing evaluation. Notably, we observe that both GUS and the class prior π play a critical role in our GH.

Table 1: Linear probing of vanilla discriminative clustering methods and variants of GH on CIFAR-100-LT.

| IR | SimCLR | +SeLA | +SwAV | +GH | w/o GUS | w/o π |
|-----|--------|-------|-------|------|---------|-----------|
| 100 | 50.7 | 50.5 | 52.2 | 54.0 | 53.3 | 53.1 |
| 50 | 52.2 | 52.0 | 53.0 | 55.4 | 54.6 | 54.4 |
| 10 | 55.7 | 56.0 | 56.1 | 57.4 | 56.7 | 56.4 |

3.3 Theoretical Understanding

Here, we reveal the theoretical analysis of GH on promoting the representation learning to achieve category-level uniformity instead of sample-level uniformity. Let us begin with a deteriorated case of sample-level uniformity under the extreme imbalance, *i.e.*, minority collapse [17].

Lemma 3.2. (*Minority collapse*) Assume the samples follow the uniform distribution $n_1 = n_2 = \dots = n_{L_H} = n_H$, $n_{L_H+1} = n_{L_H+2} = \dots = n_L = n_T$ in head and tail classes respectively. Assume $d \geq L$ and $n_H/n_T \rightarrow +\infty$, the lower bound (Lemma C.1) of $\mathcal{L}_{\text{InfoNCE}}$ achieves the minimum when the class means of the tail classes collapse to an identical vector:

$$\lim \boldsymbol{\mu}_i - \boldsymbol{\mu}_j = \mathbf{0}_L, \forall L_H \leq i \leq j \leq L,$$

where $\boldsymbol{\mu}_l = \frac{1}{n_l} \sum_{i=1}^{n_l} f_{\theta}(\mathbf{x}_{l,i})$ denotes the class means and $\mathbf{x}_{l,i}$ is the i -th data point with label l .

This phenomenon indicates all representations of the minority will collapse completely to one point without considering the category discrepancy, which aligns with our observation regarding the passive collapse of tailed samples in Figure 1. To further theoretically analyze GH, we first quantitatively define category-level uniformity in the following, and then theoretically claim that with the geometric uniform structure (Definition 3.1) and the perfect aligned allocation (Eq. (3)), we can achieve the loss minimum at the stage of realizing category-level uniformity.

Definition 3.3. (Categorical-level Uniformity) We define categorical-level uniformity on the embedding space *w.r.t* the geometric uniform structure \mathbf{M} when it satisfies

$$\boldsymbol{\mu}_k^* = \mathbf{M}_k, \forall k = 1, 2, \dots, K,$$

where $\boldsymbol{\mu}_k^* = \frac{1}{n_k} \sum_{i=1}^{n_k} f_{\theta}^*(\mathbf{x}_{k,i})$ represents the class mean for samples assigned with the surrogate geometric label k in the embedding space.

Theorem 3.4. (*Optimal state for \mathcal{L}*) Given Eq. (4) under the proper optimization strategy, when it arrives at the category-level uniformity (Definition 3.3) defined on the geometric uniform structure \mathbf{M} (Definition 3.1), we will achieve the minimum of the overall loss \mathcal{L}^* as

$$\mathcal{L}^* = -2 \sum_{l=1}^L \pi_l^y \log(1 / (1 + (K - 1) \exp(C - 1))) + \log(J/L), \quad (5)$$

where J denotes the size of the collection of the negative samples and π^y refers to the marginal distribution of the latent ground-truth labels \mathbf{y} .

This guarantees the desirable solution with the minimal intra-class covariance and the maximal inter-class covariance under the geometric uniform structure [49, 17], which benefits the downstream generalization. Notably, no matter the data distribution is balanced or not, our method can persistently maintain the theoretical merits on calibrating the class means to achieve category-level uniformity. We also empirically demonstrate the comparable performance with GH on the balanced datasets in Section 4.4, as in this case category-level uniformity is equivalent to sample-level uniformity.

3.4 Implementation and Complexity analysis

In Algorithm 2 of Appendix D, we give the complete implementation of our method. One point that needs to be clarified is that we learn the label allocation \hat{q} in the mini-batch manner. In addition, the geometric prediction q and the adjusted \hat{q} are computed at the beginning of every epoch as the population-level statistic will not change much in a few mini-batches. Besides, we maintain a momentum update mechanism to track the prediction of each sample to stabilize the training, *i.e.*, $q^m \leftarrow \beta q^m + (1 - \beta)q$. When combined with the joint-embedding loss, we naturally adopt a cross-supervision mechanism $\min \mathbb{E}[\hat{q}^+ \log q]$ for the reconciliation with contrastive baselines. The proposed method is illustrated in Figure 2 for visualization.

For complexity, assume that the standard optimization of deep neural networks requires forward and backward step in each mini-batch update with the time complexity as $\mathcal{O}(B\Lambda)$, where B is the mini-batch size and Λ is the parameter size. At the parameter level, we add an geometric uniform structure with the complexity as $\mathcal{O}(BKd)$, where K is the number of geometric labels and d is the embedding dimension. For Sinkhorn-Knopp algorithm, it only refers to a simple matrix-vector multiplication as shown in Algorithm 1, whose complexity is $\mathcal{O}(E_s(B + K + BK))$ with the iteration step E_s . The complexity incurred in the momentum update is $\mathcal{O}(BK)$. Since K, d and E_s are significantly smaller than the model parameter Λ of a million scale, the computational overhead involved in GH is negligible compared to $\mathcal{O}(B\Lambda)$. The additional storage for a mini-batch of samples is the matrix $Q^m \in \mathbb{R}^{K \times B}$, which is also negligible to the total memory usage. To the end, GH incurs only a small computation or memory cost and thus can be plugged to previous methods in a low-cost manner. The empirical comparison about the computational cost is summarized in Table 17.

4 Experiments

4.1 Experimental Setup

Baselines. We mainly choose five baseline methods, including (1) *plain contrastive learning*: SimCLR [9], (2) *hard example mining*: Focal [40], (3) *asymmetric network pruning*: SDCLR [28], (4) *multi-expert ensembling*: DnC [59], (5) *memorization-guided augmentation*: BCL [77]. Empirical comparisons with more baseline methods can be referred to Appendix F.3.

Implementation Details. Following previous works [28, 77], we use ResNet-18 [23] as the backbone for small-scale dataset (CIFAR-100-LT [5]) and ResNet-50 [23] for large-scale datasets (ImageNet-LT [44], Places-LT [44]). For experiments on CIFAR-100-LT, we train model with the SGD optimizer, batch size 512, momentum 0.9 and weight decay factor 5×10^{-4} for 1000 epochs. For experiments on ImageNet-LT and Places-LT, we only train for 500 epochs with the batch size 256 and weight decay factor 1×10^{-4} . For learning rate schedule, we use the cosine annealing decay with the learning rate $0.5 \rightarrow 1e^{-6}$ for all the baseline methods. As GH is combined with baselines, a proper warming-up of 500 epochs on CIFAR-100-LT and 400 epochs on ImageNet-LT and Places-LT are applied. The cosine decay is set as $0.5 \rightarrow 0.3, 0.3 \rightarrow 1e^{-6}$ respectively. For hyper-parameters of GH, we provide a default setup across all the experiments: set the geometric dimension K as 100, w_{GH} as 1 and the temperature γ_{GH} as 0.1. In the surrogate label allocation, we set the regularization coefficient λ as 20 and Sinkhorn iterations E_s as 300. Please refer to Appendix E.3 for more experimental details.

Evaluation Metrics. Following [28, 77], *linear probing* on a balanced dataset is used for evaluation. We conduct full-shot evaluation on CIFAR-100-LT and few-shot evaluation on ImageNet-LT and Places-LT. For comprehensive performance comparison, we present the linear probing performance and the standard deviation among three disjoint groups, *i.e.*, [many, medium, few] partitions [44].

4.2 Linear Probing Evaluation

CIFAR-100-LT. In Table 2, we summarize the linear probing performance of baseline methods *w/* and *w/o* GH on a range of benchmark datasets, and provide the analysis as follows.

(1) *Overall Performance.* GH achieves the competitive results *w.r.t* the [many, medium, few] groups, yielding a overall performance improvements averaging as 2.32%, 2.49% and 1.52% on CIFAR-100-LT with different imbalanced ratios. It is worth noting that on the basis of the previous state-of-the-art BCL, our GH further achieves improvements by 1.20%, 1.82% and 1.22%, respectively. Our

Table 2: Linear probing results on CIFAR-100-LT with different imbalanced ratios (100, 50, 10), ImageNet-LT and Places-LT. Many/Med/Few (\uparrow) indicate the average accuracy (%) *w.r.t* fine-grained partitions according to the class cardinality. Std (\downarrow) means the standard deviation of the group-level performance and Avg (\uparrow) is the average accuracy (%) of the full test set. Following the previous work [28, 77], Std represents a balancedness measure to quantify the variance among three specified groups. Improv. (\uparrow) represents the averaging performance improvements *w.r.t.* different baseline methods. **We report the error bars with the multi-run experiments in Table 12 in Appendix F.**

| Dataset | | SimCLR | +GH | Focal | +GH | SDCLR | +GH | DnC | +GH | BCL | +GH | Improv. |
|-------------|------|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------------|
| CIFAR-R100 | Many | 54.97 | 57.38 | 54.24 | 57.01 | 57.32 | 57.44 | 55.41 | 57.56 | 59.15 | 59.50 | +1.56 |
| | Med | 49.39 | 52.27 | 49.58 | 52.93 | 50.70 | 52.85 | 51.30 | 53.74 | 54.82 | 55.73 | +2.35 |
| | Few | 47.67 | 52.12 | 49.21 | 51.74 | 50.45 | 54.06 | 50.76 | 53.26 | 55.30 | 57.67 | +3.09 |
| | Std | 3.82 | 2.99 | 2.80 | 2.76 | 3.90 | 2.38 | 2.54 | 2.36 | 2.37 | 1.89 | -0.61 |
| | Avg | 50.72 | 53.96 | 51.04 | 53.92 | 52.87 | 54.81 | 52.52 | 54.88 | 56.45 | 57.65 | +2.32 |
| CIFAR-R50 | Many | 56.00 | 58.88 | 55.40 | 57.97 | 57.50 | 58.47 | 56.03 | 59.04 | 59.44 | 60.82 | +2.16 |
| | Med | 50.48 | 53.00 | 51.14 | 53.55 | 51.85 | 53.88 | 52.68 | 55.05 | 54.73 | 57.58 | +2.44 |
| | Few | 50.12 | 54.27 | 50.02 | 53.58 | 52.15 | 53.58 | 50.83 | 54.81 | 57.30 | 58.55 | +2.87 |
| | Std | 3.30 | 3.09 | 2.84 | 2.54 | 3.18 | 2.74 | 2.64 | 2.38 | 2.36 | 1.66 | -0.38 |
| | Avg | 52.24 | 55.42 | 52.22 | 55.06 | 53.87 | 55.34 | 53.21 | 56.33 | 57.18 | 59.00 | +2.49 |
| CIFAR-R10 | Many | 57.85 | 59.26 | 58.18 | 60.06 | 58.47 | 59.21 | 59.82 | 61.09 | 60.41 | 61.41 | +1.26 |
| | Med | 55.06 | 56.91 | 55.82 | 56.79 | 54.79 | 56.06 | 56.67 | 58.33 | 57.15 | 59.27 | +1.57 |
| | Few | 54.03 | 55.85 | 54.64 | 57.24 | 52.97 | 55.58 | 56.21 | 57.33 | 59.76 | 60.30 | +1.74 |
| | Std | 1.98 | 1.75 | 1.80 | 1.77 | 2.80 | 1.97 | 1.96 | 1.95 | 1.73 | 1.07 | -0.35 |
| | Avg | 55.67 | 57.36 | 56.23 | 58.05 | 55.44 | 56.97 | 57.59 | 58.94 | 59.12 | 60.34 | +1.52 |
| ImageNet-LT | Many | 41.69 | 41.53 | 42.04 | 42.55 | 40.87 | 41.92 | 41.70 | 42.19 | 42.92 | 43.22 | +0.44 |
| | Med | 33.96 | 36.35 | 35.02 | 36.75 | 33.71 | 36.53 | 34.68 | 36.63 | 35.89 | 38.16 | +2.23 |
| | Few | 31.82 | 35.84 | 33.32 | 36.28 | 32.07 | 36.04 | 33.58 | 35.86 | 33.93 | 36.96 | +3.25 |
| | Std | 5.19 | 3.15 | 4.62 | 3.49 | 4.68 | 3.26 | 4.41 | 3.45 | 4.73 | 3.32 | -1.39 |
| | Avg | 36.65 | 38.28 | 37.49 | 38.92 | 36.25 | 38.53 | 37.23 | 38.67 | 38.33 | 39.95 | +1.68 |
| Places-LT | Many | 31.98 | 32.46 | 31.69 | 32.40 | 32.17 | 32.78 | 32.07 | 32.51 | 32.69 | 33.22 | +0.55 |
| | Med | 34.05 | 35.03 | 34.33 | 35.14 | 34.71 | 35.60 | 34.51 | 35.55 | 35.37 | 36.00 | +0.87 |
| | Few | 35.63 | 36.14 | 35.73 | 36.49 | 35.69 | 36.18 | 35.84 | 35.91 | 37.18 | 37.62 | +0.45 |
| | Std | 1.83 | 1.89 | 2.05 | 2.08 | 1.82 | 1.82 | 1.91 | 1.87 | 2.26 | 2.23 | 0.00 |
| | Avg | 33.61 | 34.33 | 33.65 | 34.42 | 33.99 | 34.70 | 33.90 | 34.52 | 34.76 | 35.32 | +0.68 |

GH consistently improves performance across datasets with varying degrees of class imbalance, demonstrating its potential to generalize to practical scenarios with more complex distributions. Specially, our method does not require any prior knowledge or assumptions about the underlying data distribution, highlighting the robustness and versatility to automatically adapt to the data.

(2) *Representation Balancedness.* In Section 1, we claim that GH helps compress the expansion of head classes and avoid the passive collapse of tail classes, yielding the more balanced representation distribution. To justify this aspect, we compare the variance in linear probing performance among many/medium/few groups, namely, their groupwise standard deviation. According to Table 2, our GH provides [1.56%, 2.35%, 3.09%], [2.16%, 2.44%, 2.87%] and [1.26%, 1.57%, 1.74%] improvements *w.r.t* [many, medium, few] groups on CIFAR-100-LT-R100/R50/R10 with more preference to the minority classes for representation balancedness. Overall, GH substantially improves the standard deviation by [0.61, 0.38, 0.35] on different levels of imbalance.

ImageNet-LT and Places-LT. Table 2 shows the comparison of different baseline methods on large-scale dataset ImageNet-LT and Places-LT, in which we have consistent observations. As can be seen, on more challenging real-world dataset, GH still outperforms other methods in terms of overall accuracy, averaging as 1.68%, 0.68% on ImageNet-LT and Places-LT. Specifically, our method provides [0.44%, 2.23%, 3.25%] and [0.55%, 0.87%, 0.45%] improvements in linear probing *w.r.t.* [many, medium, few] groups on ImageNet-LT and Places-LT. The consistent performance overhead indicates the robustness of our method to deal with long-tailed distribution with different characteristics. Moreover, the averaging improvement of standard deviation is 1.39 on ImageNet-LT, indicating the comprehensive merits of our GH on the minority classes towards the representation balancedness. However, an interesting phenomenon is that the fine-grained performance exhibits a different trend on Places-LT. As can be seen, the performance of head classes is even worse than that of tail classes. The lower performance of the head partition can be attributed to the fact that it contains more chal-

Table 3: Supervised long-tailed learning by finetuning on CIFAR-100-LT, ImageNet-LT and Places-LT. We compare the performance of five self-supervised learning methods as the pre-training stage for downstream supervised logit adjustment [46] method. Improv. (\uparrow) represents the averaging stage performance improvements *w.r.t.* different baseline methods. Besides, the performance of logit adjustment via learning from scratch is also reported for comparisons.

| Dataset | LA | Logit adjustment pretrained with the following SSL methods | | | | | | | | | | Improv. |
|-------------|-------|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------------|
| | | SimCLR | +GH | Focal | +GH | SDCLR | +GH | DnC | +GH | BCL | +GH | |
| CIFAR-LT | 46.61 | 49.81 | 50.84 | 49.83 | 51.04 | 49.79 | 50.73 | 49.97 | 50.84 | 50.38 | 51.32 | +1.00 |
| ImageNet-LT | 48.27 | 51.10 | 51.67 | 51.15 | 51.82 | 50.94 | 51.64 | 51.31 | 51.88 | 51.43 | 52.06 | +0.63 |
| Places-LT | 27.07 | 32.63 | 33.86 | 32.69 | 33.75 | 32.55 | 34.03 | 32.98 | 34.09 | 33.15 | 34.48 | +1.24 |

Table 4: Image classification on ImageNet, Places and fine-grained visual classification on various fine-grained datasets, pretrained on large-scale long-tailed CC3M and then finetuned.

| | Image Classification | | Fine-Grained Visual Classification | | | | | | Average |
|--------|----------------------|--------------|------------------------------------|--------------|--------------|--------------|--------------|--------------|---------|
| | ImageNet | Places | CUB200 | Aircraft | StanfordCars | StanfordDogs | NABirds | | |
| SimCLR | 52.06 | 37.65 | 44.61 | 65.89 | 57.63 | 50.99 | 46.86 | 53.20 | |
| +GH | 53.39 | 38.47 | 45.76 | 68.08 | 60.24 | 52.88 | 47.58 | 54.91 | |

lenging classes. As a result, we observe that the standard deviation of our GH does not significantly decrease on Places-LT, which requires more effort and exploration for improvement alongside GH.

4.3 Downstream Finetuning Evaluation

Downstream supervised long-tailed learning. Self-supervised learning has been proved to be beneficial as a pre-training stage of supervised long-tailed recognition to exclude the explicit bias from the class imbalance [68, 41, 77].

To validate the effectiveness of our GH, we conduct self-supervised pre-training as the initialization for downstream supervised classification tasks on CIFAR-100-LT-R100, ImageNet-LT and Places-LT. The state-of-the-art logit adjustment [46] is chosen as the downstream baseline. The combination of GH + LA can be interpreted as a compounded method where GH aims at the re-balanced representation extraction and LA targets the classifier debiasing. In Table 3, we can find that the superior performance improvements are achieved by self-supervised pre-training over the plain supervised learning baseline. Besides, our method can also consistently outperform other SSL baselines, averaging as 1.00%, 0.63% and 1.24% on CIFAR-100-LT-R100, ImageNet-LT and Places-LT. These results demonstrate that GH are well designed to facilitate long-tailed representation learning and improve the generalization for downstream supervised tasks.

Cross-dataset transfer learning. To further demonstrate the representation transferability of our GH, we conduct more comprehensive experiments on the large-scale, long-tailed dataset CC3M [52] with various cross-dataset transferring tasks, including downstream classification, object detection and instance segmentation. Specifically, we report the finetuning classification performance on ImageNet, Places and fine-grained visual datasets Caltech-UCSD Birds (CUB200) [61], Aircrafts [45], Stanford Cars [33], Stanford Dogs [32], NABirds [60]. Besides, we evaluate the quality of the learned representation by finetuning the model for object detection and instance segmentation on COCO2017 benchmark [39]. As shown in Tables 4 and 5, we can see that our proposed GH consistently outperforms the baseline across various tasks and datasets. It further demonstrates the importance of considering long-tailed data distribution under large-scale unlabeled data in the pre-training stage. This can potentially be attributed to that our geometric harmonization motivates a more balanced and general embedding space, improving the generalization ability of the pretrained model to a range of real-world downstream tasks.

4.4 Further Analysis and Ablation Studies

Dimension of Geometric Uniform Structure. As there is even no category number L available in SSL paradigm, we empirically compare our GH with different geometric dimension K on CIFAR-100-LT-R100, as shown in Figure 3(a). From the results, GH is generally robust to the change of

Table 5: Object detection and instance segmentation with Table 6: Inter-class uniformity (\uparrow) and finetuned features on COCO2017 benchmark, pretrained neighborhood uniformity (\uparrow) of pretrained on large-scale long-tailed CC3M. features on CIFAR-LT.

| | Object Detection | | | Instance Segmentation | | | Inter-class Uniformity | | Neighborhood Uniformity | | |
|--------|--------------------|----------------------------------|----------------------------------|-----------------------|----------------------------------|----------------------------------|------------------------|------|-------------------------|------|-------------|
| | AP ^{bbox} | AP ₅₀ ^{bbox} | AP ₇₅ ^{bbox} | AP ^{mask} | AP ₅₀ ^{mask} | AP ₇₅ ^{mask} | SimCLR | +GH | SimCLR | +GH | |
| SimCLR | 31.7 | 51.0 | 33.9 | 30.2 | 49.8 | 32.1 | C100 | 1.00 | 2.80 | 0.72 | 2.00 |
| +GH | 32.7 | 52.2 | 35.2 | 31.1 | 50.8 | 33.0 | C50 | 1.23 | 2.73 | 0.91 | 1.94 |
| | | | | | | | C10 | 1.18 | 2.60 | 0.85 | 1.83 |




Figure 3: (a) Linear probing performance *w.r.t.* the dimension K of the geometric uniform structure \mathbf{M} (Appendix B) on CIFAR-LT-R100. (b) NMI score between the surrogate geometric labels and the ground-truth labels in the training stage on CIFAR-LT-R100. (c) Average linear probing and the error bars of the surrogate label allocation with variants of the label prior on CIFAR-LT-R100.

K , but slightly exhibits the performance degeneration when the dimension is extremely large or small. Intuitively, when K is extremely large, our GH might pay more attention to the uniformity among sub-classes, while the desired uniformity on classes is not well guaranteed. Conversely, when K is extremely small, the calibration induced by GH is too coarse that cannot sufficiently avoid the internal collapse within each super-class. For discussions of the structure, it can refer to Appendix B.

Surrogate Label Quality Uncovered. To justify the effectiveness of surrogate label allocation, we compare the NMI scores [54] between the surrogate and ground-truth label in Figure 3(b). We observe that GH significantly improves the NMI scores across baselines, indicating that the geometric labels are effectively calibrated to better capture the latent semantic information. Notably, the improvements of the existing works are marginal, which further verifies the superiority of GH.

Exploration with Other Label-Distribution Prior. To further understand π , we assume the ground-truth label distribution is available and incorporate the oracle π^y into the surrogate label allocation. Comparing the results of the softened variants $\pi_{\gamma_T}^y$ with the temperature γ_T in Figure 3(c), we observe that GH outperforms all the counterparts equipped with the oracle prior. A possible reason is that our method automatically captures the inherent geometric statistics from the embedding space, which is more reconcilable to the self-supervised learning objectives.

Uniformity Analysis. In this part, we conduct experiments with two uniformity metrics [62, 37]:

$$U = \frac{1}{L(L-1)} \sum_{i=1}^L \sum_{j=1, j \neq i}^L \|\mu_i - \mu_j\|_2, \quad U_k = \frac{1}{Lk} \sum_{i=1}^L \min_{j_1, \dots, j_k} \left(\sum_{m=1}^k \|\mu_i - \mu_{j_m}\|_2 \right),$$

where $j_1, \dots, j_k \neq i$ represent different classes. Specifically, U evaluates average distances between different class centers and U_k measures how close one class is to its neighbors. As shown in Table 6, our GH outperforms in both inter-class uniformity and neighborhood uniformity when compared with the baseline SimCLR [9]. This indicates that vanilla contrastive learning struggles to achieve the uniform partitioning of the embedding space, while our GH effectively mitigates this issue.

Comparison with More SSL Methods. In Table 7, we present a more comprehensive comparison of different SSL baseline methods, including MoCo-v2 [24], MoCo-v3 [11] and various non-contrastive methods such as SimSiam [10], BYOL [20] and Barlow Twins [71]. From the results, we can see that the combinations of different SSL methods and our GH can achieve consistent performance improvements, averaging as 2.33%, 3.18% and 2.21% on CIFAR-100-LT. This demonstrates the prevalence of representation learning disparity under data imbalance in general SSL settings.

Table 7: Linear probing of more SSL variants on CIFAR-100-LT with different imbalanced ratios.

| Dataset | SimSiam | +GH | Barlow | +GH | BYOL | +GH | MoCo-v2 | +GH | MoCo-v3 | +GH |
|------------|---------|-------|--------|-------|-------|-------|---------|-------|---------|-------|
| CIFAR-R100 | 49.01 | 51.43 | 48.70 | 51.23 | 51.43 | 52.87 | 51.49 | 53.53 | 54.08 | 55.82 |
| CIFAR-R50 | 48.98 | 53.54 | 49.29 | 51.95 | 52.04 | 53.84 | 52.68 | 55.01 | 55.34 | 56.45 |
| CIFAR-R10 | 55.51 | 57.03 | 53.11 | 56.34 | 55.86 | 57.28 | 58.23 | 60.11 | 59.10 | 60.57 |






Figure 4: T-SNE visualization of the pre-trained features from 8 randomly selected classes *w.r.t* CIFAR-LT training images.

Figure 5: Ablations of w_{GH} on CIFAR-LT.

On Importance of Bi-Level Optimization. In Table 8, we empirically compare the direct joint optimization strategy to Eq. (4). From the results, we can see that the joint optimization (*w/* or *w/o* the warm-up strategy) does not bring significant performance improvement over SimCLR compared with that of our bi-level optimization, probably due to the undesired collapse in label allocation [1]. This demonstrates the necessity of the proposed bi-level optimization for Eq. (4) to stabilize the training.

Qualitative Visualization. We conduct t-SNE visualization of the learned features to provide further qualitative intuitions. For simplicity, we randomly selected four head classes and four tail classes on CIFAR-LT to generate the t-SNE plots. Based on the results in Figure 4, the observations are as follows: (1) SimCLR: head classes exhibit a large presence in the embedding space and heavily squeeze the tail classes, (2) GH: head classes reduce their occupancy, allowing the tail classes to have more space. This further indicates that the constructed surrogate labels can serve as the high-quality supervision, effectively guiding the harmonization towards the geometric uniform structure.

Sensitivity Analysis. To further validate the stability of our GH, We conduct empirical comparison with different weight w_{GH} , temperature γ_{GH} , regularization coefficient λ and Sinkhorn iteration E_s on CIFAR-LT, as shown in Figures 5 and 7. From the results, we can see that our GH can consistently achieve satisfying performance with different hyper-parameter.

5 Conclusion

In this paper, we delve into the defects of the conventional contrastive learning in self-supervised long-tail context, *i.e.*, representation learning disparity, motivating our exploration on the inherent intuition for approaching the category-level uniformity. From the geometric perspective, we propose a novel and efficient Geometric Harmonization algorithm to counteract the long-tailed effect on the embedding space, *i.e.*, over expansion of the majority class with the passive collapse of the minority class. Specially, our proposed GH leverages the geometric uniform structure as an optimal indicator and manipulate a fine-grained label allocation to rectify the distorted embedding space. We theoretically show that our proposed method can harmonize the desired geometric property in the limit of loss minimum. It is also worth noting that our method is orthogonal to existing self-supervised long-tailed methods and can be easily plugged into these methods in a lightweight manner. Extensive experiments demonstrate the consistent efficacy and robustness of our proposed GH. We believe that the geometric perspective has the great potential to evolve the general self-supervised learning paradigm, especially when coping with the class-imbalanced scenarios.

Table 8: Linear probing of joint optimization on CIFAR-100-LT with different IRs.

| Method | C100 | C50 | C10 |
|----------------|-------|-------|-------|
| SimCLR | 50.72 | 52.24 | 55.67 |
| +GH (Joint) | 50.18 | 52.31 | 54.98 |
| w/ warm-up | 51.14 | 52.75 | 55.37 |
| +GH (Bi-level) | 53.96 | 55.42 | 57.36 |

Acknowledgement

This work was supported by the National Key R&D Program of China (No. 2022ZD0160702), STCSM (No. 22511106101, No. 22511105700, No. 21DZ1100100), 111 plan (No. BP0719010) and National Natural Science Foundation of China (No. 62306178). BH was supported by the NSFC Young Scientists Fund No. 62006202, NSFC General Program No. 62376235, and Guangdong Basic and Applied Basic Research Foundation No. 2022A1515011652.

References

- [1] Yuki M. Asano, Christian Rupprecht, and Andrea Vedaldi. Self-labelling via simultaneous clustering and representation learning. In *International Conference on Learning Representations (ICLR)*, 2020.
- [2] Mido Assran, Randall Balestriero, Quentin Duval, Florian Bordes, Ishan Misra, Piotr Bojanowski, Pascal Vincent, Michael Rabbat, and Nicolas Ballas. The hidden uniform cluster prior in self-supervised learning. In *The Eleventh International Conference on Learning Representations*, 2023.
- [3] Tanya Boone-Sifuentes, Asef Nazari, Imran Razzak, Mohamed Reda Bouadjenek, Antonio Robles-Kelly, Daniel Ierodiaconou, and Elizabeth S Oh. Marine-tree: A large-scale marine organisms dataset for hierarchical image classification. In *Proceedings of the 31st ACM International Conference on Information & Knowledge Management*, pages 3838–3842, 2022.
- [4] Sergiy V Borodachov, Douglas P Hardin, and Edward B Saff. *Discrete energy on rectifiable sets*. Springer, 2019.
- [5] Kaidi Cao, Colin Wei, Adrien Gaidon, Nikos Arechiga, and Tengyu Ma. Learning imbalanced datasets with label-distribution-aware margin loss. *Advances in Neural Information Processing Systems*, 32:1567–1578, 2019.
- [6] Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Matthijs Douze. Deep clustering for unsupervised learning of visual features. In *Proceedings of the European conference on computer vision (ECCV)*, pages 132–149, 2018.
- [7] Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. *Advances in Neural Information Processing Systems*, 33:9912–9924, 2020.
- [8] Mengxi Chen, Linyu Xing, Yu Wang, and Ya Zhang. Enhanced multimodal representation learning with cross-modal kd. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11766–11775, 2023.
- [9] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning*, pages 1597–1607. PMLR, 2020.
- [10] Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15750–15758, 2021.
- [11] Xinlei Chen*, Saining Xie*, and Kaiming He. An empirical study of training self-supervised vision transformers. *arXiv preprint arXiv:2104.02057*, 2021.
- [12] Henry Cohn and Abhinav Kumar. Universally optimal distribution of points on spheres. *Journal of the American Mathematical Society*, 20(1):99–148, 2007.
- [13] Jiequan Cui, Zhisheng Zhong, Shu Liu, Bei Yu, and Jiaya Jia. Parametric contrastive learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 715–724, 2021.
- [14] Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. *Advances in neural information processing systems*, 26, 2013.

- [15] Carl Doersch, Abhinav Gupta, and Alexei A Efron. Unsupervised visual representation learning by context prediction. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 1422–1430, 2015.
- [16] Ziqing Fan, Yanfeng Wang, Jiangchao Yao, Lingjuan Lyu, Ya Zhang, and Qi Tian. Fedskip: Combatting statistical heterogeneity with federated skip aggregation. In *2022 IEEE International Conference on Data Mining (ICDM)*, pages 131–140. IEEE, 2022.
- [17] Cong Fang, Hangfeng He, Qi Long, and Weijie J Su. Exploring deep neural networks via layer-peeled model: Minority collapse in imbalanced training. *Proceedings of the National Academy of Sciences*, 118(43):e2103091118, 2021.
- [18] Quentin Garrido, Yubei Chen, Adrien Bardes, Laurent Najman, and Yann LeCun. On the duality between contrastive and non-contrastive self-supervised learning. In *The Eleventh International Conference on Learning Representations*, 2023.
- [19] Florian Graf, Christoph Hofer, Marc Niethammer, and Roland Kwitt. Dissecting supervised contrastive learning. In *International Conference on Machine Learning*, pages 3821–3830. PMLR, 2021.
- [20] Jean-Bastien Grill, Florian Strub, Florent Alché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent—a new approach to self-supervised learning. *Advances in neural information processing systems*, 33:21271–21284, 2020.
- [21] DP Hardin and EB Saff. Minimal riesz energy point configurations for rectifiable d -dimensional manifolds. *Advances in Mathematics*, 193(1):174–204, 2005.
- [22] John A Hartigan and Manchek A Wong. Algorithm as 136: A k-means clustering algorithm. *Journal of the royal statistical society. series c (applied statistics)*, 28(1):100–108, 1979.
- [23] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.
- [24] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9729–9738, 2020.
- [25] Feng Hong, Jiangchao Yao, Zhihan Zhou, Ya Zhang, and Yanfeng Wang. Long-tailed partial label learning via dynamic rebalancing. In *The Eleventh International Conference on Learning Representations*, 2023.
- [26] Chaoqin Huang, Haoyan Guan, Aofan Jiang, Ya Zhang, Michael Spratling, and Yan-Feng Wang. Registration based few-shot anomaly detection. In *European Conference on Computer Vision*, pages 303–319. Springer, 2022.
- [27] Chaoqin Huang, Qinwei Xu, Yanfeng Wang, Yu Wang, and Ya Zhang. Self-supervised masking for unsupervised anomaly detection and localization. *IEEE Transactions on Multimedia*, 2022.
- [28] Ziyu Jiang, Tianlong Chen, Bobak J Mortazavi, and Zhangyang Wang. Self-damaging contrastive learning. In *International Conference on Machine Learning*, pages 4927–4939. PMLR, 2021.
- [29] Bingyi Kang, Saining Xie, Marcus Rohrbach, Zhicheng Yan, Albert Gordo, Jiashi Feng, and Yannis Kalantidis. Decoupling representation and classifier for long-tailed recognition. In *International Conference on Learning Representations*, 2019.
- [30] Bingyi Kang, Yu Li, Sa Xie, Zehuan Yuan, and Jiashi Feng. Exploring balanced feature spaces for representation learning. In *International Conference on Learning Representations*, 2020.
- [31] Tejaswi Kasarla, Gertjan Burghouts, Max van Spengler, Elise van der Pol, Rita Cucchiara, and Pascal Mettes. Maximum class separation as inductive bias in one matrix. In *Advances in Neural Information Processing Systems*, volume 35, pages 19553–19566, 2022.

- [32] Aditya Khosla, Nityananda Jayadevaprakash, Bangpeng Yao, and Fei-Fei Li. Novel dataset for fine-grained image categorization: Stanford dogs. In *Proc. CVPR Workshop on Fine-Grained Visual Categorization (FGVC)*, volume 2. Citeseer, 2011.
- [33] Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *Proceedings of the IEEE international conference on computer vision workshops*, pages 554–561, 2013.
- [34] A Krizhevsky. Learning multiple layers of features from tiny images. *Technical Report TR-2009, University of Toronto*, 2009.
- [35] Anna Kukleva, Moritz Böhle, Bernt Schiele, Hilde Kuehne, and Christian Rupprecht. Temperature schedules for self-supervised contrastive methods on long-tail data. In *The Eleventh International Conference on Learning Representations*, 2023.
- [36] Junnan Li, Pan Zhou, Caiming Xiong, and Steven Hoi. Prototypical contrastive learning of unsupervised representations. In *International Conference on Learning Representations*, 2021.
- [37] Tianhong Li, Peng Cao, Yuan Yuan, Lijie Fan, Yuzhe Yang, Rogerio S Feris, Piotr Indyk, and Dina Katabi. Targeted supervised contrastive learning for long-tailed recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6918–6928, 2022.
- [38] Jiye Liang, Liang Bai, Chuangyin Dang, and Fuyuan Cao. The k -means-type algorithms versus imbalanced data distributions. *IEEE Transactions on Fuzzy Systems*, 20(4):728–745, 2012.
- [39] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *Computer Vision—ECCV 2014: 13th European Conference, Zurich, Switzerland, September 6-12, 2014, Proceedings, Part V 13*, pages 740–755. Springer, 2014.
- [40] Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2980–2988, 2017.
- [41] Hong Liu, Jeff Z HaoChen, Adrien Gaidon, and Tengyu Ma. Self-supervised learning is more robust to dataset imbalance. In *International Conference on Learning Representations*, 2021.
- [42] Weiyang Liu, Yandong Wen, Zhiding Yu, Ming Li, Bhiksha Raj, and Le Song. Sphereface: Deep hypersphere embedding for face recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 212–220, 2017.
- [43] Weiyang Liu, Rongmei Lin, Zhen Liu, Lixin Liu, Zhiding Yu, Bo Dai, and Le Song. Learning towards minimum hyperspherical energy. *Advances in neural information processing systems*, 31, 2018.
- [44] Ziwei Liu, Zhongqi Miao, Xiaohang Zhan, Jiayun Wang, Boqing Gong, and Stella X Yu. Large-scale long-tailed recognition in an open world. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2537–2546, 2019.
- [45] Subhansu Maji, Esa Rahtu, Juho Kannala, Matthew Blaschko, and Andrea Vedaldi. Fine-grained visual classification of aircraft. *arXiv preprint arXiv:1306.5151*, 2013.
- [46] Aditya Krishna Menon, Sadeep Jayasumana, Ankit Singh Rawat, Himanshu Jain, Andreas Veit, and Sanjiv Kumar. Long-tail learning via logit adjustment. In *International Conference on Learning Representations*, 2021.
- [47] Dustin G Mixon, Hans Parshall, and Jianzong Pi. Neural collapse with unconstrained features. *Sampling Theory, Signal Processing, and Data Analysis*, 20(2):1–13, 2022.
- [48] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

- [49] Vardan Papyan, XY Han, and David L Donoho. Prevalence of neural collapse during the terminal phase of deep learning training. *Proceedings of the National Academy of Sciences*, 117(40):24652–24663, 2020.
- [50] William J Reed. The pareto, zipf and other power laws. *Economics letters*, 74(1):15–19, 2001.
- [51] Rasmus Rothe, Radu Timofte, and Luc Van Gool. Deep expectation of real and apparent age from a single image without facial landmarks. *International Journal of Computer Vision*, 126(2-4):144–157, 2018.
- [52] Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut. Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2556–2565, 2018.
- [53] Steve Smale. Mathematical problems for the next century. *The mathematical intelligencer*, 20(2):7–15, 1998.
- [54] Alexander Strehl and Joydeep Ghosh. Cluster ensembles—a knowledge reuse framework for combining multiple partitions. *Journal of machine learning research*, 3(Dec):583–617, 2002.
- [55] Jianhua Sun, Yuxuan Li, Hao-Shu Fang, and Cewu Lu. Three steps to multimodal trajectory prediction: Modality clustering, classification and synthesis. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 13250–13259, 2021.
- [56] Jianhua Sun, Yuxuan Li, Liang Chai, Hao-Shu Fang, Yong-Lu Li, and Cewu Lu. Human trajectory prediction with momentary observation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6467–6476, 2022.
- [57] Jianhua Sun, Yuxuan Li, Liang Chai, and Cewu Lu. Modality exploration, retrieval and adaptation for trajectory prediction. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2023.
- [58] Joseph John Thomson. Xxiv. on the structure of the atom: an investigation of the stability and periods of oscillation of a number of corpuscles arranged at equal intervals around the circumference of a circle; with application of the results to the theory of atomic structure. *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, 7(39): 237–265, 1904.
- [59] Yonglong Tian, Olivier J Henaff, and Aäron van den Oord. Divide and contrast: Self-supervised learning from uncurated data. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10063–10074, 2021.
- [60] Grant Van Horn, Steve Branson, Ryan Farrell, Scott Haber, Jessie Barry, Panos Ipeirotis, Pietro Perona, and Serge Belongie. Building a bird recognition app and large scale dataset with citizen scientists: The fine print in fine-grained dataset collection. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 595–604, 2015.
- [61] Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The caltech-ucsd birds-200-2011 dataset. 2011.
- [62] Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *International Conference on Machine Learning*, pages 9929–9939. PMLR, 2020.
- [63] Xiaolong Wang and Abhinav Gupta. Unsupervised learning of visual representations using videos. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2794–2802, 2015.
- [64] Yifei Wang, Qi Zhang, Yisen Wang, Jiansheng Yang, and Zhouchen Lin. Chaos is a ladder: A new theoretical understanding of contrastive learning via augmentation overlap. In *International Conference on Learning Representations*, 2021.

- [65] Chaoyi Wu, Feng Chang, Xiao Su, Zhihan Wu, Yanfeng Wang, Ling Zhu, and Ya Zhang. Integrating features from lymph node stations for metastatic lymph node detection. *Computerized Medical Imaging and Graphics*, 101:102108, 2022.
- [66] Chaoyi Wu, Xiaoman Zhang, Ya Zhang, Yanfeng Wang, and Weidi Xie. Towards generalist foundation model for radiology. *arXiv preprint arXiv:2308.02463*, 2023.
- [67] Yibo Yang, Liang Xie, Shixiang Chen, Xiangtai Li, Zhouchen Lin, and Dacheng Tao. Do we really need a learnable classifier at the end of deep neural network? *arXiv preprint arXiv:2203.09081*, 2022.
- [68] Yuzhe Yang and Zhi Xu. Rethinking the value of labels for improving class-imbalanced learning. *Advances in neural information processing systems*, 33:19290–19301, 2020.
- [69] Yuzhe Yang, Kaiwen Zha, Yingcong Chen, Hao Wang, and Dina Katabi. Delving into deep imbalanced regression. In *International Conference on Machine Learning*, pages 11842–11851. PMLR, 2021.
- [70] Jiangchao Yao, Bo Han, Zhihan Zhou, Ya Zhang, and Ivor W Tsang. Latent class-conditional noise model. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2023.
- [71] Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow twins: Self-supervised learning via redundancy reduction. In *International Conference on Machine Learning*, pages 12310–12320. PMLR, 2021.
- [72] Fei Zhang, Lei Feng, Bo Han, Tongliang Liu, Gang Niu, Tao Qin, and Masashi Sugiyama. Exploiting class activation value for partial-label learning. In *International Conference on Learning Representations*, 2021.
- [73] Fei Zhang, Chaochen Gu, Chenyue Zhang, and Yuchao Dai. Complementary patch for weakly supervised semantic segmentation. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 7242–7251, 2021.
- [74] Ruipeng Zhang, Ziqing Fan, Qinwei Xu, Jiangchao Yao, Ya Zhang, and Yanfeng Wang. Grace: A generalized and personalized federated learning method for medical imaging. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 14–24. Springer, 2023.
- [75] Yifan Zhang, Bingyi Kang, Bryan Hooi, Shuicheng Yan, and Jiashi Feng. Deep long-tailed learning: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2023.
- [76] Yuhang Zhou, Jiangchao Yao, Feng Hong, Ya Zhang, and Yanfeng Wang. Balanced destruction-reconstruction dynamics for memory-replay class incremental learning. *arXiv preprint arXiv:2308.01698*, 2023.
- [77] Zhihan Zhou, Jiangchao Yao, Yan-Feng Wang, Bo Han, and Ya Zhang. Contrastive learning with boosted memorization. In *International Conference on Machine Learning*, pages 27367–27377. PMLR, 2022.
- [78] Zhihui Zhu, Tianyu Ding, Jinxin Zhou, Xiao Li, Chong You, Jeremias Sulam, and Qing Qu. A geometric analysis of neural collapse with unconstrained features. *Advances in Neural Information Processing Systems*, 34:29820–29834, 2021.