29th International Conference on Optical Fiber Sensors

José Luís Santos Manuel Lopez-Amo Sainz Tong Sun Editors

25–30 May 2025 Porto, Portugal

Organized by INESC TEC – Institute for Systems and Computer Engineering, Technology and Science (Portugal)

Institutional Support

Visit Portugal • Visit Porto&North of Portugal • PRR - Plano de Recuperação e Resiliência • República Portuguesa • European Union: NextGenerationEU • European Photonics Industry Consortium (EPIC) 27th International Conference on Optical Fiber Sensors (OFS2022) • 28th International Conference on Optical Fiber Sensors (OFS28)

Sponsored by

HBK FiberSensing S.A. (Portugal) • Exail SAS (France) • Luna Innovations Inc. (United States) • Yangtze Optical Electronic Co., Ltd. (China) • Shandong Micro-Sensor Photonics, Ltd. (China) • Thorlabs, Inc. (United States) • NorthLab Photonics AB (Sweden) • B-SENS (France) • FEBUS Optics (France) FiberLogix International Ltd. (United Kingdom)

Published by SPIE

Volume 13639

Part One of Two Parts

Proceedings of SPIE 0277-786X, V. 13639

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

The papers in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. Additional papers and presentation recordings may be available online in the SPIE Digital Library at SPIEDigitalLibrary.org.

The papers reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from these proceedings: Author(s), "Title of Paper," in 29th International Conference on Optical Fiber Sensors, edited by José Luís Santos, Manuel Lopez-Amo Sainz, Tong Sun, Proc. of SPIE 13639, Seven-digit Article CID Number (DD/MM/YYYY); (DOI URL).

ISSN: 0277-786X ISSN: 1996-756X (electronic)

ISBN: 9781510691872 ISBN: 9781510691889 (electronic)

Published by **SPIE** P.O. Box 10, Bellingham, Washington 98227-0010 USA Telephone +1 360 676 3290 (Pacific Time) SPIE.org Copyright © 2025 Society of Photo-Optical Instrumentation Engineers (SPIE).

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of fees. To obtain permission to use and share articles in this volume, visit Copyright Clearance Center at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher.

Printed in the United States of America by Curran Associates, Inc., under license from SPIE.

Publication of record for individual papers is online in the SPIE Digital Library.



Paper Numbering: A unique citation identifier (CID) number is assigned to each article in the Proceedings of SPIE at the time of publication. Utilization of CIDs allows articles to be fully citable as soon as they are published online, and connects the same identifier to all online and print versions of the publication. SPIE uses a seven-digit CID article numbering system structured as follows:

• The first five digits correspond to the SPIE volume number.

• The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc. The CID Number appears on each page of the manuscript.

Contents

xxvii Conference Committee xxxi Welcome

Part One

PLENARY SESSIONS

13639 04 Distributed acoustic sensing (DAS) a real-world perspective, requirements, applications, and techniques (Plenary Paper) [13639-601]

WORKSHOP SESSIONS

13639 09 Innovative platforms for optical sensing: hollow-core and biodegradable optical fibers (Invited Paper) [13639-615]

DISTRIBUTED SENSING I

13639 OE Distributed acoustic sensing in submarine optical fibers (Invited Paper) [13639-609] 13639 OF Polarization pulling in Brillouin fiber sensing using orthogonal probes [13639-458] 13639 OG Microcomb-enhanced BOTDR [13639-459] 13639 OH High-spatial-resolution distributed Brillouin sensing in plastic optical fibers: detection of 5cm heated region [13639-398] Temperature sensing based on forward stimulated Brillouin scattering using high-order 13639 OI optical modes in few-mode fibers [13639-570] 13639 OJ DAS with 302km sensing range using remote amplification and engineered fiber [13639-412] Quasi-distributed acoustic sensing with DSB-OFDR for large measurement range and 13639 OK enhanced frequency response [13639-185] NEW ELEMENTS, EFFECTS, OR TECHNOLOGIES AND MATERIALS FOR PHOTONIC SENSING

13639 0M Plasmonic tilted fiber Bragg grating sensors: insights into their effective demodulation [13639-205]

13639 ON	Enhancing a	polarimetric fiber	sensor using	Fisher information	[13639-517]
----------	-------------	--------------------	--------------	---------------------------	------------	---

- 13639 00 Control of Bragg wavelength drift in high-temperature annealing cycles for RFBGs and fs-FBGs [13639-579]
- 13639 OP Natural scene images reconstruction based on multimode fiber [13639-167]

DISTRIBUTED SENSING II

- 13639 0Q Recent advances in time-expansion distributed sensing technology (Invited Paper) [13639-621]
- 13639 OR Ambient noise interferometry using chirped-pulse DAS data for subsurface exploration [13639-460]
- 13639 0S Absolute temperature sensing in the 67-350K range using Brillouin scattering in gases [13639-196]

INTEGRATED PHOTONICS, CAVITY OPTOMECHANICS, AND QUANTUM SENSING

- 13639 0U Silicon photonics MIOC with forward-biased phase modulators for closed-loop operation in an interferometric fiber optic gyroscope [13639-402]
- 13639 0V Ultra-sensitive monolithically integrated tri-axial fiber-optic accelerometer with a nano-g level noise floor [13639-54]
- 13639 0W PDMS-based flexible distributed tactile sensor in a multi-waveguide system fabricated by the Mosquito Method [13639-165]
- 13639 0X Role of thin film refractive index contrast in the design and performance of nano-photonic crystal D-shaped fiber devices for label-free biosensing [13639-82]

MICRO-NANO SENSORS

- 13639 0Z Effect of TiO₂ coating on neutron response of UV-written B-Ge co-doped optical fiber longperiod gratings [13639-477]
- 13639 10 Ultra-sensitive gas detection using noise-canceled graphene-microcavity-based fiber laser sensor [13639-52]
- 13639 11 Ultra-high resolution fiber laser strain sensor based on optical injection phase-lock loop [13639-166]
- 13639 12 A graphene micro-rod resonator gas sensor with switchable selectivity [13639-103]

SMART STRUCTURES

- 13639 14 High-precision colonoscope image guidance using OFDR shape sensing with right-angle core configuration in multicore fiber [13639-35]
- 13639 15 Simultaneous distributed acoustic and temperature sensing for robust leakage detection in gas pipelines [13639-480]
- 13639 16 Novel sensing network based on seamless integration of DAS and PON [13639-266]
- 13639 17 Beam shaping the evanescent field for distributed fluorescence-based optical fibre sensing [13639-178]

BIOCHEMICAL SENSING

- 13639 19 Multifunctional integrated fiber-optic probe for in vivo tumor identification, therapy, and efficacy assessment [13639-13]
- 13639 1A Pharmaceutical chemical sensing in hollow-core anti-resonant fiber with surfaces functionalized by semiconductor nanoparticles [13639-315]
- 13639 1B Fiber ultrasound transducer array for in vivo anatomic and functional photoacoustic imaging of mouse glioma [13639-260]
- 13639 1C Metasurface-based lab-on-fiber biosensor for label-free detection of vitamin D [13639-470]

ENVIRONMENT, SECURITY, DEFENCE, INDUSTRIAL APPLICATIONS, TECHNOLOGY COMMERCIALIZATION

- 13639 1E In situ ppb-level dissolved gas detection with micro-gas-cavity-based fiber photoacoustic spectrometer [13639-340]
- 13639 1F Palladium/hafnium-coated pi-FBGs: a path to wavelength-encoded, zero-pointreferenced, linearized, and temperature-decoupled hydrogen sensing [13639-359]
- 13639 1G Shock wave overpressure history mapping using high-resolution distributed acoustic sensing [13639-568]
- 13639 1H Humidity response analysis of optical fibers with hygroscopic coatings based on Lamé's equations [13639-109]

INTERFEROMETRIC/DISTRIBUTED SENSORS

13639 1J Ultra-miniature optical fiber accelerometer based on a 3D microprinted proof massintegrated Fabry-Pérot micro-interferometer [13639-289]

- 13639 1K Self-integrated auxiliary interferometer for nonlinearity compensation in optical frequency domain reflectometry [13639-210]
- 13639 1L Distributed electric field measurements along a hollow-core fiber by localizing a trapped charged particle with sub-mm spatial resolution using coherent optical frequency domain reflectometry [13639-253]
- 13639 1M Measuring tip deflection in multicore fiber optic probes based on fiber segment interferometry [13639-248]

PHYSICAL, MECHANICAL, AND ELECTROMAGNETIC SENSORS

- 13639 10 Resolving twist-induced errors in fiber optic shape sensing via polarization-sensitive reflectometry [13639-195]
- 13639 1P Femtosecond-laser-inscribed large-scale fiber Bragg grating arrays for distributed sensing in harsh environments [13639-434]
- 13639 1Q Application of PM-EDF ring laser with cascaded-chirped LPG to intensity-modulation-based acoustic sensing [13639-523]
- 13639 1R Transient fiber optical current sensing during high-voltage short-circuit events [13639-548]

POSTER SESSION I

- 13639 1S σ-BOTDA: exploiting frequency symmetry in Brillouin sensors [13639-6]
- 13639 1T An investigation of Rayleigh backscattering: utilizing coherent laser sources for enhanced IFOG performance [13639-15]
- 13639 1U Semi-distributed optical fiber bending extensometer system for precision landslide monitoring based on OTDR [13639-23]
- 13639 1V Broad-bandwidth distributed acoustic sensor with phase offset and phase sensitivity fading compensation [13639-30]
- 13639 1W High thermal-stability Fabry-Perot acoustic sensor with graphene diaphragm [13639-32]
- 13639 1X Fiber Fabry-Perot interferometer sensor for dynamic magnetic field detection based on microwave photonic filter [13639-33]
- 13639 1Y Parallel data transmission using modulated vibration and Mach–Zehnder interferometer [13639-36]
- 13639 1Z Chitosan-ion-imprinted polymer-based Mach-Zehnder interferometer sensors for Cd²⁺ detection using cross-linking polymerization [13639-41]

- 13639 20 Enhanced multi-branch sensing by leveraging the Fresnel reflection points in phasesensitive OTDR-based PON monitoring [13639-42]
- 13639 21 High-fidelity vehicle sensing with swiftly deployed DAS system [13639-44]
- 13639 22 Forward Brillouin scattering in few-mode fiber towards sensing [13639-50]
- 13639 23 The impact of chromatic dispersion on frequency scanning COTDR and its compensation [13639-61]
- 13639 24Extension of the measurable strain range in OFDR using overlapping and averaging method[13639-72]
- 13639 25 Lightweight distributed vibration sensing algorithm boosted with cross-domain distillation [13639-77]
- 13639 26 Novel OFDR enhanced by dual microcombs [13639-80]
- 13639 27 BOTDR based on a self-sweeping fiber laser [13639-124]
- 13639 28 Distributed Brillouin measurement in graded index multimode optical fiber [13639-131]
- 13639 29 Separation of temperature and strain measurement in photon-counting BOTDR [13639-136]
- 13639 2A Characterization of heterogeneously integrated periodically polled lithium niobate using optical frequency domain reflectometry [13639-137]
- 13639 2B A modal-interferometer-based wearable system for health monitoring [13639-147]
- 13639 2C Mitigation of nonlocal polarization effect in Φ -OTDR using MIMO technique [13639-150]
- 13639 2D Optical flow processing for chirped-pulse coherent OTDR [13639-159]
- 13639 2E Compact highly-sensitive device based on interference-whispering gallery mode composite structure [13639-168]
- 13639 2F High-precision fabrication method for Fabry-Perot cavities using white light interferometry [13639-177]
- 13639 2G Analysis and compensation for the impact of modulation signal reset errors on scale factor of interferometric fiber optic gyroscopes [13639-192]
- 13639 2H Extending the measurement range of Brillouin optical correlation domain analysis through asymmetric adjustment of Stokes and anti-Stokes intensities [13639-203]
- 13639 21 Dual closed-loop detection scheme for differential FOG driven by dual sources [13639-207]

- 13639 2J Short-time Fourier neural operator for self-extraction of data feature in distributed acoustic sensing [13639-209]
- 13639 2K A vibration sensor with four channels utilizing an in-line Sagnac interference structure [13639-223]
- 13639 2L Dual-stage modulation correlation OTDR for high-resolution monitoring in passive optical networks [13639-226]
- 13639 2M Distributed humidity measurements using fibre-segment interferometry [13639-229]
- 13639 2N Detection of waves and sea-surface vessels via time-domain-only analysis of underwater DAS data [13639-242]
- 13639 20 Hollow-core fiber Fabry-Pérot photothermal gas sensing characteristics over the temperature range of 256–354K [13639-243]
- 13639 2P Deployment of fibre segment interferometry in a high-temperature superconducting magnet [13639-263]
- 13639 2Q Raman-assisted large chirped-pulse phi-OTDR for long range millikelvin distributed fibre thermometry [13639-269]
- 13639 2R Large chirped-pulse phi-OTDR for single-shot to day-long nano-strain measurements with high dynamic range [13639-270]
- 13639 28 Reference matrix self-correction for perturbation compensation in MFDD-DAS [13639-271]
- 13639 2T A closed loop fiber-optic gyroscope based on phase-locked loop [13639-274]
- 13639 2U Bending-loss-compensated backscattering-enhanced fiber for distributed acoustic sensing [13639-278]
- 13639 2V High-accuracy OFDR-type dynamic distributed strain measurement using phase integration coherence compensation method and interferometer base point shift [13639-280]
- 13639 2W **497-km distributed acoustic sensing with 20-m spatial resolution 45-pε**/√Hz strain resolution and broad-bandwidth [13639-281]
- 13639 2X Field trial of DAS data analysis methods for detecting excavation encroachment [13639-286]
- 13639 2Y Self-supervised pre-training for distributed acoustic sensing data feature learning with transformers [13639-300]
- 13639 2Z Exploring the use of a virtual reference spectrum in the Vernier effect [13639-306]
- 13639 30 A new perspective on the optical Vernier effect and its apparent sensitivity enhancement [13639-309]

- 13639 31 Quasi-distributed ultrasonic sensing scheme based on crosstalk suppressed optical coherence domain reflectometry [13639-312]
- 13639 32Frequency- and time-multiplexed high-precision BOTDR using a frequency-shifting loop[13639-313]
- 13639 33 An 80km open path Brillouin optical time domain analysis with far-end probe light [13639-316]
- 13639 34 Ultra-high-resolution compact spectropolarimeter based on leaky-mode speckle from random interference and scattering [13639-317]
- 13639 35 Fiber-optic DAS for efficient wellbore data transmission [13639-328]
- 13639 36 Fiber-artefact methodology for distributed Brillouin sensing [13639-331]
- 13639 37 High-performance Φ-OTDR with the temporally sequenced multi-frequency multiwavelength chirped source [13639-336]
- 13639 38 High-speed strain measurement in dual-laser Brillouin optical correlation-domain reflectometry [13639-341]
- 13639 39 Fiber optic Fabry-Pérot sensor multiplexing technology based on self-calibration wavelength modulation [13639-342]
- 13639 3A Monitoring of FTTH-PON using direct-detection FBG-assisted φ-OTDR [13639-357]
- 13639 3B Extending the range of measurement and the sensitivity response of Fabry-Perot interferometric sensors [13639-369]
- 13639 3C Soft force sensor based on silicone rubber embedding single mode fiber using Brillouin optical correlation-domain reflectometry [13639-370]
- 13639 3D Distributed fibre-optic acoustic sensing: a tool to assess rock properties during active and passive seismic surveys [13639-375]
- 13639 3E Self-referenced carrier frequency offset interferogram correction for dual-comb systems [13639-377]
- 13639 3F Potential of electrical-domain interference driven by modal distribution in optical fibers for strain and displacement sensing [13639-386]
- 13639 3G Distributed temperature measurement with Brillouin optical correlation-domain reflectometry at 8.5mm spatial resolution [13639-387]
- 13639 3H Proposal of OCDR based on periodic pseudo-random modulation [13639-388]
- 13639 3 Proposal of correlation-dip-based optical correlation-domain reflectometry [13639-391]

- 13639 3J Interferometric optical fiber sensor with a polyoxometalate-doped xerogel for the selective detection of ammonia [13639-392]
- 13639 3K Time-transformed spectral analysis for multiparametric sensing using a single antiresonant interferometer [13639-393]
- 13639 3L Long range Brillouin optical time-domain analysis using cyclic m-sequence [13639-394]
- 13639 3M Frequency-division-multiplexed optical correlation-domain reflectometry for overcoming sampling rate constraint [13639-395]
- 13639 3N Beat spectrum in dual-laser optical correlation-domain reflectometry [13639-397]
- 13639 30 Dual sideband probe Pound-Drever-Hall Brillouin optical time domain analysis [13639-405]
- 13639 3P Experimental investigation of relationship between modulation frequency and spatial resolution in OCDR with frequency shifter [13639-408]
- 13639 3Q Vernier-effect-based C-shaped fiber sensor for temperature measurement [13639-409]
- 13639 3R Strain and temperature simultaneous measurement in kilometer-scale fiber-optic gyroscopic coils using OFDR [13639-415]
- 13639 3S Fiber-optic micro-displacement sensor probe based on Vernier effect [13639-422]
- 13639 3T An optimized method to suppress the spontaneous MI-induced phase noise in the interferometric fiber sensing system [13639-423]
- 13639 3U Implementation of externally modulated Brillouin optical correlation-domain reflectometry using single-sideband modulator [13639-425]
- 13639 3V Analysis on the strain and temperature dependence of stimulated Brillouin scattering in a PANDA-type few-mode fiber [13639-426]
- 13639 3W Water absorption effects on distributed temperature sensing using polyimide-coated optical fiber [13639-427]
- 13639 3X A stimulated Brillouin scattering suppression method in the remote interferometric fiber sensing system based on electro-optic phase modulator and modified phase-generated carrier [13639-429]
- 13639 3Y Improving the strain measurement accuracy in OFDR by suppressing residual phase noise [13639-435]
- 13639 32 Positive and negative slope-assisted BOTDA based on five-frequency light to compensate for the effect of loss and reflection [13639-436]

- 13639 40 Slope-assisted BOTDA using Brillouin gain and loss spectra with phase-shift pulse pump for improved spatial resolution and reduced measurement time [13639-438]
- 13639 41 Temporal data densification in fiber optic interferometer with triangular-wave phase modulation for dynamic displacement measurement [13639-439]
- 13639 42 **Proposal of phase measurement method from FFT on broadband-probe-based BOTDA** [13639-444]
- 13639 43 Efficient inhibition of Rayleigh scattering in interferometric sensor through random phase noise [13639-446]
- 13639 44 Fast and robust post-processing algorithm for STFT-BOTDR [13639-451]
- 13639 45 High-frequency response TGD-OFDR-based distributed acoustic sensor utilizing frequencyshifting loop [13639-453]
- 13639 46 Quasi-static pressure sensitivity of single-mode optical fibers [13639-455]
- 13639 47 High-sensitivity distributed random lasing sensor [13639-474]
- 13639 48 A novel distributed interferometer for security monitoring of ultra-long-distance submarine optical cables [13639-475]
- 13639 49 Suppression of Doppler-shift-induced crosstalk in linear-frequency-swept φ-OTDR by using scattering-enhanced fiber [13639-476]
- 13639 4A Frequency-distortion-suppressed phase-sensitive OFDR by using dual-wavelength digitally enhanced interferometry [13639-491]
- 13639 4B Realization of a collinear pump-probe beam configuration for a fiber-optic photothermal trace gas sensing system [13639-493]
- 13639 4C Impact of the laser spectral purity on high-resolution distributed acoustic sensing based on optical frequency domain reflectometry [13639-494]
- 13639 4D Microwave frequency OTDR for high strain-rate sensing [13639-499]
- 13639 4E Signal fading analysis for φ-OTDR applied in vehicle detection [13639-506]
- 13639 4F Acoustic resonance sensing of hydrogen diffusion in standard single-mode optical fibers [13639-510]
- 13639 4G Acoustic sensing over 100km using coherent-correlation OTDR and Manchester coding [13639-511]
- 13639 4H Influence of Doppler frequency shift induced by environmental perturbations on sensing performance of OFDR [13639-520]

13639 41	Comparison investigation of DAS measurements between fibers in/on the cable for the smartification of optical fiber cables [13639-525]
13639 4J	Investigation of metal-coated optical fiber in temperature response using TD-BOCDA [13639-528]
13639 4K	High-speed BOCDA system with dual sidebands for analyzing two-dimensional deformation induced by mechanical shock [13639-529]
13639 4L	Quasi-distributed FBG-based temperature measurement of rotating components of electrical motor through fiber optical rotary joint [13639-531]
13639 4M	Rayleigh signature interrogation in time-domain DAS sensors using the short-frequency Fourier transform [13639-533]
13639 4N	Fiber-optic torsion sensing using fiber segment interferometry [13639-536]
13639 40	Current sensing in phase-OTDR systems using deep learning [13639-541]
13639 4P	Phase-bias-enhanced Sagnac interferometer for airborne audible sound detection based on 3×3 fiber coupler [13639-550]
13639 4Q	Separation of Lamb waves modes using remotely bonded seven-core fiber Bragg grating Fabry-Pérot interferometer [13639-551]
13639 4R	Ultra-low-ZCPs long-distance OFDR based on compressive sensing technology [13639-555]
13639 4S	Harnessing speckle optical fiber sensors through high-frequency interrogation with an event-based camera. [13639-564]
13639 4T	Enhancement of DAS sensitivity with acoustic metasurface [13639-590]

POSTER SESSION II

13639 4U	Optical fiber macrobend sensor assisted by artificial intelligence for monitoring a flexible structure [13639-16]
13639 4V	Homogenizing fibre optic for plasma emission in multichannel LIBS spectrometry [13639-17]
13639 4W	Analysis of the effects of temperature, strain, and refractive index in long-period fiber grating used for epoxy resin cure monitoring [13639-37]
13639 4X	A low-noise Brillouin/erbium fiber laser module for optical sensing [13639-45]
13639 4Y	Hyperbolic-metamaterial-enhancement-based high-sensitivity side-polished fiber SPR sensors [13639-47]

13639 4Z	Exchangeable scanning probe microscopy optical fiber tips [13639-56]
13639 50	BNNT coating of FBGs written in tapered optical fiber for hydrophilic gas sensing [13639-57]
13639 51	Two-dimensional force-sensing whisker based on a WGM microbubble resonator [13639-58]
13639 52	Fiber optical sensor for structural strain and displacement monitoring of large power generation facilities [13639-67]
13639 53	Expressway embankment health monitoring by DAS measurement [13639-71]
13639 54	Unraveling the generation dynamics of Brillouin-Kerr microcomb using a harmonically synchronized time magnifier [13639-84]
13639 55	Fiber-enhanced Fourier-transform photothermal spectroscopy for multi-component gas sensing [13639-86]
13639 56	Sound detection and recognition based on biomimetic fiber-microcavity acoustic sensors [13639-88]
13639 57	NN-recognition algorithm with Gaussian activation function adjusted to probability range for fiber vibration multi-classification [13639-93]
13639 58	Linearizing the mode transition in LPFG sensors with metal and dielectric thin films [13639-100]
13639 59	Force feedback using fiber Bragg gratings embedded in a suction cup [13639-104]
13639 5A	Pipeline intrusion events recognition method based on AWTFE image enhancement for DAS [13639-113]
13639 5B	Full spectral interrogation of π -phase-shifted TFBG-based refractive index sensor using convolutional neural network [13639-120]
13639 5C	Hollow-core-fiber-cavity-enhanced stimulated Raman gain spectroscopy for trace hydrogen detection [13639-125]
13639 5D	Mechanical measurements in filament-wound composite cylinders by optical fiber specklegram sensor [13639-127]
13639 5E	Optical fiber-based sensing platform with integrated biodegradable agar-structured transducer [13639-128]
13639 5F	High-resolution interrogation of FBG-based inclination sensor with microwave photonic filtering technique [13639-129]
13639 5G	All-optical direct strain sensor based on multimode fiber and optical computing [13639-148]

13639 5H	Silicon photonic interrogator for Brillouin optical time-domain analysis [13639-151]
13639 51	High-SNR integrated Φ-OTDR based on injection locking laser and frequency diversity [13639-154]
13639 5J	Research on temperature characteristics of open cavity fiber optic sensing structure [13639-158]
13639 5K	Nano-g resolution optical fiber MEMS accelerometer with symmetric push-pull spring structure [13639-161]
13639 5L	Detecting single ultra-fine particles with fiber tip sensors [13639-173]
13639 5M	Chirped-pulse DAS as a seismic surface wave monitoring tool along trackside dark fibers: application in the analysis of superstructure features [13639-174]
13639 5N	ZnO-nanoparticles-doped optical fibers for radioluminescence sensors [13639-176]
13639 50	Field trial of railway track defect detection with DAS [13639-184]
13639 5P	A hybrid demodulation algorithm for high-sensitivity and wide-range quasi-distributed fiber optic sensing [13639-187]
13639 5Q	Applying draw tower FBGs to characterize fiber drawing processes [13639-188]

Part Two

13639 5R	Large-area hole-sphere nanogap platform for high-sensitivity, low-deviation SERS analysis and its applications [13639-190]
13639 55	Ultra-wideband wavelength-swept laser with a 440nm scanning range using four SOAs [13639-191]
13639 5T	Two-dimensional acoustic source localization algorithm based on physics-informed neural network in distributed acoustic sensing [13639-193]
13639 5U	Embedding fiber-optic sensors in DED-LB processes for structural monitoring [13639-201]
13639 5V	Astigmatism-controlled beam shaping for high-quality fibre Bragg grating inscription using femtosecond laser [13639-214]
13639 5W	Wide-spectrum erbium-doped fiber ring laser induced by deexcitation at high pump power [13639-215]
13639 5X	Smart tape for monitoring the automated tape layering process using all-grating fiber sensors [13639-216]
13639 5Y	Monitoring the effects of planar constraint on strain accumulation during epoxy resin curing process using fibre Bragg gratings [13639-217]

- 13639 5Z Remote structural health monitoring employing OFDR via optical fiber communication networks [13639-219]
- 13639 60 Photo-bleaching effect of a 980nm light source on radiation-induced attenuation in pure silica core fibers [13639-224]
- 13639 61 Multi-gas analysis using dual-comb-driven nanomaterial-functionalized micro-fiber Bragg grating array [13639-228]
- 13639 62 A machine learning approach for designing surface plasmon resonance PCF-based sensors [13639-231]
- 13639 63 Hydrogen sensor based on hollow-core fiber photothermal spectroscopy [13639-239]
- 13639 64 All-fiber content-addressable memory (CAM) for in-sensor computing [13639-245]
- 13639 65 LSPR-based fibre optic sensor fabricated by laser annealing of thin gold films [13639-246]
- 13639 66 Microdisplacement sensor based on a processed optical fiber by an ultrafast laser-assisted etching method [13639-247]
- 13639 67 Laser-activated optofluidic microrod hydrogen sensor with single ppm sensitivity and 5 orders of magnitude detection range [13639-249]
- 13639 68 FEM simulation for the design of a smart washer-type sensor with FBG for use in metrorailway platform door security systems [13639-254]
- 13639 69 Monitoring and early-warning technique for expressway substructure defect detection based on ultra-weak FBG array sensors [13639-257]
- 13639 6A End-to-end deep learning framework for coarsely sampled TFBG-SPR spectrum demodulation [13639-284]
- 13639 6B Sparking fiber random laser for wavelength scanning [13639-288]
- 13639 6C Phase-sensitive common-path dual frequency comb spectroscopy [13639-294]
- 13639 6D Self-assembled hierarchical nanostructures: towards advanced SERS optrodes [13639-296]
- 13639 6E Polarization-mode-phase-difference photothermal gas sensing with an optical microfiber coupler [13639-301]
- 13639 6F Data processing optimization for TFBG spectral discretization and sensor coding [13639-311]
- 13639 6G Plastic optical fiber alkane gas sensor with polyisoprene cladding and carbon blackdoped polyisoprene layers [13639-318]

- 13639 6H All-fiber counter-propagating all-normal-dispersion (CANDi) laser for coherently averaged dual-comb spectroscopy [13639-320]
- 13639 61 A hybrid structural health monitoring system based on Lamb waves and distributed optical fiber sensors [13639-324]
- 13639 6J Ultra-high stability chip-scale optical gyroscope [13639-326]
- 13639 6K High-resolution mid-infrared dual electro-optic comb spectroscopy based on spectral interleaving [13639-338]
- 13639 6L New sensing solutions based on fibre Bragg gratings for engineering applications [13639-344]
- 13639 6M Avalanche-photodiode-integrated silicon photonics MIOC for interferometric fiber optic gyroscope [13639-346]
- 13639 6N Monitoring heat losses in a heating pipeline model using distributed temperature sensing [13639-347]
- 13639 60 Railway track monitoring using distributed acoustic sensing (DAS) with standard telecom cable [13639-348]
- 13639 6P Optical fiber gas sensors based on the interaction of evanescence waves with active layers detecting pure gases and liquid vapours [13639-349]
- 13639 6Q Low-noise refractive index sensing with short-length long-period gratings written with femtosecond laser [13639-350]
- 13639 6R Feature extraction of disturbance signal based on Hilbert-Huang transform for event recognition of Φ-OTDR [13639-351]
- 13639 6S Silica microlenses for extrinsic optical fibre sensors [13639-354]
- 13639 6T A reflection scheme for optical-chemical sensors via light-diffusing fibers and molecularly imprinted polymers [13639-358]
- 13639 6U Limitations of OFDR measurements in civil structural health monitoring [13639-360]
- 13639 6V Femtosecond-laser-written microstructured dual hole flat fibre pressure sensor [13639-361]
- 13639 6W Microfluidic flowmeter using a PDMS-coated capillary [13639-364]
- 13639 6X Organic solvents in-diffusion probe based on Bragg reflectors inscribed in polypropylene no-core optical fibers [13639-366]
- 13639 6Y Hybrid fibre-optic assemblies: a miniature, multi-functional cable for quasi- and fullydistributed measurements [13639-389]

- 13639 6Z **Two-photon 3D printed Fabry-Perot cavity combined with a femtosecond fiber Bragg** grating on a single fiber for simultaneous sensing of pressure and temperature at high temperatures [13639-396]
- 13639 70 Underground pipeline imaging using broadband fiber optic seismometer array [13639-399]
- 13639 71 Assessing electron radiation impact on long period gratings: radiation saturation and recovery insights [13639-400]
- 13639 72 Investigation of internal fine structure testing and defect analysis methods for fiber optic couplers [13639-414]
- 13639 73 **Pressure and temperature sensing with 3D nanoprinted structure integrated on optical fiber** [13639-416]
- 13639 74 Temperature and relative humidity fiber optic sensing system for concrete monitoring [13639-417]
- 13639 75 Magnetic field measurement using Fabry-Perot fiber-optic sensor with 3D microstructures [13639-421]
- 13639 76 Opto-mechanical analysis of thermal stability of fiber coatings [13639-428]
- 13639 77 Development of a low-cost Raman spectroscopy platform for high-throughput analysis [13639-431]
- 13639 78 Multidimensional monitoring of gas pipeline leakage: an application of distributed multiparameter sensing based on hybrid UWFBG array [13639-437]
- 13639 79 Stimulated Raman photothermal spectroscopy on an optical nanofiber for hydrogen detection [13639-441]
- 13639 7A Pipeline leaks acoustic detection using mechanically amplified fiber Bragg grating sensors and artificial intelligence [13639-447]
- 13639 7B Topological sensing with plasmons [13639-456]
- 13639 7C Polarization sensing for optical network security: a comparative study of 1G and 200G systems [13639-461]
- 13639 7D NV centres in diamond for magnetic field quantum sensing [13639-463]
- 13639 7E Low-cost versatile optical fiber sensor for structural health monitoring of reinforced concrete structures [13639-466]
- 13639 7F Measuring the Monument: fibre optic sensor systems show why Hooke's and Wren's plans for a giant telescope within the Monument in London failed [13639-481]
- 13639 7G Generation of lossy mode resonances in a printed optical waveguide [13639-482]

- 13639 7H Anisotropic plasmonic nano-emitters to excite surface plasmon polaritons on thin-filmcoated tapered optical fibers [13639-484]
- 13639 71 Repeatability of vibration-based damage detection on rolling element bearings with FBG sensors [13639-486]
- 13639 7J Molecularly imprinted optical fibre sensor for detection of nitroglycerin [13639-497]
- 13639 7K Early leak detection in wastewater pipelines using fibre Bragg grating sensors [13639-498]
- 13639 7L Hybrid sensor based on a single segment of hollow-core microstructured optical fiber for simultaneous measurement of pressure and temperature [13639-509]
- 13639 7M Mind the splice: ultra-high-sensitivity refractometer based on thin-wall silica capillary tube [13639-514]
- 13639 7N Hydrophobicity level detection of superhydrophobic glass-composite coatings based on a fibre-hole-fibre structure [13639-526]
- 13639 70 Reversible pH sensing utilizing U-bent optical fibers coated with a layer-by-layer application of polymer multilayers [13639-537]
- 13639 7P Fiber-optic EFPI acoustic emission sensor with bulk silicon micromachined membrane [13639-538]
- 13639 7Q Optical fibers used as structural sensing elements in a tensegrity structure for force measurement and localization [13639-539]
- 13639 7R An improved deconvolution beamforming algorithm based on fiber optic microphone array for acoustic imaging [13639-540]
- 13639 78 Analyzing the laser-driven dynamics of SU-8 microcantilevers with optical fiber Fabry-Perot cavity [13639-546]
- 13639 7T **2.7µm surface plasmon resonance fiber optic sensors** [13639-549]
- 13639 70 Ultra-high-SMSR femtosecond apodized FBG based on variable pulse number inscription technology [13639-553]
- 13639 7V Polarization-switched fiber optic ring laser for L-band multiwavelength remote sensing applications [13639-554]
- 13639 7W Functional near-infrared spectroscopy sensor using a combined short-channel regression and frequency-division multiplexing [13639-560]
- 13639 7X Displacement sensor based on an external cavity fiber laser for non-contact photoacoustic sensing [13639-563]

- 13639 7Y Enhancement of fiber-optic sensor performance through hyperbolic dispersion engineering [13639-571]
- 13639 7Z Multi-fiber-optic sensing system for eco-friendly gas-insulated switchgear condition monitoring [13639-577]

POSTER SESSION III

13639 80	Capillary-based optical fiber sensor for turbidity measurement [13639-7]
13639 81	Advanced optical fiber sensors for measuring seawater salinity and pressure [13639-21]
13639 82	Evaluation of overhead cable sag using distributed acoustic sensing [13639-26]
13639 83	Remote power over fiber electro-mechanical modulation for enabling hybrid sensor networks [13639-28]
13639 84	Indoor comfort monitoring in buildings using fiber optic sensors [13639-31]
13639 85	Fiber-optic flammable vapor sensor based on a porous cholesteric liquid crystal film [13639-34]
13639 86	Spectral analysis of type III femtosecond fiber Bragg gratings at high temperatures [13639-38]
13639 87	Optical fiber sensor based on lossy mode resonance for high-sensitive temperature detection [13639-46]
13639 88	A polarization switching and Faraday rotator mirror hybrid method for ultra-low polarization fading noise in optical fiber hydrophone [13639-49]
13639 89	Intensity-based refractive index sensor using sliced fiber Bragg grating [13639-55]
13639 8A	Dynamic strain measurement at high frequencies by using portable fiber Bragg grating (FBG) interrogator [13639-59]
13639 8B	Resilient DFOS placement strategy for power grid monitoring: integrating fiber and power network dependencies [13639-70]
13639 8C	Intermittent still image monitoring system operated by weak power-over-fiber from an unused port of a PON splitter [13639-73]
13639 8D	DFBG-based shape sensor for large-curvature reconstruction [13639-74]
13639 8E	Optical fiber laser sensor for torsion measurement using a three-core fiber and a nanocrystals-based reflector [13639-83]

13639 8F	Determining insertion depth of silica optical fiber-integrated cochlear implant electrode array using optical frequency domain reflectometry [13639-89]
13639 8G	Measurement of curvilinearly varying strain using a Brillouin-gain-spectrum-based method with a multiline strain model [13639-91]
13639 8H	Integrated fiber-optic drug delivery system for effective anti-tumor synergistic therapy [13639-95]
13639 81	Hetero-core optical-fiber-based force myography sensor [13639-101]
13639 8J	Polarization-diversity-detection-based wavelength-scanning coherent-optical-time- domain reflectometer and its application for bus monitoring [13639-107]
13639 8K	Fault classification in electric motors using feature selection on vibration data from fiber Bragg grating accelerometers: a comparison of MLP and KAN networks [13639-108]
13639 8L	Direct electronical readout of surface plasmon resonance biosensor enabled by on-fiber graphene/PMMA photodetector [13639-116]
13639 8M	Leak detection in insulated pipe for nuclear pressure boundary monitoring using optical fiber distributed temperature sensor [13639-117]
13639 8N	Hydrogen sensing performance of partially Pd10:Ni10-coated pi-FBGs in nitrogen and air backgrounds [13639-121]
13639 80	Hyperbolic-metamaterial-based optical fiber SPR sensor enhanced by a smart hydrogel for perspiration pH measurements [13639-123]
13639 8P	Wind-resistant fault location method for aerial cables using speaker-assisted distributed vibration sensing [13639-126]
13639 8Q	FBG touch sensors in a social robot: toward natural behaviors controlled by physical human-robot interactions [13639-133]
13639 8R	Unveiling simultaneous detection and identification of different forms of amyloid-ß peptides in Alzheimer's disease via multi-channel TFBG-SPR biosensor [13639-134]
13639 85	Pre-eclampsia diagnosis on clinical samples using microfiber-Bragg-grating-assisted point- of-care biosensor [13639-135]
13639 8T	WSe ₂ -PDA-enhanced fiber optic surface plasmon resonance bioprobe for the detection of prostate-specific antigen [13639-160]
13639 8U	Vibration identification of fiber optic current sensors based on dual closed-loop feedback and VMD [13639-162]
13639 8V	Non-contact sleep atrial fibrillation monitoring using fiber optic sensors [13639-163]
13639 8W	Abandoned objects detection on the highway based on distributed features of UWFBG array sensors [13639-171]

13639 8X	High-resolution optical fiber ring magnetic field sensor [13639-180]
13639 8Y	A magneto-optical fibre rotary sensor for robotics [13639-181]
13639 8Z	Localized-surface-plasmon-resonance-based optical fiber mercury ion sensor employing CNT/PVA nanocomposite [13639-183]
13639 90	GST-enhanced fiber SPR curvature sensor [13639-189]
13639 91	Fiber Bragg grating monitoring during 3D wire arc additive manufacturing process [13639-212]
13639 92	Comparative analysis of distributed acoustic sensing and geophones for multichannel surface wave applications [13639-227]
13639 93	Double-helix-shaped optical fibers as a route for high-torsion sensing [13639-230]
13639 94	A new embeddable FBG sensor system to measure and decouple moisture swelling, thermal expansion, and mechanical strain [13639-232]
13639 95	Bacterial biofilm detection using a fiber optic Mach-Zehnder interferometer [13639-233]
13639 96	Outstanding sensitivity to ionizing radiation of custom optical fibers evaluated in real time by long period gratings [13639-235]
13639 97	Comparative evaluation of Thiram detection by LSPR-based fiber optic probes with different nanostructures [13639-236]
13639 98	Seismic activity monitoring in Iceland with fiber Bragg grating accelerometers [13639-238]
13639 99	Ship hydrodynamic pressure field detection using distributed acoustic sensing and a submarine photoelectric composite cable [13639-241]
13639 9A	A step towards multipoint hydrogen sensing: development of metal hydride-coated FBG hydrogen sensors [13639-250]
13639 9B	Coating of microfibrillated cellulose on plastic optical fiber [13639-252]
13639 9C	Ballistocardiography sensor based on polymeric optical fiber: a frequencies validation study [13639-255]
13639 9D	Evaluating the performance of CT method in distributed Brillouin fiber sensing [13639-256]
13639 9E	A magneto-optical fibre transducer [13639-258]
13639 9F	Fiber-Bragg-grating-based sensing for dynamic strain and speech recognition [13639-261]

- 13639 9G Normalized temperature sensitivity of fiber Bragg gratings inscribed under different conditions [13639-265]
- 13639 9H Fiber Bragg grating seven-core hydrophone as an acoustic waves direction sensor [13639-267]
- 13639 91 **FBG-based force-sensing gripper in minimally invasive robot-assisted laparoscopic surgery** [13639-268]
- 13639 9J Logic-gated biolaser for digital biochemical sensing [13639-275]
- 13639 9K Temperature characterization of nanoparticles-doped fiber in the context of transmissionreflection analysis [13639-277]
- 13639 9L Multipoint measurement of strain using FSBS-induced acoustic mode resonances [13639-279]
- 13639 9M Real-time high-precision traffic flow monitoring with DAS [13639-282]
- 13639 9N Fiber-Bragg-grating-based optical fiber sensing system integrated with ensemble deep learning for enhanced liquid level sensing [13639-285]
- 13639 90 Humidity sensor based on MMF-CLF-MMF structure with GO-enhanced SPR effect [13639-290]
- 13639 9P A novel plate-type fiber optic sensor for enhanced underwater detection [13639-302]
- 13639 9Q Reliable, doped hybrid xerogel-based optical fibre sensor for pH monitoring for industry [13639-307]
- 13639 9R Optical fiber fluorescence sensor integrated into a photobioreactor [13639-310]
- 13639 98 Low-cost implementation of polarization-stable Sagnac intrusion detection system using standard networking hardware [13639-323]
- 13639 9T Bio-amplified fiber microlaser for ultrasensitive and disposable immunosensing [13639-329]
- 13639 9U Distributed magnetic sensing with high precision and long distance using polarizationsensitive optical frequency domain reflectometry [13639-330]
- 13639 9V Portable SPR-based optical fibre sensing platform for detection of cortisol and Escherichia coli [13639-337]
- 13639 9W Flexible wearable optical sensor based on a balloon-like interferometer to breathing monitoring [13639-339]
- 13639 9X Electromagnetic feedback fiber optic accelerometer with wide bandwidth and high sensitivity [13639-345]

- 13639 9Y Exploring the application of Tamm plasmon resonance structures in fiber tips for remote hydrogen sensing [13639-352]
- 13639 9Z Optical fiber sensor for assessing asphaltene content in crude oil [13639-353]
- 13639 A0 Fluorescence-based optical fiber sensor for liquid sample analysis in silica glass well [13639-355]
- 13639 A1 Calibrating ITER-fibre optic current sensor [13639-356]
- 13639 A2 Extreme temperature fiber Bragg grating sensors for superconducting magnet and spacecraft applications [13639-368]
- 13639 A3 Reaching mGy resolution in radiation sensing with a slow-light FBG [13639-371]
- 13639 A4 Optical fiber apta-biosensor for Alzheimer's disease via amyloid-β oligomers sensing based on polished microsphere-LSPR [13639-376]
- 13639 A5 Discrimination of strain and temperature using Bragg gratings in side-hole rectangular fiber and embedded reduced-cladding fibers [13639-382]
- 13639 A6 **FBG-based temperature and fire sensors for use in industrial microwave ovens** [13639-390]
- 13639 A7 Artificial skin using photothermal optical fibers for material identification [13639-410]
- 13639 A8 Hydrogen optical sensors based on magnesium thin films for leak detection in industrial settings [13639-419]
- 13639 A9 Monitoring the manufacturing process and the operation of high-voltage bushings with fiber optics [13639-420]
- 13639 AA Simultaneous measurement of position and vibration in correlation-domain LiDAR [13639-424]
- 13639 AB In situ monitoring and sensing of gas generation during internal short circuits in Li-ion batteries using Raman spectroscopy and fiber bundle signal collection [13639-440]
- 13639 AC Study of a long-range perimeter intrusion detection system using deep-learning-based optical fiber distributed acoustic sensor [13639-445]
- 13639 AD Effect of gamma radiation on variously fabricated FBGs to verify the applicability of optical fiber sensors in radioactive environments [13639-452]
- 13639 AE Lab-around-fiber for rapid biological agent detection [13639-471]
- 13639 AF High-performance fiber-optic hot-wire flowmeter based on surface plasmon resonance and PDMS [13639-473]

- 13639 AG Single-mode helical sapphire fiber Bragg grating sensors fabricated by femtosecond laser direct writing technology [13639-479]
- 13639 AH Optical fiber sensor for glyphosate detection combining the functionality of gold and plasmonic properties of silver thin films [13639-485]
- 13639 AI Etched single-crystal sapphire fiber Bragg gratings for simultaneous temperature and strain sensing at 1500°C [13639-487]
- 13639 AJ Next-generation photonic-crystal-fiber-based plasmonic sensor for heavy metal detection via spectroscopy and refractive index integration [13639-489]
- 13639 AK Development of a multi-core fiber-Bragg-grating-based axial tip force sensor for left-atrial appendage closure procedure [13639-490]
- 13639 AL Fiber laser LIBS as a sensing tool for chemical mapping of heritage tiles [13639-492]
- 13639 AM Graphene oxide for improved sensitivity and response time of fibre-Bragg-grating-based humidity sensors [13639-495]
- 13639 AN Online monitoring of electric transmission lines using an optical ground wire with distributed acoustic sensing [13639-502]
- 13639 AO SPR-based tapered MCF sensor for monitoring of poly (T) poly (A) binding [13639-512]
- 13639 AP Staphylococcus aureus detection based on tapered MCF [13639-516]
- 13639 AQ Effect of adhesives on the spectral response of Bragg gratings embedded on sapphire wafer in extreme cryogenic temperatures [13639-518]
- 13639 AR Simultaneous measurement of temperature and ionizing radiation dose based on type-II FBGs inscribed in P-doped optical fibers [13639-521]
- 13639 AS Fiber optical current sensor for quasi-DC currents during high-voltage short-circuit tests [13639-542]
- 13639 AT Decoupling temperature and humidity with chitosan-coated tilted FBG sensor [13639-544]
- 13639 AU High-sensitivity dual-disk fiber-optic vibration sensing with wideband flattened response [13639-547]
- 13639 AV Highly strain sensitivity sensor by long period fiber grating inscribed in multi-mode fiber using CO₂ laser [13639-552]
- 13639 AW Hydrogel-integrated FBG sensors for real-time pH monitoring [13639-556]
- 13639 AX Torque and rotational speed FBG-based measurements by sensorized FDM support structure for aerospace applications [13639-558]

13639 AY	Effect of core breakage on measurement symmetry in shape sensing based on optical fiber sensors [13639-566]
13639 AZ	Gas sensing inside hollow-core fibers [13639-572]

- 13639 B0 Plasmonic immunosensors based on POF D-shaped for detection of ochratoxin A [13639-573]
- 13639 B1 FBG-based optical extensometer for high-precision mechanical tests [13639-575]
- 13639 B2 Estimating fiber borehole seismometer orientation using active-source P-wave particle motion analysis [13639-576]
- 13639 B3 Cell movement monitoring using microcavity Mach-Zehnder interferometer [13639-578]