

# **2026 IEEE Radio Frequency Integrated Circuits Symposium (RFIC 2026)**

**Boston, Massachusetts, USA  
7-9 June 2026**

IEEE Catalog Number: CFP26MMW-POD  
ISBN: 979-8-3195-1804-0



Copyright © 2026, IEEE

All Rights Reserved

**Copyright and Reprint Permissions:**

Abstracting is permitted with credit to the source. Libraries are permitted to photocopy beyond the limit of U.S. copyright law for private use of patrons those articles in this volume that carry a code at the bottom of the first page, provided the per-copy fee indicated in the code is paid through Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923.

For other copying, reprint or republication permission, write to IEEE Copyrights Manager, IEEE Service Center, 445 Hoes Lane, Piscataway, NJ 08854. All rights reserved.

\*\*\* This is a print representation of what appears in the IEEE Digital Library. Some format issues inherent in the e-media version may also appear in this print version.

|                         |                   |
|-------------------------|-------------------|
| IEEE Catalog Number:    | CFP26MMW-POD      |
| ISBN (Print-On-Demand): | 979-8-3195-1804-0 |
| ISBN (Online):          | 979-8-3195-1803-3 |
| ISSN:                   | 1529-2517         |

**Additional Copies of This Publication Are Available From:**

Curran Associates, Inc  
57 Morehouse Lane  
Red Hook, NY 12571 USA

|         |                                                                    |
|---------|--------------------------------------------------------------------|
| Phone:  | (845) 758-0400                                                     |
| Fax:    | (845) 758-2633                                                     |
| E-mail: | <a href="mailto:curran@proceedings.com">curran@proceedings.com</a> |
| Web:    | <a href="http://www.proceedings.com">www.proceedings.com</a>       |

# TABLE OF CONTENTS

|                                                                                                                                                                                                               |    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Ethernet to RF: Single Chip ORAN 4TX/4RX 5G Radio Unit Base Station Transceiver .....                                                                                                                         | 3  |
| <i>Kevin Gard, Jianxun Fan, Dicle Ozis, Gord Allan, Kashif Sheikh, Justin Fortier, Tony Montalvo, Bing Zhao<br/>David McLaurin, Benjamin Babjak, Ionel Gheorghe, Bruce Wilcox, Manish Manglani, Adam Bray</i> |    |
| A 57-67 GHz+14 dBm 4-Channel Transmitter with 7-Bit Phase Shifter and Built-in Self-Test for<br>Doppler-Offset Doppler Division Multiplexing Fmcw Radar .....                                                 | 7  |
| <i>Jeff Shih-Chieh Chien, Samrat Dey, Ying Chen, Mingyuan Li, Ivan Siu-Chuang Lu, Tienyu Chang<br/>Wanhua Wu, Joonhoi Hur</i>                                                                                 |    |
| A $\pi$ -Band Fully-Connected 4-Channel Beamforming Transmitter IC for LEO SATCOM in 65 nm<br>CMOS .....                                                                                                      | 11 |
| <i>Jongho Yoo, Junhan Lim, Seong-Mo Moon, Hakmin Lee, Hongkie Lim, Dong-pil Chang</i>                                                                                                                         |    |
| A Sige Txsip for E-Band Point-To-Point Systems From 71 to 86 Ghz With $>32 \text{ dBm}$ Output<br>Power .....                                                                                                 | 15 |
| <i>Christoph Steinbrecher, Fatih Kocer, Julio Canelo, Ekrem Oran, Ozgun Serttek, Kasim Ayyildiz<br/>Santosh Kudtarkar, Arun Raj, Sacid Oruc, Mete Coskun</i>                                                  |    |
| A 12-16.3-GHz 197.7-dBc/Hz-FOMT Harmonic-Shaping VCO Using Enhanced Common-Mode<br>Resonance Expansion Based on a Triple-Tank Coupled Resonator .....                                                         | 19 |
| <i>Jin Zhang, Miao Yu, Kaixue Ma</i>                                                                                                                                                                          |    |
| A 15-18.3 GHz Upper Ku-Band LC-Vco Achieving 201 dBc/Hz FoMA in 65-nm CMOS .....                                                                                                                              | 23 |
| <i>Alan Nelson, Adarsh Yadav, Narahari N. Moudghalya, Abhishek Srivastava</i>                                                                                                                                 |    |
| Cross-Coupled Cmos Series-Resonance VCO with 3Rd-Harmonic Output and $-142 \text{ dBc/Hz}$ Phase<br>Noise at 10 MHz Offset from 29.7 GHz .....                                                                | 27 |
| <i>Kemal Vural, Andrea Bilato, Guglielmo De Filippi, Andrea Mazzanti</i>                                                                                                                                      |    |
| Fundamental 9.9-to-30GHz $207 \text{ dBc} / \text{Hz}$ $\text{FoM}_{\text{T}}$ Quad-Core<br>Quad-Mode VCO Utilizing One-Coil-for-All Topology in 40nm CMOS .....                                              | 31 |
| <i>Changqi Zhou, Hao He, Haobin He, Hanlin Yang, Yi Liu, Zuojun Wang, Bin Li, Xiang Yi, Zhijian Chen</i>                                                                                                      |    |
| A 2.4-GHz Reconfigurable Digital Transmitter with Three-Vector-Synthesized IQ-Shared PA and<br>Envelope Rotation Calibration for Multi-Standard IoT Applications .....                                        | 35 |
| <i>Linhao Ma, Zongle Ma, Qing Li, Hui Zhang, Dong Liang, Kai Li, Huan Yan, Keping Wang</i>                                                                                                                    |    |
| A $28.5 \text{ dBm}$ $3.3 \sim 1.1 \text{ V}$ All-Digital Wi-Fi 7 Polar Transmitter<br>Employing Triple-Stacked Doherty Class-G SC-DPA in 14 NM Fin-FET .....                                                 | 39 |
| <i>Naor R. Shay, Elad Solomon, David Ben-Haim, Eran Socher, Ofir Degani</i>                                                                                                                                   |    |
| +28.5 dBm 5–7 GHz FIR and Doherty Polar DTX Achieving -155 dBc/Hz OOC Noise for WiFi MLO<br>Applications .....                                                                                                | 43 |
| <i>Eli Borokhovich, Eran Socher, Ofir Degani</i>                                                                                                                                                              |    |
| A 12 bit, 1.3 GHz to 4.7 GHz Switched Current Source RF Power-DAC Achieving $-47.2 \text{ dB}$ EVM for<br>4096-QAM .....                                                                                      | 47 |
| <i>Manuel Wittlinger, Jakob Finkbeiner, Raphael Nägele, Markus Grözing, Manfred Berroth<br/>Georg Rademacher</i>                                                                                              |    |

|                                                                                                                                                                                            |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Low Cost Wideband Continuous-Time Linear Equalizers (CTLE) based on SiGe BiCMOS Phase Change Material (PCM) Switches .....                                                                 | 51  |
| <i>Tian Liang, Mir H. Mahmud, Hasan Al-Rubaye, Gabriel M. Rebeiz</i>                                                                                                                       |     |
| A $1.28 \text{ pJ} / 32 \text{ Gb/s}$ Digital Isolator Using Coupled-Line Transformer for High-Speed Data Links .....                                                                      | 55  |
| <i>Jinyu Zhang, Rongxiang Wu, Yan Huo, Zheng Wang</i>                                                                                                                                      |     |
| A npn-npn Folded Cascode 240-Gs/S 2-to-1 Analog Multiplexer in Complementary 130-nm SiGe BiCMOS .....                                                                                      | 59  |
| <i>Maaz Khurram, Truman Jian, Peter Schvan, Sorin P. Voinigescu</i>                                                                                                                        |     |
| A Cryo-Cmos Electron/Nuclear Spin Controller with Combined Ghz/Mhz Drivers for Color-Center Qubits .....                                                                                   | 63  |
| <i>Mohamed A. Elbadry, Niels Fakkkel, Luc Enthoven, Fabio Sebastiano, Masoud Babaie</i>                                                                                                    |     |
| INFINITY: A 45-310 GHz InP-FinFET CMOS Co-packaged Sliding-IF Transmitter with On-Chip Resonant Cavity Antenna .....                                                                       | 67  |
| <i>Berke Gungor, Senne Gielen, Yang Zhang, Mark Ingels, Patrick Reynaert</i>                                                                                                               |     |
| A Novel 128 GHz 8-PSK Receiver Using an on-Chip Multi-Probed Interferometer for Direct Phase-to-Bits Demodulation .....                                                                    | 71  |
| <i>Runzhou Chen, Hao-Yu Chien, Boxun Yan, Chao-Jen Tien, Mau-Chung Frank Chang</i>                                                                                                         |     |
| Antenna-Integrated, Chip-Embedded Glass Packaging of $200\text{-GHz}$ Transceiver Modules .....                                                                                            | 75  |
| <i>Yuya Nemoto, Xingchen Li, Madhavan Swaminathan, Mark J.W. Rodwell</i>                                                                                                                   |     |
| A 240 Gb/s 0.51 pJ/b D-Band Direct-Conversion Receiver with Injection-Locking Based Quadrature Correction in 28 nm CMOS .....                                                              | 79  |
| <i>Xiaohan Shen, Xiaodi Feng, Siyu Men, Haoyu Zhu, Ningsheng Xu, Chen Jiang</i>                                                                                                            |     |
| A 138-GHz Dielectric Waveguide Link with 4.87 pj/bit Efficiency in 28-nm CMOS .....                                                                                                        | 83  |
| <i>Jiacheng Guo, Xinsheng Cheng, Yixia Wang, Yuchi Liu, Jizhao Li, Li Du, Yuan Du</i>                                                                                                      |     |
| A 140-GHz 9-mW Self-Calibrating Quadrature Generator .....                                                                                                                                 | 87  |
| <i>Long Kong</i>                                                                                                                                                                           |     |
| An 85.5-to-94.5-GHz W-Band Fully-Symmetric Quadrature Lo Generator with a Fast Quadrature Calibration Technique, Achieving Closely Matched 61-FsRMS Jitter and 41-dB IRR .....             | 91  |
| <i>Sarang Lee, Seohee Jung, Seohyeon Kwak, Seungjae Lee, Hoojung Lee, Jaehyouk Choi</i>                                                                                                    |     |
| A 69.2-85.6-GHz LO Generator Achieving 192.2-dBc Hz FoM and 201.4-dBc Hz FoMA with Current-Reused Coupled Frequency Tripler and Implicit Ninth Harmonic Extraction in 65 Nm CMOS .....     | 95  |
| <i>Shuo Tian, Kaitian Yang, Yong Chen, Xiaolong Liu</i>                                                                                                                                    |     |
| A 40-GHz Series-Resonance VCO with Windmill-Coupled F-Type Inductive Network Achieving $-132.36 \text{ dBc Hz PN}$ at a 10-MHz Offset .....                                                | 99  |
| <i>Chen Yu, Changwenquan Song, Shiyuan Zheng, Liang Wu</i>                                                                                                                                 |     |
| A High Performance Complementary Sige Hbt Power Amplifier with a Three Conductor Coupled Line Four-Way Wilkinson Combiner Balun for Emerging K-Band Leo Satcom Transmit Front-End Ic ..... | 103 |
| <i>Seungkyun Lee, Yoongoo Kang, Inchan Ju</i>                                                                                                                                              |     |

|                                                                                                                                                                                           |     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A Ka-Band CMOS 4-Element Beamforming Transmitter for LEO SATCOM Using PA with Negative-Feedback-Based Interstage Matching Network and Asymmetric Wilkinson Power Divider .....            | 107 |
| <i>Wonseob Lee, Hyungju Kim, Hyeonwon Song, Mingyu Lee, Sunwoo Kong, Seunghyun Jang, Hui-Dong Lee Bonghyuk Park, Seungchan Lee, Jinseok Park</i>                                          |     |
| A Watt-level, Thermally Reliable Ku-Band SiGe HBT Cascode Flip-Chip Power Amplifier Module Using an Optimal IC-to-Package ElectroThermal Codesign for LEO SATCOM Transmit Front-End ..... | 111 |
| <i>Seungpyo Han, Minchul Kim, Inchan Ju</i>                                                                                                                                               |     |
| Top-Metal-Only RFIC Retargeting for Fast Specs-To-Silicon Iteration Enabled by AI-Assisted Inverse Design .....                                                                           | 115 |
| <i>Chenhao Chu, Yuqi Liu, Yizhou Xu, Shouqing Fu, Takuma Torii, Shintaro Shinjo, Konstantinos Manetakis Andreas Burg, Hua Wang</i>                                                        |     |
| A 2-to-18 GHz Reconfigurable LNA Using Direction Switchable Coupling Presenting 0.78-to-1.24 dB NF in 0.15- $\mu$ m GaAs PHEMT .....                                                      | 119 |
| <i>Hao Ning, Zhaowu Wang, Yijie Zhang, Xinyan Li, Xiaochen Tang, Yong Wang</i>                                                                                                            |     |
| Mim Capacitor-Assisted Inverse Design of Nonintuitive Amplifiers .....                                                                                                                    | 123 |
| <i>Vinay Chenna, Hossein Hashemi</i>                                                                                                                                                      |     |
| A Broadband Distributed Low-Noise Amplifier with Full-Band Noise Optimization and Built-In Balun .....                                                                                    | 127 |
| <i>Yidong Fang, Lianbo Liu, Hao Guo, Taiyun Chi, Sensen Li</i>                                                                                                                            |     |
| A Broadband Distributed Amplifier Extending the Operation Frequency to $0.944 f_{\text{T}}$ .....                                                                                         | 131 |
| <i>Jianquan Hu, Changzi Xie, Fanyi Meng, Kaixue Ma</i>                                                                                                                                    |     |
| A Dc-to- 170 Ghz Broadband Distributed Spdt-Switch and Powercombiner Combo with Source Switch Control .....                                                                               | 135 |
| <i>Yidong Fang, Lianbo Liu, Song Hang Chai, Hang Wang, Taiyun Chi, Sensen Li</i>                                                                                                          |     |
| A W-Band Low-Noise Switched-Gm Down-Conversion Mixer With Gm-Boosting Feedback and Trifilar Transformer in 65- CMOS .....                                                                 | 139 |
| <i>Benqing Guo, Jing Gong, Jun Chen</i>                                                                                                                                                   |     |
| A Broadband Fully-Distributed Mixer-First Receiver Achieving 40-128 GHz Rf Bandwidth .....                                                                                                | 143 |
| <i>Zhaojing Fu, Hao Yu, Gerald Topalli, Taiyun Chi, Sensen Li</i>                                                                                                                         |     |
| An FR3 Simultaneous Dual-Carrier Passive Mixer-First Diplexer Receiver Front-End Achieving 6.4 dB NF and -3.2 dBm B1dB .....                                                              | 147 |
| <i>Jamie C. Ye, Alain H. Antón, Alyosha C. Molnar</i>                                                                                                                                     |     |
| A 6Ghz 3X Subharmonic Mixer with 12.4-Db Conversion Gain and 73-dB Fundamental Rejection .....                                                                                            | 151 |
| <i>Ahmed R. Aboulsaad, Zhuoran Wu, Noah Levy, Jacques C. Rudell</i>                                                                                                                       |     |
| A 1.5–4-GHz Reconfigurable N-Path Notch Filter with 40-\text{dBc} Rejection and 15-\text{dBm} B1dB .....                                                                                  | 155 |
| <i>Gucheng Zhou, Ziyuan Chen, Xiong Chen, Pei-Ling Chi, Tao Yang</i>                                                                                                                      |     |
| D-Band Variable-Gain Balanced Power Amplifier with 36% FBW, 18.2 dBm PSAT and Reconfigurable Adaptive Bias in 22-nm FD-SOI .....                                                          | 159 |
| <i>Giacomo Venturini, Patrick Reynaert</i>                                                                                                                                                |     |

|                                                                                                                                                              |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A 0.036 mm <sup>2</sup> , 145 GHz CMOS Power Amplifier with 7.4% PAE <sub>1dB</sub> and 4.2 dBm OP <sub>1dB</sub> for Large Arrays .....                     | 163 |
| <i>Kwangwon Park, Mark Rodwell</i>                                                                                                                           |     |
| A 9.5-to-40 GHz Ultra-Broadband Linear Power Amplifier with Compensated Coupled-Line Transformer in 65-nm Bulk CMOS .....                                    | 167 |
| <i>Sangjin Yoo, Kyutaek Oh, Geuntae Kim, Ilku Nam, Ockgoo Lee</i>                                                                                            |     |
| A 15.5-46.0 GHz Broadband Power Amplifier with 19.0-22.0 dBm P <sub>sat</sub> and 30.0% Peak PAE <sub>max</sub> in 28-nm Bulk CMOS .....                     | 171 |
| <i>Ting Huang, Hongtao Xu, Yun Yin</i>                                                                                                                       |     |
| A 37–43 GHz VSWR-Resilient Load-Isolated Doherty Power Amplifier Achieving 26% Average PAE at 36 Gb/s in 45-nm SOI CMOS .....                                | 175 |
| <i>Yahia Ibrahim, Ali Niknejad</i>                                                                                                                           |     |
| A 4T4R Code-Domain UWB Radar with Fully Analog Multi-Lag Correlators and Pre-Correlation Averaging .....                                                     | 179 |
| <i>A. Undavalli, A. S. Kumar, T. G. Liang, K. Rashed, S. Chakrabartty, A. Natarajan, A. Nagulu</i>                                                           |     |
| A 2 to 20 GHz Resolution-Enhanced RF Spectrum Sensor Using a Looped Phase-Time Array .....                                                                   | 183 |
| <i>Liwen Zhong, Meijun Tian, Wooram Lee</i>                                                                                                                  |     |
| 405-GHz 2×2 Concurrent Transceiver Pixel Array with 7.8-GHz Bandwidth Using Series-Coupled Standing-Wave Oscillators .....                                   | 187 |
| <i>Seungmo Noh, Goutham Murugesan, Seongjae Mun, Young-Joon Lee, Frank Zhang, Wooyeol Choi, Kenneth K. O</i>                                                 |     |
| A Doppler-Assisted 76 GHz PMCW Radar with Meter-Scale Unambiguous Range and $\mu\text{m}$ -Scale Range Accuracy .....                                        | 191 |
| <i>Zhengyang Zhang, Xuyang Liu, Yilun Huang, Hamidreza Aghasi</i>                                                                                            |     |
| A W-Band RTWO-Based Digital Transmitter for PMCW Radar Achieving 14.9% Efficiency .....                                                                      | 195 |
| <i>Shaoqi Yang, Zhongjun Zhang, Weichen Tao, Yuhao Yang, Juncheng Deng, Jing Liu, Fujiang Lin, Robert Bogdan Staszewski, Liheng Lou, Yizhe Hu</i>            |     |
| A 4-Channel Self-Synchronizing Receiver Array Without LO Distribution with Angle-of-Arrival Estimation .....                                                 | 199 |
| <i>Subhan Zakir, Waleed Ahmad, Alireza Kiyaei, Atif H. Shah, Saeed Zeinolabedinzadeh</i>                                                                     |     |
| A 24–29.5-GHz CMOS Front-End Module With 33.6% TX Peak Efficiency and 5.8-mW RX Power Consumption .....                                                      | 203 |
| <i>Dong-Jun Shin, Songcheol Hong</i>                                                                                                                         |     |
| A 5.2 $\sim$ 7.8 GHz Cryo-CMOS LNA with 4-K Noise Temperature with Cascode $g_m$ -Boosting and Current Reuse for Noise Reduction .....                       | 207 |
| <i>Yujie Geng, Hang Fu, Haotian Chen, Cheng Wang</i>                                                                                                         |     |
| A 10–19.2 GHz LNA Using a Partially Three-Winding Transformer and Class-AB Operation Achieving –5.3 to –2.4 dBm IP <sub>1dB</sub> for 6G FR3 Receivers ..... | 211 |
| <i>Min-Seok Baek, Joon-Hyung Kim, Jae-Hyeok Song, Jong-Seong Park, Ilhun Kim, Eun-Gyu Lee, Seong-Mo Moon, Dongpil Chang, Choul-Young Kim</i>                 |     |

|                                                                                                                                                                                                                                                                                                                            |     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A 77.3-GHz 3.36-dB Nf Lna with Cross-Coupled Noise Cancellation and Low-Loss Input Matching Transformer in 22-nm Cmos .....                                                                                                                                                                                                | 215 |
| <i>Juncheng Deng, Aodi Li, Binzhi Liao, Zhongjun Zhang, Shaoqi Yang, Jing Liu, Zhongguang Xu<br/>Robert Bogdan Staszewski, Liheng Lou, Yizhe Hu</i>                                                                                                                                                                        |     |
| A 187-224-GHz 20-dB-Gain 4.5-dBm- $P_{\text{sat}}$ Power Amplifier With Dualband Matching Networks and Slotline Combining in 40-nm CMOS .....                                                                                                                                                                              | 219 |
| <i>Cheng-Xuan Tsai, Chun-Hsing Li</i>                                                                                                                                                                                                                                                                                      |     |
| A Compact 125-150-GHz Power Amplifier in 90-nm SiGe 9HP+ BiCMOS with 34-dB Gain for Phased-Array Transmitters .....                                                                                                                                                                                                        | 223 |
| <i>Joon-Hyung Kim, Jae-Hyeok Song, Min-Seok Baek, Jong-Seong Park, Gabriel M. Rebeiz, Choul-Young Kim</i>                                                                                                                                                                                                                  |     |
| A 286-GHz CMOS Amplifier Achieving 56-GHz BW <sub>3dB</sub> via $f_{\text{max}}$ -Boosting and Gain-Staggering .....                                                                                                                                                                                                       | 227 |
| <i>Dawei Tang, Yu-Chen Xue, Peigen Zhou, Zhe Chen, Jixin Chen, Hao Gao, Wei Hong</i>                                                                                                                                                                                                                                       |     |
| A D-Band Bidirectional Amplifier Utilizing Lossy U-Boosting Network .....                                                                                                                                                                                                                                                  | 231 |
| <i>Sunghwan Park, Yudai Yamazaki, Chenxin Liu, Chun Wang, Hiroyuki Sakai, Kazuaki Kunihiro<br/>Kenichi Okada</i>                                                                                                                                                                                                           |     |
| A Broadband 360° Distributed Vector-Summing Phase Shifter Achieving <1.99°/0.22-dB RMS Gain and Phase Error Over 8-to-110-GHz Bandwidth .....                                                                                                                                                                              | 235 |
| <i>Lianbo Liu, Yidong Fang, Zhaojing Fu, Hao Guo, Taiyun Chi, Sensen Li</i>                                                                                                                                                                                                                                                |     |
| A 91-125 GHz 6-Bit RF Beamforming Receive Channel Using a Dual Current-Steering Phase Shifter with a Digitized Transistor Core and Tunable Gate Bias in 22-Nm FD-SOI .....                                                                                                                                                 | 239 |
| <i>Haisu Ju, Yingtao Zou, Gabriel M. Rebeiz</i>                                                                                                                                                                                                                                                                            |     |
| A 28-GHz Bi-Directional Reflection-Amplifier-Based Phase Shifter for Active Reconfigurable Intelligent Surface (RIS) .....                                                                                                                                                                                                 | 243 |
| <i>Patchara Sawakewang, Apisak Worapishet, Tissana Kijsanayotin, Pingda Guan, Chawin Khongprasongiri<br/>Robert Bogdan Staszewski, Teerachot Siriburanon</i>                                                                                                                                                               |     |
| An 8-28 GHz Bidirectional Variable-Gain Phase Shifter for 6G FR3/ 5G n258 FR2 Featuring a Magnitude-Equalized Self-Similar 90° Coupler and a Simultaneously Phase-Temperature Compensated Attenuator .....                                                                                                                 | 247 |
| <i>Basem Abdelaziz Abdelmagid, Hua Wang</i>                                                                                                                                                                                                                                                                                |     |
| A 24-30 GHz 7-Bit Passive Hybrid Phase Shifter with <1.1° RMS Phase Error and <0.61 dB Amplitude Error .....                                                                                                                                                                                                               | 251 |
| <i>Ziang Zhang, Qin Chen, Xuhao Jiang, Yuchen Liang, Xuanxuan Yang, Rui Cao, Xiangning Fan<br/>Lianming Li</i>                                                                                                                                                                                                             |     |
| A 76-81 GHz FMCW MIMO Coded Transceiver for Automotive Radar .....                                                                                                                                                                                                                                                         | 255 |
| <i>Benny Sheinman, Tom Heller, Jakob Vovnoboy, Dan Corcos, Yanir Schwartz, Michael Grubman<br/>Dror Malowany, Yaal Horesh, Florian Bohn, Nico Bochmann, Mohamed Hussein Eissa<br/>Iskender Haydaroglu, Stefan Malz, Chris Menkus, Robert Kim, Abhilash Nagabhushana, Ichiro Aoki<br/>Scott Kee, Jeff Zachan, Oded Katz</i> |     |
| A Built-In Self-Test System for 60GHz MIMO FMCW Radar SoCs .....                                                                                                                                                                                                                                                           | 259 |
| <i>Wen Zhou, Gennady Feygin, Pranav Dayal, Hou-Shin Chen, Sowmya Srinivasa, Renu Krishna Gutta<br/>Pankaj D Solanki, Gregory Rogers, Oren E Eliezer, Mingyuan Li, Sai Krishna Rayudu, Taewoo Yu<br/>Junseuk Suh, Joonhoi Hur</i>                                                                                           |     |

|                                                                                                                                                                         |     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A 28-nm FD-SOI 77-GHz Automotive FMCW Radar with Antenna Launcher in Package .....                                                                                      | 263 |
| <i>Faisal Ahmed, Muhammad Furqan, Farshad Piri, Ibrahim Petricli, Mahmoud M. Pirbazari</i>                                                                              |     |
| <i>Federico Vecchi, Chandrajit Debnath, Andrea Manzoni, A. Michelin Salomon</i>                                                                                         |     |
| An Area-Efficient NBA-MMS UWB Receiver with Capacitance Boosting and PVT-Robust RSSI for IEEE 802.15.4Ab .....                                                          | 267 |
| <i>Sumin Kang, Junhyeong Kim, Sinyoung Kim, Wonjun Jung, Jonghoon Myeong, Duyong Seo, Hyun-Gi Seok</i>                                                                  |     |
| <i>Hyun-Chul Park, Chanhong Park, Joonsuk Kim</i>                                                                                                                       |     |
| An 802.15.4ab Narrowband Assistance RX Resilient to $-32\text{dBm}$ Blocker at $3.2\text{dB}$ NF with High Dynamic Range TIA and Clip Detector .....                    | 271 |
| <i>Anoop Narayan Bhat, Aasish Boora, Kaijie Ding, Johan van den Heuvel, Murat Eskiyeerli, Erwin Allebes</i>                                                             |     |
| <i>Peng Zhang, Mario Konijnenburg, Yao-Hong Liu, Peter Vis, Christian Bachmann</i>                                                                                      |     |
| A Calibration-Free 55-to-70 dBc H1 Rejection, 13.8 % Efficiency, 102-to-120 GHz CMOS Frequency Tripler using Phase-Alignment Technique for Harmonic Recombination ..... | 275 |
| <i>Sarah Koop-Brinkmann, Victor Lasserre, Vadim Issakov</i>                                                                                                             |     |
| A 110-142-GHz Frequency Quadrupler with $13.1\text{-}\text{dBm}$ $P_{\text{sat}}$ Achieved by Coupled-Line-Based Output Matching Technique in 130-nm SiGe .....         | 279 |
| <i>Zuojun Wang, Haorui Luo, Qin Dong, Zhou Shu, Jixin Chen, Kevin Tshun Chuan Chai, Yongxin Guo</i>                                                                     |     |
| A 108–170-GHz $\times 6$ Amplifier-Multiplier Chain with $16\text{-dBm}$ Output Power and $>29.5\text{-dBc}$ Harmonics Rejection in 130-nm SiGe Process .....           | 283 |
| <i>Chang Shu, Lingzheng Kong, Peigen Zhou, Dawei Tang, Zekun Li, Liqun Lu, Jixin Chen, Wei Hong</i>                                                                     |     |
| A Broadband $241\text{-}306\text{ GHz}$ Frequency Multiply-By-24 Based Coherent Radiator Delivering $+26.5\text{ dBm}$ EIRP in $90\text{-nm}$ SiGe BiCMOS .....         | 287 |
| <i>Jaskirat Singh Virdi, Wei Sun, Aydin Babakhani</i>                                                                                                                   |     |
| A 2–18 GHz Integrated 4-Channel Transmit/Receive Beamformer in 65-nm CMOS .....                                                                                         | 291 |
| <i>Jianhao Gong, Yudi Yang, Kun Gao, Zixuan Wang, Xingcun Li, Zan Zhou, Jiewen Wang, Huibo Wu</i>                                                                       |     |
| <i>Wenhua Chen</i>                                                                                                                                                      |     |
| A K-Band 4-Beam Phased Array Transmitter in Only 5-Layer PCB Enabled by Silicon-Assisted Beam-Combining Network for SATCOM .....                                        | 295 |
| <i>Ruiyang Jiang, Haikun Jia, Huanyu Ge, Jiankai Zhao, Wei Deng, Baoyong Chi</i>                                                                                        |     |
| Scalable and Compact Fully-Connected Network based on Gm-Cell Grid for $28\text{-GHz}$ Multi-Stream MIMO Receiver .....                                                 | 299 |
| <i>Seunghoon Lee, Sungmin Cho, Seung-Uk Choi, Sungbeom Kim, Inho Choi, Jiwon Kang, Youngseo Du</i>                                                                      |     |
| <i>Ho-Jin Song</i>                                                                                                                                                      |     |
| A 256-Element 28Ghz 5G NR Wirelessly-Powered Active Relay Transceiver with TDD Synchronization Free Bidirectional Amplifiers .....                                      | 303 |
| <i>Shu Date, Atsuya Hirayama, Sena Kato, Keito Yuasa, Michihiro Ide, Masayuki Kikuchi, Takashi Tomura</i>                                                               |     |
| <i>Jill Mayeda, Atsushi Shirane</i>                                                                                                                                     |     |
| A W-Band FMCW Radar Transceiver with Self-Calibrated Type-III ADPLL Achieving $1.27\text{-cm}$ Range Resolution for Imaging Applications .....                          | 307 |
| <i>Ling Hao, Haoyu Bai, Zhenkun Shen, Ningyuan Zhang, Jiazheng Zhou, Chuancheng Wu, Zihe Wang</i>                                                                       |     |
| <i>Junhua Liu, Huailin Liao</i>                                                                                                                                         |     |

|                                                                                                                                                                                                                 |     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A 460 Gb/s PAM-4 Linear Distributed Driver with 105 GHz BW for TFLN Modulators in 130nm SiGe BiCMOS .....                                                                                                       | 311 |
| <i>Leandro da Silva, Cedric Bruynsteen, Jakob Declercq, Armands Ostrovskis, Fabio Pittala, Guy Torfs</i>                                                                                                        |     |
| <i>Nishant Singh, Xin Yin</i>                                                                                                                                                                                   |     |
| A Single-Stage Feedback-Feedforward D-Band LNA in SiGe BiCMOS .....                                                                                                                                             | 315 |
| <i>Guglielmo De Filippi, Lorenzo Piatto, Andrea Mazzanti</i>                                                                                                                                                    |     |
| A 200-Gb/s Low-Noise TIA in 28-nm CMOS .....                                                                                                                                                                    | 319 |
| <i>Feiyang Zhang, Jianyu Yang, Yifei Xia, Zhixing Zhang, Ruixuan Yang, Liang Zhao, Wenxin Zhang</i>                                                                                                             |     |
| <i>Cailing Li, Zetong Zhang, Shenlei Bao, Binhao Wang, Li Geng, Dan Li</i>                                                                                                                                      |     |
| A $4 \times 212$ Gbps $3.34 \text{ pJ} / \$$ Bit Electronic-Photonic Co-Designed Transmitter Chipset in 0.18 -Um SiGe BICMOS and 90 NM Silicon Photonics .....                                                  | 323 |
| <i>Ziyue Dang, Ziyu Deng, Ye Liu, Qiansheng Wang, Zhicheng Wang, Ziyang Xie, Ruiyang Jiang, Haikun Jia</i>                                                                                                      |     |
| <i>Min Tan, Xi Xiao</i>                                                                                                                                                                                         |     |
| A 55-GHz Bandwidth PAM-4 InP DHBT Photoreceiver Based on PD-TIA Co-Design for > 112-GBd Optical Transceivers .....                                                                                              | 327 |
| <i>Antoine Chauvet, Romain Hersent, Fabrice Blache, Filipe Jorge, Marie Da-Rocha-Amaro, Karim Mekhazni</i>                                                                                                      |     |
| <i>Harry Gariah, Nil Davy, Colin Mismar, Virginie Nodjiadjim, Michel Goix, Agnieszka Konczykowska</i>                                                                                                           |     |
| <i>Bertrand Ardouin, Christophe Caillaud, Abed-Elhak Kasbari, Achour Ouslimani</i>                                                                                                                              |     |
| A 5-7 GHz Channel and Bandwidth Selective Shunt N-Path LNA Based Receiver with +6dBm OOC IB1dB, <-71 dBm LO Re-Radiation for WiFi 7 Multi-Link Operation .....                                                  | 331 |
| <i>Ran Krichman, Ashoke Ravi, Natan Ershengoren, Rotem Banin, Sashank Krishnamurthy, Uri Groszlik</i>                                                                                                           |     |
| <i>Oded Tal, Nave Sharvit, Oren E. Avraham, Sarit Zur, Ofir Degani</i>                                                                                                                                          |     |
| A Broadband G-Band Frequency Doubler in $130\text{-nm}$ SiGe Technology .....                                                                                                                                   | 335 |
| <i>Mingquan Bao, Yu Yan, Klaus Aufinger, Herbert Zirath</i>                                                                                                                                                     |     |
| A Fully Differential DC-Capable RF SPDT Switch in SOI .....                                                                                                                                                     | 339 |
| <i>Ilker Kalyoncu, Huseyin Kayahan</i>                                                                                                                                                                          |     |
| An 8–28-GHz 16-Phase Delay Locked Loop Employing Nested Feedback Loops in 28-nm CMOS .....                                                                                                                      | 343 |
| <i>Junyan Bi, Yechen Tian, Junjie Gu, Kaixuan Cen, Xiaoliang Shen, Hao Xu, Na Yan</i>                                                                                                                           |     |
| A 6.2-GHz Reference-Feedthrough-Suppressed Type-I Sampling PLL with a Bottom-Plate-Sampling PD Scoring $18.2 \text{ fs}_{\text{rms}}$ Jitter, $-258.7\text{-dB}$ FoM and $-80.6\text{dBc}$ Reference Spur ..... | 347 |
| <i>Ningyi Zhang, Jinhai Xiao, Xiaolong Liu, Rui Liu, Junao Zhu, Yuanhao Zhou, Futian Liang, Xinzhe Wang</i>                                                                                                     |     |
| <i>Wenyi Peng, Yintang Yang, Xiaohua Ma, Yue Hao, Maliang Liu, Yong Chen</i>                                                                                                                                    |     |
| A 25.4 Fs Jitter Fractional-N Digital Pll With an Lc-Based Power-Gated Oscillator and Series-Resonance Dco .....                                                                                                | 351 |
| <i>Daniele Lodi Rizzini, Michele Rossoni, Filippo Osio, Stefano Gallucci, Riccardo Moleri, Andrea Mazzanti</i>                                                                                                  |     |
| <i>Andrea L. Lacaita, Simone M. Dartizio, Salvatore Levantino</i>                                                                                                                                               |     |
| A 2.4-GHz $168\text{-fs}_{\text{rms}}$ -Jitter and $-56\text{-dBc}$ -Reference-Spur RO-Based Cascaded Injection-Locked Clock Multiplier .....                                                                   | 355 |
| <i>Qixuan Luo, Hongyu Mao, Xiaolong Liu</i>                                                                                                                                                                     |     |
| An Ultra Low Noise 5-GHz Ring Oscillator-Based PLL with Over-Sampling Feedforward Phase Noise Cancellation Achieving $-267.05 \text{ dB}$ FoMN .....                                                            | 359 |
| <i>Yi-Hsiang Huang, Po-Hao Cheng, Jacques C. Rudell</i>                                                                                                                                                         |     |

|                                                                                                                                                                                            |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A 110-170 GHz Phase-Insensitive and PVT-Robust Digital-Step Attenuator with Phase Compensation and Background Step Calibration .....                                                       | 363 |
| <i>Basem Abdelaziz Abdelmagid, Adam Wang, Hua Wang</i>                                                                                                                                     |     |
| A 121/145 GHz Dual-Band LNA with Single-Path and Dual-Mode Gain-Boosting Core in 28 nm CMOS .....                                                                                          | 367 |
| <i>Hokeun Lee, Hyo-Ryeong Jeon, Namun Hwang, Sang-Gug Lee, Kyung-Sik Choi</i>                                                                                                              |     |
| A 224-GHz 5.9-dBm- $P_{out}$ VCO Utilizing Deep-Triode-Induced Current Top-Clipping Technique .....                                                                                        | 371 |
| <i>Miao Yu, Jin Zhang, Kaixue Ma, Zhen Yang</i>                                                                                                                                            |     |
| A 111.5GHz-to-163.6GHz 37.9%-Tuning-Range –200.3dBc/Hz-FoMT VCO Employing Hybrid Coarse-Magnetic-Tuning and Fine-Capacitive-Tuning Techniques .....                                        | 375 |
| <i>Hanlin Yang, Bodong Zhang, Yi Liu, Zixi Jing, Zhiyu Liu, Howard C. Luong</i>                                                                                                            |     |
| A 220 to 260 GHz Ultra-Compact, Calibration-Free 5-bit Phase Shifter with 1.8° RMS Phase Error in 9HP SiGe Process .....                                                                   | 379 |
| <i>Meijun Tian, Liwen Zhong, Wooram Lee</i>                                                                                                                                                |     |
| A 1.49 3pJ/b 4-Channel 256-Gb/s MRM-Based Coherent Co-Packaged Optics with Linear Carrier Phase Recovery .....                                                                             | 383 |
| <i>Pengyu Zeng, Marziyeh Rezaei, Daniel Sturm, Asha Rashmi Nayak, Hongyong Li, Sajjad Moazeni</i>                                                                                          |     |
| A 200Gbps 0.67 pJ/bit Transceiver Front-End for Silicon-Photonics with Group Delay and Nonlinear Adjustment in 28 nm CMOS .....                                                            | 387 |
| <i>Yihao Yang, Shenlei Bao, Chao Cheng, Binhao Wang</i>                                                                                                                                    |     |
| An 8 × 64 Gb/s Pam-4 Retimed Optical Receiver with Forwarded Clock for Ucie Compliant Optical I/O in 28-nm CMOS .....                                                                      | 391 |
| <i>Yukun He, Junhao Zhao, Zhouchi Duan, Puxi Tan, Yucong Li, Yujie Zeng, Zhihao Peng, Huanfa Sun, Shangjie Wei, Chenming Zhang, Dong Wang, Shiming Wu, Jian Luan, Hao Luo, Xiaoyan Gui</i> |     |
| A 3.5-to-14Ghz, Less-Than-0.81Lsb-Inl <sub>pp</sub> , 7B Adaptive Phase Interpolator with Segment-Squeeze Inl Calibration Algorithm for Die-to-Die Interfaces .....                        | 395 |
| <i>Shiju Li, Yihan Chen, Wei Deng, Nan Qi, Haikun Jia, Liyuan Liu, Baoyong Chi</i>                                                                                                         |     |
| High-Performance Near-Enhancement-Mode InAlGa <sub>N</sub> /Ga <sub>N</sub> HEMTS on Silicon with High $f_{\text{max}}$ of 71.5/173.1 GHz for Millimeter-Wave Applications .....           | 399 |
| <i>Hsuan-Yao Huang, Po-Wei Chen, You-Chen Weng, You-Ting Lin, Fitriyadi, Jeng-Chyang Sun, Chen Zhang, Edward Yi Chang</i>                                                                  |     |
| GH10-10 Nonlinear Thermal Model Capability & 3W SatCom HPA .....                                                                                                                           | 403 |
| <i>Samira Bouzid-Driad, Frederic Drillet, Christophe Chang, Manfred Madel, Kimon Vivien, Laurent Brunel, Romain Pecheux, Herve Blanck, Valeria Di Giacomo-Brunel</i>                       |     |
| Fully Aluminum-Based 0.25 $\mu\text{m}$ 20 $\text{V}$ GaN-on-Si Process With 3 $\text{W}/\text{mm}^2$ for FR3 .....                                                                        | 407 |
| <i>Hsien Shun Wu, Yuan Gao, Qingyun Xie, Yi Heng Leong, Wee Leng Ong, Lakshmi Kanta Bera, Navab Singh, Geok Ing Ng</i>                                                                     |     |
| A 4 W Heterogeneous Power Amplifier With Gan-On-Si Dielets in Single-Crystal Diamond Interposer for 6G Fr3 Applications .....                                                              | 411 |
| <i>Pradyot Yadav, Xingchen Li, Danish A. Baig, Ruonan Han, Madhavan Swaminathan, Tomas Palacios</i>                                                                                        |     |

|                                                                                                                                                                                                                                          |     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A Transformer-Based Inverse-Class-F-Like VCO With a Digitally Controlled Common-Mode Impedance Tuner .....                                                                                                                               | 415 |
| <i>Hyunjoon Kim, Donghyeon Seong, Seungwoo Shim, Sanggeun Jeon</i>                                                                                                                                                                       |     |
| A 5.56-9.09 GHz Octa-Core Dual-Mode DCO Based on Multi-Tap Three-Turn Inductor Achieving 195.7 dBc/Hz FoM and Wideband Flicker PN Suppression .....                                                                                      | 419 |
| <i>Jiexi Weng, Liangqi Dong, Yuhao Yang, Guanjun Liu, Liheng Lou, Robert Bogdan Staszewski, Yizhe Hu</i>                                                                                                                                 |     |
| A 7.0-to-8.6 GHz Balanced Class-F <sup>-1</sup> VCO with a Trifilar Transformer-Based Tank Achieving 194.5 dBc/Hz FoM .....                                                                                                              | 423 |
| <i>Yunbo Huang, Zunsong Yang, Kai Cheng, Hongyu Ren, Xiaoyu Shan, Li Wang, Yong Chen, Bo Li</i>                                                                                                                                          |     |
| Harmonically Coupled Current-Sharing 4-Phase and 6-Phase Oscillators in 65-nm CMOS .....                                                                                                                                                 | 427 |
| <i>Bahram Jafari, Samad Sheikhaei, Sankaran Aniruddhan, Shahriar Mirabbasi, Sudip Shekhar</i>                                                                                                                                            |     |
| A 10.66-to-15.03 GHz Dual-Core Dual-Mode Series Resonance VCO Achieving 209 dBc/Hz FoM <sub>TA</sub> .....                                                                                                                               | 431 |
| <i>Yichen Liu, Zhenbo Rao, Yan Wang</i>                                                                                                                                                                                                  |     |
| 3D-RDL and Bondwire Technology Comparison for Implementation of a 10W Broadband Three-way LDMOS Doherty Power Amplifier .....                                                                                                            | 435 |
| <i>Mohadi Rousstia, Ayad Ghannam, Mariano Ercoli, John Gajadharsing</i>                                                                                                                                                                  |     |
| A 10-W 7-GHz GaN-on-Si Doherty Power Amplifier with Hybrid MMIC-Module Integration for 6G Base-Station Applications .....                                                                                                                | 439 |
| <i>Kyung Pil Jung, Seunghoon Jee, Seung Hun Kim, Sungjae Oh, Jungsik Kim, Dongki Kim, Seong-Kyun Kim</i>                                                                                                                                 |     |
| A 60GHz LNA and PA Achieving 5dB NF and 35.6% Peak PAE in a Gate-All-Around (GAA) CMOS Process with Backside Power Delivery .....                                                                                                        | 443 |
| <i>Steven Callender, Ibukun Momson, Awani Khodkumbhe, Ali Niknejad, Said Rami, Stefano Pellerano</i>                                                                                                                                     |     |
| A Wideband and Linear 300 GHz Power Amplifier in 130 Nm SiGe BiCMOS Technology .....                                                                                                                                                     | 447 |
| <i>Enrico Jimenez Tuero, Seyyid Dilek, Andrea Malignaggi, Corrado Carta</i>                                                                                                                                                              |     |
| A 533μW Fast Duty-Cycled Pulsed-Lo Beam-Steering Receiver .....                                                                                                                                                                          | 451 |
| <i>Yasir Al-Theyabi, David D. Wentzloff</i>                                                                                                                                                                                              |     |
| MSCR: Multi-Source-Collaborative Reconfigurable RF Energy Harvester with 3-D MPPT Achieving -32 dBm Sensitivity and 8X Boost in Available Output Power .....                                                                             | 455 |
| <i>Yunzhi Ma, Yiming Liu, Haoyu Chen, Yongling Zhang, Lei Qiu, Miao Meng</i>                                                                                                                                                             |     |
| High Resolution Active True Time Delay with Quasi-Quadrature Generator with 31.7 dB/500 MHz Self-Interference Cancellation for Full-Duplex Communication .....                                                                           | 459 |
| <i>Eunji Jeong, Eunhae Jo, Honghyun Jeon, Haram Park, Hyeonwon Song, Taehyeon Kim, Subin Lim, Seongmo Moon, Seunghyun Jang, Seunguk Oh, Taehwan Jang, Seungchan Lee, Songcheol Hong, Jinseok Park</i>                                    |     |
| A 1 × 2 cm <sup>2</sup> Localization Tag With a 2.92 GHz Transmitter Chipset for Leo Satellite Localization Using Hardware and Algorithm Co-Design .....                                                                                 | 463 |
| <i>Yunfan Wang, Rahul Narasimha, Steve Young, Yi Shen, Zhen Feng, Demba Komma, Seokhyeon Jeong, Qirui Zhang, Andrea Bejarano-Carbo, Jiajun Tang, Chien-Wei Tseng, Guanchen Tao, Yufan Yue, Taekwang Jang, Hun-Seok Kim, David Blaauw</i> |     |
| Design and Comparison of Two SiGe Complementary Millimeter-Wave Power Amplifiers .....                                                                                                                                                   | 467 |
| <i>Wei Ma, Weiqing Wang, Fangkai Wang, Hanzhong Xu, Xudong Wang</i>                                                                                                                                                                      |     |

|                                                                                                                                                                                                                                                 |     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| A Millimeter-Wave Frequency Reconfigurable Dual-Band T/R Front-End for 2.5:1 VSWR-Resilient in Tx Operation .....                                                                                                                               | 471 |
| <i>Zikang Hu, Yanchen Lin, Wen Rao, Li Gao, Xiu Yin Zhang</i>                                                                                                                                                                                   |     |
| A 47 -To- 100 Ghz Oscillator-Embedded Artificial Transmission Line Based Lo Generator Achieving Averaged Fomt of $-193.7 \text{ dBc} / \text{Hz}$ .....                                                                                         | 475 |
| <i>Wei Sun, Benyamin Fallahi Motlagh, Boxun Yan, Aydin Babakhani</i>                                                                                                                                                                            |     |
| A Blocker-Tolerant K-Band LNA with 52-dB Ka-Band TX Rejection for Satellite Communications .....                                                                                                                                                | 479 |
| <i>Heyi Sun, Chenxi Zhao, Yiming Yu, Huihua Liu, Yunqiu Wu, Kai Kang</i>                                                                                                                                                                        |     |
| A General-Purpose Schematic-Layout Co-Optimization Platform for RFIC Design Demonstrated with a 1.7-dB-Nf 12-28GHz LNA .....                                                                                                                    | 483 |
| <i>Yuwen Tao, Xiangyu Meng, Pengfei Bai, Junbin Ouyang, Baoyong Chi</i>                                                                                                                                                                         |     |
| Accurate, High Coverage On-Chip Built-In Self-Test Adopting Precision-Enhanced Power Detection and Multipath Loopback for mmWave Radar IC Measurements .....                                                                                    | 487 |
| <i>Doyoon Kim, Kyunghwan Kim, Geonho Park, Goeun Baek, Byeong-Taek Moon, Hyun-Chul Park Chan-Hong Park</i>                                                                                                                                      |     |
| Sub-60 fs RFSOI Switch Performances in Advanced 200 nm 130/65 nm Hybrid Technology .....                                                                                                                                                        | 491 |
| <i>Robin Bousmaha--Jouve, Julien Dura, Julien Amouroux, Pascal Masson, Remy Vauche Frederic Ganesello, Wenceslas Rahajandraibe, Julien Babic, Romain Laire, Fayrouz Haddad Pascal Fornara, Franck Julien, Clement Charbuillet, Alain Fleury</i> |     |
| A 9-11 GHz Multistage Switched-Capacitor Delay Element and Signal Repeater Achieving 4.6-71.4 ns Delay and 40 dB Gain .....                                                                                                                     | 495 |
| <i>Travis Forbes, Benjamin Magstadt, Robert Costanzo, Jesse Moody</i>                                                                                                                                                                           |     |
| A 2.4 GHz $369\text{-}\mu\text{W}$ Low-Latency Wux with Voltage-To-Frequency Digital Demodulation and Bit-Error Correction .....                                                                                                                | 499 |
| <i>Hui Zhang, Dong Liang, Linhao Ma, Zongle Ma, Qing Li, Keping Wang</i>                                                                                                                                                                        |     |
| A Battery-Less Crystal-Less Event-Driven UWB Tag With Hybrid Power Management Network and PI-CDR-Based Wake-Up Receiver .....                                                                                                                   | 503 |
| <i>Bowen Wang, Rong Zhou, Jianhang Yang, Xianlong Xiong, Minsong Zhang, Nannan Shi, Xin An Zhangming Zhu</i>                                                                                                                                    |     |
| An 802.11b-WiFi Backscatter Modulator Featuring 30 dB PSLR with All-Digital Gaussian Pulse Shaping .....                                                                                                                                        | 507 |
| <i>Yongling Zhang, Miao Meng</i>                                                                                                                                                                                                                |     |
| A Fully Integrated 2.4GHz BLE Transmitter with ADPLL and Class-G Switched-Capacitor PA Achieving 30% System Efficiency .....                                                                                                                    | 511 |
| <i>Chen-Hsing Hsu, Yi-Chen Hsiao, Yu-Che Yang, Sheng-Chiang Tu, Yi-Chang Shih, Ka-Un Chan, Yu-Te Liao</i>                                                                                                                                       |     |